



TYPE 1

TYPE 2

Ordering Information:

A2543H-XP - **
1 2

1.Part No.

2.Style:

(blank)-Type 1/Beige

2-Type 2/White

SPECIFICATIONS:

Current Rating: 4A AC,DC

Voltage Rating: 250V AC,DC

Temperature Range: -40°C ~ +105°C

Contact Resistance: 10mΩ Max

Insulation Resistance: 1000MΩ Min

Withstanding Voltage: 1000V AC/minute

Material: Nylon 66,UL94V-0(Beige)

Ordering Information & Dimensions

Circuits	Dimensions(mm)		Circuits	Dimensions(mm)	
	A	B		A	B
2P	2.54	5.68	12P	27.94	31.08
3P	5.08	8.22	13P	30.48	33.62
4P	7.62	10.76	14P	33.02	36.16
5P	10.16	13.30	15P	35.56	38.70
6P	12.70	15.84	16P	38.10	41.24
7P	15.24	18.38	17P	40.64	43.78
8P	17.78	20.92	18P	43.18	46.32
9P	20.32	23.46	19P	45.72	48.86
10P	22.86	26.00	20P	48.26	51.40
11P	25.40	28.54			



CHANGJIANG CONNECTORS CO.,LTD.

Unit	Scale	Sheet
mm	4:1	1 of 1

Draw BY:	Approved :
LIZQ	GONGYB

General Tolerance

x.x≤0.25	ANGLE±
x.xx≤0.20	
x.xxx≤0.15	

Title :	
2.54mm PITCH	
HOUSING	
DRAW NO :	A2543H-XP
REV	A0

A0	NEW RELEEASE	2005.05.10
REV	DESCRIPTION	DATE