

Contact insert module - HC-M-RJ45-AD-PC-M - 1419885


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Contact insert module, number of positions: RJ45, type : RJ45, Pin, 50 V, 1 A, application: Data, with adapter for patch cables



Key Commercial Data

| | |
|--------------|---|
| Packing unit | 1 pc |
| GTIN |  4 055626 253237 |
| GTIN | 4055626253237 |

Technical data

Dimensions

| | |
|--------|---------|
| Height | 50.7 mm |
| Width | 34.2 mm |
| Length | 14.6 mm |

Electrical characteristics

| | |
|---|--------|
| Rated voltage (III/3) | 50 V |
| Rated current | 1 A |
| Rated surge voltage | 0.8 kV |
| Connection profile | RJ45 |
| Transmission characteristics (category) | CAT6 |

Ambient conditions

| | |
|---------------------------------|------------------|
| Ambient temperature (operation) | -25 °C ... 60 °C |
|---------------------------------|------------------|

Mechanical characteristics

| | |
|-----------------------------|-------|
| Insertion/withdrawal cycles | ≥ 500 |
|-----------------------------|-------|

General

| | |
|------|--|
| Note | Use the patch cable from the accessories list. |
| Type | RJ45 |

Contact insert module - HC-M-RJ45-AD-PC-M - 1419885

Technical data

General

| | |
|--|---|
| Series | HC-M-RJ45 |
| Color | light gray |
| Number of module slots | 1 |
| Flammability rating according to UL 94 | V0 |
| Degree of pollution | 3 |
| Overvoltage category | III |
| Assembly instructions | To ensure correct use, installation in housing with IP54 protection or better is required |

Material data

| | |
|--------------------------|--------------|
| Contact material | Copper alloy |
| Contact surface material | Au |
| Contact carrier material | PC |

Standards and Regulations


| | |
|--|----|
| Flammability rating according to UL 94 | V0 |
|--|----|

Environmental Product Compliance

| | |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
| | No hazardous substances above threshold values |

Drawings

Dimensional drawing



Male insert

Approvals

Approvals

Approvals

CSA / UL Recognized / EAC


Ex Approvals


Contact insert module - HC-M-RJ45-AD-PC-M - 1419885

Approvals

Approval details

| | | | |
|-----|---|---|-------|
| CSA |  | http://www.csagroup.org/services-industries/product-listing/ | 13631 |
|-----|---|---|-------|

| | | | |
|---------------|---|---|---------|
| UL Recognized |  | http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm | E118976 |
|---------------|---|---|---------|

| | | | |
|-----|---|--|--------------------------|
| EAC |  | | RU C- DE.AI30.B.01102 |
|-----|---|--|--------------------------|

Phoenix Contact 2018 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>