HC-ADV-B06-HHWH-1TTM32-EMC-AL - Housing

1413376

https://www.phoenixcontact.com/us/products/1413376

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



HEAVYCON ADVANCE sleeve housing, B6, with stainless steel screw locking (Allen screw), salt-water-resistant aluminum, height 93.7 mm, with 1x M32 thread, straight cable outlet, without surface; conductive seal (EMC properties)

Commercial data

Item number	1413376
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	BF58
Product key	BF7APH
Catalog page	Page 597 (C-2-2019)
GTIN	4055626030210
Weight per piece (including packing)	233.233 g
Weight per piece (excluding packing)	233.233 g
Customs tariff number	85389099
Country of origin	CN

Technical data

Notes

General	For contact inserts HC-B6, BB10, DD24, M


Product properties

Product type	Housing with screw locking
Housing type	Sleeve housing
Product family	HC-ADV
Application	Offshore/EMC
Type	B6
No. of cable outlets	1
Type of the screw connection	1x M32
Type	Tall design
Fixing screws	M6 (screw head: 5 mm Allen screw)
Cable outlet	straight
Pg screw connection	none

Connection data

Tightening torque	3 Nm ... 5 Nm (for M6 mounting screws on the sleeve housing)

Dimensions

Dimensional drawing	
Width	57 mm
Height	93.7 mm
Length	92 mm

Installation dimensions

Width of the assembly cutout	35 mm
Length of the assembly cutout	52 mm

Material specifications

Seal material	NBR, conductive
Housing material	Die-cast aluminum, salt water resistant
Housing surface material	uncoated
Locking latch material	Stainless steel

Environmental and real-life conditions

Ambient conditions

	IP66

Degree of protection	IP68 (0.2 bar/24 h)
	IP69 (ISO 20653:2013-02)
Enclosure rating (NEMA)	4 (UL 50e)
	4X (UL 50e)
	12 (UL 50e)
Impact strength	IK09
Ambient temperature (operation)	-40 °C ... 125 °C

Mechanical properties

Mechanical data


Type of the screw connection	1x M32
Locking type	Screw

Mounting

Assembly note	In order to guarantee that the protective conductor contact functions even when plugged in at an angle, the two panel-mount flanges must have sufficient electrical contact with the metal mounting panel.
Fixing screws	M6 (screw head: 5 mm Allen screw)


Drawings

Dimensional drawing



Mounting cutout
1) when M4 screws are used
2) when self-tapping Torx® screws are used (Torx® 20, M4)

Dimensional drawing



Dimensional drawing

Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/us/products/1413376

DNV
Approval ID: TAE000037S

cUL Recognized
Approval ID: E255026

UL Recognized
Approval ID: E255026

EAC
Approval ID: RU C-DE.AI30.B.01102

EAC
Approval ID: RU C-DE.BL08.B.00511

cULus Recognized

Classifications

ECLASS

ECLASS-11.0	27440202
ECLASS-12.0	27440202
ECLASS-13.0	27440202

ETIM

ETIM 9.0	EC000437

UNSPSC

UNSPSC 21.0	31261500

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions

China RoHS

Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Accessories

HC-B-AF - Panel-mount flange

1686533

https://www.phoenixcontact.com/us/products/1686533




Panel-mount flange for HEAVYCON ADVANCE housing

HC-B-AF-SET - Panel-mount flange

1604638

https://www.phoenixcontact.com/us/products/1604638



Panel-mount flange for HEAVYCON ADVANCE housing, set consisting of: 2 panel-mount flanges with 4 self-tapping screws (M4, Torx®) and 4 fan-type washers

HC-B 6-TMS-SD-IP50 - Protective cover

1690736

https://www.phoenixcontact.com/us/products/1690736



Protective cover B6, with clip locking, protective cover material: PA, height: 31.2 mm, seal: no, with lanyard

HC-B 6-TMS-SD-IP66 - Protective cover

1411494

https://www.phoenixcontact.com/us/products/1411494



HEAVYCON ADVANCE, IP66, B6 protective cover for panel mounting side, with screw locking, with retaining cord, diameter of retaining cord eyelet: 3 mm

G-INS-M32-M68N-PNES-GY - Cable gland

1411127

https://www.phoenixcontact.com/us/products/1411127



Cable gland, material for screw connection: PA, application: Standard, external cable diameter 15 mm ... 21 mm, shielding: no, connecting thread: M32 x 1.5, color: silver-grey RAL 7001

G-INS-M32-M68N-NNES-S - Cable gland

1411166

https://www.phoenixcontact.com/us/products/1411166



Cable gland, material for screw connection: Brass, nickel-plated, application: Standard, external cable diameter 15 mm ... 21 mm, shielding: no, connecting thread: M32 x 1.5, color: silver, with O-ring

HC-M-KV-M32(19-27) - Cable gland

1646010

https://www.phoenixcontact.com/us/products/1646010



Metal screw connection up to 5 bar, thread length: 8 mm, cable diameter: 19 - 27 mm, WAF 43, screw connection: M32

US-EMLP-HA (20X9) - Plastic label

0830989

https://www.phoenixcontact.com/us/products/0830989



Plastic label, Card, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: adhesive, lettering field size: 20 x 9 mm, Number of individual labels: 70

US-EMLP-HA (20X9) CUS - Plastic label

0830995

https://www.phoenixcontact.com/us/products/0830995



Plastic label, Card, white, labeled, can be labeled with: THERMOMARK CARD, mounting type: adhesive, lettering field size: 20 x 9 mm, Number of individual labels: 70

WP-G HF IP66 M32 BK - Screw connection

3240900

https://www.phoenixcontact.com/us/products/3240900



Cable gland, metric thread, IP66 protection, straight

WP-G HF IP69K M32 BK - Screw connection

3240886

https://www.phoenixcontact.com/us/products/3240886



Cable gland, metric thread, IP68/69k protection, straight

WP-GA HF IP66 M32 BK - Screw connection

3240928

https://www.phoenixcontact.com/us/products/3240928



Cable gland, metric thread, IP66 protection, angled

WP-GA HF IP69K M32 BK - Screw connection

3240914

https://www.phoenixcontact.com/us/products/3240914



Cable gland, metric thread, IP68/69k protection, angled

WP-GR HF IP66 M32 BK - Screw connection

3240956

https://www.phoenixcontact.com/us/products/3240956



Cable gland, metric thread, IP66 protection, with strain relief

WP-GR HF IP69K M32 BK - Screw connection

3240942

https://www.phoenixcontact.com/us/products/3240942



Cable gland, metric thread, IP68/69k protection, with strain relief

WP-G PP HF M32 - Screw connection

3241000

https://www.phoenixcontact.com/us/products/3241000



Cable gland made from PP with metric thread, IP65 protection

WP-GT PP HF M32 - Screw connection

3241014

https://www.phoenixcontact.com/us/products/3241014



Cable gland made from PP with metric thread, rotatable, IP54 protection

WP-G BRASS IP40 M32 - Screw connection

3241049

https://www.phoenixcontact.com/us/products/3241049



Cable gland made from brass with metric thread, IP40 protection

WP-GT BRASS M32 - Screw connection

3241035

https://www.phoenixcontact.com/us/products/3241035



Cable gland made from brass with metric thread, rotatable, IP40 protection

WP-G BRASS IP65 M32 - Screw connection

3241063

https://www.phoenixcontact.com/us/products/3241063



Cable gland made from brass with metric thread, IP65 protection

SF-BIT-HEXB 5-89 - Screw insert

1208911

https://www.phoenixcontact.com/us/products/1208911



Screw bit, hexagonal with ball head, E6.3-1/4" drive, size: Hex 5 x 89 mm, hardened, suitable for holder according to DIN 3126-F 6.3/ISO 1173

SF-M BH - Screwdriver

1212070

https://www.phoenixcontact.com/us/products/1212070



Bit screwdriver, with 1/4" quick-action chuck, handle length 119 mm, 2-component handle, with non-slip grip, suitable for bits according to DIN 3126-C 6.3 and E 6.3/ISO 1173, magnetic

Phoenix Contact 2024 © - all rights reserved
https://www.phoenixcontact.com

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com