



孔位	A	B	C	E
2	1.25	7.25	7.65	3.05
3	2.50	8.50	8.90	4.30
4	3.75	9.75	10.15	5.55
5	5.00	11.00	11.40	6.80
6	6.25	12.25	12.65	8.05
7	7.50	13.50	13.90	9.30
8	8.75	14.75	15.15	10.55
9	10.00	16.00	16.40	11.80
10	11.25	17.25	17.65	13.05
11	12.50	18.50	18.90	14.30
12	13.75	19.75	20.15	15.55
13	15.00	21.00	21.40	16.80
14	16.25	22.25	22.65	18.05
15	17.50	23.50	23.90	19.30
16	18.75	24.75	25.15	20.55

性能：  
 额定电流：1A  
 额定电压：100V  
 耐电压：500V  
 接触电阻： $\leq 20m\Omega$   
 绝缘电阻： $500M\Omega$   
 工作温度： $-20^{\circ}C \sim +85^{\circ}C$   
 塑件 (材质)：LCP, UL94V-0  
 插簧 (材质)：磷青铜, 镀锡/  
 焊片 (材质)：磷青铜, 镀锡/

深圳市钜硕电子有限公司

UNLESS OTHERWISE SPECIFIED TOLERANCES ARE		APPROVED	DATE	PART NO.	1.25-D-nPWB
△	X.X	CHECKED	DATE	DRAWING NO.	JUSHUO
△	X.XX	DATE	2004.6.16	COMPUTER NO.	
△	X.XXX	SCALE	SIZE	NAME	
△	ANG.	UNIT	MM	REV	A
△					
SER	AREA	REVISIONS	CHK	DATE	