

Tel : +44 118 979 1238
Fax : +44 118 979 1283
Email: info@actcrystals.com

The **ACTF458C/458.0/F11** is a low-loss, compact, and economical surface-acoustic-wave (**SAW**) filter in a low-profile metal **F-11** case, for mobile radio applications, with a centre frequency of **458.000** MHz.

1. Package Dimension (F-11)






2.

Pin	Configuration
1	Input / Output
4	Output / Input
2/3	Case Ground

Dimensions	Data (unit: mm)
A	11.0±0.3
B	4.5±0.3
C	3.2±0.3
D	0.45±0.1
E	5.0±0.5
F	2.54±0.2


3. Test Circuit



In keeping with our ongoing policy of product evolvement and improvement, the above specification is subject to change without notice.

Tel : +44 118 979 1238
Fax : +44 118 979 1283
Email: info@actcrystals.com

4. Typical Frequency Response



5. Performance

5-1. Maximum Ratings

Rating		Value	Unit
RF Power Dissipation	P	0	dBm
DC Voltage	V_{DC}	10	V
Operable Temperature Range	T_A	-10 to +65	°C
Storage Temperature Range	T_{stg}	-40 to +85	°C

Advanced crystal technology

Tel : +44 118 979 1238
Fax : +44 118 979 1283
Email: info@actcrystals.com

5-2. Electronic Characteristics

Characteristic		Minimum	Typical	Maximum	Unit
Centre Frequency	f_C	--	458.000	--	MHz
User Signal Band	*BW*	--	±1.0	--	MHz
Insertion Loss f_C ± 1.0 MHz	*IL*	--	3.5	4.8	dB
Absolute Attenuation f_C -100.0 MHz to f_C -10.0 MHz f_C +6.0 MHz to f_C +23.0 MHz f_C +23.0 MHz to f_C +100.0 MHz	*α*	 38 22 40	 50 30 52	 -- --	 dB dB dB
Pass Band Ripple f_C ± 1.0 MHz	*Δα*	--	--	2.0	dB
Input / Output Impedance (Nominal)		50Ω // 0pF			

i CAUTION: Electrostatic Sensitive Device. Observe precautions for handling!

1. The frequency f_C is defined as the midpoint between the 3dB frequencies.
2. Unless noted otherwise, all measurements are made with the filter installed in the specified test fixture that is connected to a 50 Ω test system with VSWR ≤1.2:1. The test fixture L and C are adjusted for minimum insertion loss at the filter centre frequency, f_C. Note that insertion loss, bandwidth, and passband shape are dependent on the impedance matching component values and quality.
3. Unless noted otherwise, specifications apply over the entire specified operating temperature range.
4. The specifications of this device are based on the test circuit shown above and subject to change or obsolescence without notice.
5. All equipment designs utilizing this product must be approved by the appropriate government agency prior to manufacture or sale.
6. Our liability is only assumed for the Surface Acoustic Wave (SAW) component(s) per se, not for applications, processes and circuits implemented within components or assemblies.
7.