



RECOMMENDED P.C.B HOLE LAYOUT
COMPONENT SIDE VIEW(TOLERANCE: +/-0.05)

REV.	DESCRIPTION	NAME	DATE
A	NEWS ISSUE	LXH	2018/01/18

说明:

1. 材质:
胶芯: LCP, UL94V-0; COLOR: BLACK
端子: C2680

外壳: SPCC/C2680
2. 电镀说明:

端子: 接触区域镀金
焊锡区域镀锡100 u"Min
全部区域镀底50 u" Min
外壳: 表面镀镍100 u" Min

3. 电气性能:
绝缘阻抗 (EIA-364-21) : 100 MΩ MIN.
AT 500V/DC FOR 1 MINUTE.
接触阻抗 (EIA-364-06) 30 mΩ MAX.
耐电压 (EIA-364-20) NO DISCHARGE,
FLASHOVER OR BREAKDOWN
AT 500 V/AC 1MINUTE.

TOLERANCE UNSPECIFIED		TITLE:	
.0	±0.35	深圳市金航标电子有限公司	WWW.BDS666.COM
.00	±0.25	KH-HDMI-19P-CU	0755-83044319
.000	±0.15		
1"	±2.00"		
CUSTOMER DRAWING			
DATE	DATE	SIZE: A4	UNIT: mm
DRAWN	2018/01/18		
LXH			
DATE	DATE	SCALE: 1:1	PROJECTION
CHECKED	2018/01/18		
LCY			
DATE	DATE	DWG	PATH
APPROVED	2018/01/18		
LCY			
		PART. NO:	HAXX-NLX-X1-1
		REV. :	A
		C00-0000-0024	1/3