







flow90PIM 1	1200V/4A				
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr style="background-color: #000080; color: white;"> <th style="padding: 2px;">Features</th> </tr> <tr> <td style="padding: 2px;"> <ul style="list-style-type: none"> Trench Fieldstop Technology IGBT4 for low saturation loss Supports design with 90° mounting angle between heatsink and PCB Clip-in PCB mounting Clip or screw on heatsink mounting </td> </tr> </table>	Features	<ul style="list-style-type: none"> Trench Fieldstop Technology IGBT4 for low saturation loss Supports design with 90° mounting angle between heatsink and PCB Clip-in PCB mounting Clip or screw on heatsink mounting 	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr style="background-color: #000080; color: white;"> <th style="padding: 2px;">flow90PIM 1</th> </tr> <tr> <td style="text-align: center; padding: 5px;">  </td> </tr> </table>	flow90PIM 1	
Features					
<ul style="list-style-type: none"> Trench Fieldstop Technology IGBT4 for low saturation loss Supports design with 90° mounting angle between heatsink and PCB Clip-in PCB mounting Clip or screw on heatsink mounting 					
flow90PIM 1					
					
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr style="background-color: #000080; color: white;"> <th style="padding: 2px;">Target Applications</th> </tr> <tr> <td style="padding: 2px;"> <ul style="list-style-type: none"> Industrial drives </td> </tr> </table>	Target Applications	<ul style="list-style-type: none"> Industrial drives 	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr style="background-color: #000080; color: white;"> <th style="padding: 2px;">Schematic</th> </tr> <tr> <td style="text-align: center; padding: 5px;">  </td> </tr> </table>	Schematic	
Target Applications					
<ul style="list-style-type: none"> Industrial drives 					
Schematic					
					
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr style="background-color: #000080; color: white;"> <th style="padding: 2px;">Types</th> </tr> <tr> <td style="padding: 2px;"> <ul style="list-style-type: none"> V23990-P638-A40-PM </td> </tr> </table>	Types	<ul style="list-style-type: none"> V23990-P638-A40-PM 			
Types					
<ul style="list-style-type: none"> V23990-P638-A40-PM 					

Maximum Ratings

$T_j=25^{\circ}\text{C}$, unless otherwise specified

Parameter	Symbol	Condition	Value	Unit
Input Rectifier Diode				
Repetitive peak reverse voltage	V_{RRM}		1600	V
DC forward current	I_{FAV}	$T_j=T_{j,max}$ $T_h=80^{\circ}\text{C}$ $T_c=80^{\circ}\text{C}$	28 36	A
Surge forward current	I_{FSM}	$t_p=10\text{ms}$ $T_j=25^{\circ}\text{C}$	200	A
I2t-value	I^2t		200	A^2s
Power dissipation per Diode	P_{tot}	$T_j=T_{j,max}$ $T_h=80^{\circ}\text{C}$ $T_c=80^{\circ}\text{C}$	33 50	W
Maximum Junction Temperature	$T_{j,max}$		150	$^{\circ}\text{C}$

Inverter Transistor				
Collector-emitter break down voltage	V_{CE}		1200	V
DC collector current	I_C	$T_j=T_{j,max}$ $T_h=80^{\circ}\text{C}$ $T_c=80^{\circ}\text{C}$	9 9	A
Repetitive peak collector current	I_{Cpulse}	t_p limited by $T_{j,max}$	12	A
Turn off safe operating area		$V_{CE} \leq 1200\text{V}$, $T_j \leq T_{op\ max}$	12	A
Power dissipation per IGBT	P_{tot}	$T_j=T_{j,max}$ $T_h=80^{\circ}\text{C}$ $T_c=80^{\circ}\text{C}$	39 60	W
Gate-emitter peak voltage	V_{GE}		± 20	V
Short circuit ratings	t_{SC} V_{CC}	$T_j \leq 150^{\circ}\text{C}$ $V_{GE} = 15\text{V}$	10 800	μs V
Maximum Junction Temperature	$T_{j,max}$		175	$^{\circ}\text{C}$

Maximum Ratings

 $T_j=25^{\circ}\text{C}$, unless otherwise specified

Parameter	Symbol	Condition	Value	Unit
-----------	--------	-----------	-------	------

Inverter FWD

Peak Repetitive Reverse Voltage	V_{RRM}		1200	V
DC forward current	I_F	$T_j=T_{jmax}$ $T_h=80^{\circ}\text{C}$ $T_c=80^{\circ}\text{C}$	18 23	A
Repetitive peak forward current	I_{FRM}	t_p limited by T_{jmax}	20	A
Power dissipation per Diode	P_{tot}	$T_j=T_{jmax}$ $T_h=80^{\circ}\text{C}$ $T_c=80^{\circ}\text{C}$	42 63	W
Maximum Junction Temperature	T_{jmax}		175	$^{\circ}\text{C}$

Brake Transistor

Collector-emitter break down voltage	V_{CE}		1200	V
DC collector current	I_C	$T_j=T_{jmax}$ $T_h=80^{\circ}\text{C}$ $T_c=80^{\circ}\text{C}$	9 9	A
Repetitive peak collector current	I_{Cpuls}	t_p limited by T_{jmax}	12	A
Turn off safe operating area		$V_{CE} \leq 1200\text{V}$, $T_j \leq T_{jmax}$	12	A
Power dissipation per IGBT	P_{tot}	$T_j=T_{jmax}$ $T_h=80^{\circ}\text{C}$ $T_c=80^{\circ}\text{C}$	39 59	W
Gate-emitter peak voltage	V_{GE}		± 20	V
Short circuit ratings	t_{SC} V_{CC}	$T_j \leq 150^{\circ}\text{C}$ $V_{GE} = 15\text{V}$	10 800	μs V
Maximum Junction Temperature	T_{jmax}		175	$^{\circ}\text{C}$

Brake FWD

Peak Repetitive Reverse Voltage	V_{RRM}		1200	V
DC forward current	I_F	$T_j=T_{jmax}$ $T_h=80^{\circ}\text{C}$ $T_c=80^{\circ}\text{C}$	7 7	A
Repetitive peak forward current	I_{FRM}	t_p limited by T_{jmax}	6	A
Power dissipation per Diode	P_{tot}	$T_j=T_{jmax}$ $T_h=80^{\circ}\text{C}$ $T_c=80^{\circ}\text{C}$	31 38	W
Maximum Junction Temperature	T_{jmax}		175	$^{\circ}\text{C}$

Thermal Properties

Storage temperature	T_{stg}		-40...+125	$^{\circ}\text{C}$
Operation temperature under switching condition	T_{op}		-40...+($T_{jmax} - 25$)	$^{\circ}\text{C}$

Insulation Properties

Insulation voltage	V_{is}	$t=2\text{s}$ DC voltage	4000	V
Creepage distance			min 12,7	mm
Clearance			min 12,7	mm
Comparative tracking index	CTI		>200	

Characteristic Values

Parameter	Symbol	Conditions					Value			Unit
		$V_{GE}[V]$ or $V_{GS}[V]$	$V_r[V]$ or $V_{CE}[V]$ or $V_{DS}[V]$	$I_c[A]$ or $I_F[A]$ or $I_b[A]$	T_j	Min	Typ	Max		
Input Rectifier Diode										
Forward voltage	V_F				30	$T_j=25^\circ\text{C}$ $T_j=125^\circ\text{C}$	1	1,26 1,24	1,6	V
Threshold voltage (for power loss calc. only)	V_{to}				30	$T_j=25^\circ\text{C}$ $T_j=125^\circ\text{C}$		0,92 0,82		V
Slope resistance (for power loss calc. only)	r_t				30	$T_j=25^\circ\text{C}$ $T_j=125^\circ\text{C}$		11 14		m Ω
Reverse current	I_r			1500		$T_j=25^\circ\text{C}$ $T_j=125^\circ\text{C}$			0,2	mA
Thermal resistance chip to heatsink per chip	R_{thJH}	Thermal grease thickness \leq 50um $\lambda = 1$ W/mK						2,10		K/W
Inverter Transistor										
Gate emitter threshold voltage	$V_{GE(th)}$	$V_{CE}=V_{GE}$			0,00015	$T_j=25^\circ\text{C}$ $T_j=150^\circ\text{C}$	5	5,8	6,5	V
Collector-emitter saturation voltage	$V_{CE(sat)}$		15		4	$T_j=25^\circ\text{C}$ $T_j=150^\circ\text{C}$	1,6	1,87 2,20	2,3	V
Collector-emitter cut-off current incl. Diode	I_{CES}		0	1200		$T_j=25^\circ\text{C}$ $T_j=150^\circ\text{C}$			0,0005	mA
Gate-emitter leakage current	I_{GES}		20	0		$T_j=25^\circ\text{C}$ $T_j=150^\circ\text{C}$			120	nA
Integrated Gate resistor	R_{gint}							none		Ω
Turn-on delay time	$t_{d(on)}$	$R_{goff}=64 \Omega$ $R_{gon}=64 \Omega$	± 15	600	4	$T_j=25^\circ\text{C}$		83		ns
Rise time	t_r					$T_j=150^\circ\text{C}$		77		
Turn-off delay time	$t_{d(off)}$					$T_j=25^\circ\text{C}$		26		
Fall time	t_f					$T_j=150^\circ\text{C}$		28		
Turn-on energy loss per pulse	E_{on}					$T_j=25^\circ\text{C}$		191		
Turn-off energy loss per pulse	E_{off}					$T_j=150^\circ\text{C}$		254		
Input capacitance	C_{ies}							250		pF
Output capacitance	C_{oss}	$f=1\text{MHz}$	0	25		$T_j=25^\circ\text{C}$		25		
Reverse transfer capacitance	C_{riss}							15		
Gate charge	Q_{Gate}		± 15	960	4	$T_j=25^\circ\text{C}$		28		nC
Thermal resistance chip to heatsink per chip	R_{thJH}	Thermal grease thickness \leq 50um $\lambda = 1$ W/mK						2,42		K/W
Inverter FWD										
Diode forward voltage	V_F				4	$T_j=25^\circ\text{C}$ $T_j=150^\circ\text{C}$	1,2	1,43 1,23	2,3	V
Peak reverse recovery current	I_{RRM}					$T_j=25^\circ\text{C}$ $T_j=150^\circ\text{C}$		4 6		A
Reverse recovery time	t_{rr}	$R_{gon}=64 \Omega$	± 15	600	4	$T_j=25^\circ\text{C}$		246		ns
Reverse recovered charge	Q_{rr}					$T_j=150^\circ\text{C}$		426		
Peak rate of fall of recovery current	$di(rec)max/dt$					$T_j=25^\circ\text{C}$		0,54		
Reverse recovered energy	E_{rec}					$T_j=150^\circ\text{C}$		1,20		μC
						$T_j=25^\circ\text{C}$		65		A/ μs
						$T_j=150^\circ\text{C}$		42		mWs
Thermal resistance chip to heatsink per chip	R_{thJH}	Thermal grease thickness \leq 50um $\lambda = 1$ W/mK						2,28		K/W

Characteristic Values


Parameter	Symbol	Conditions					Value			Unit
		$V_{GE}[V]$ or $V_{GS}[V]$	$V_r[V]$ or $V_{CE}[V]$ or $V_{DS}[V]$	$I_c[A]$ or $I_F[A]$ or $I_D[A]$	T_j	Min	Typ	Max		
Brake Transistor										
Gate emitter threshold voltage	$V_{GE(th)}$	$V_{CE}=V_{GE}$			0,00015	$T_j=25^\circ C$ $T_j=150^\circ C$	5	5,8	6,5	V
Collector-emitter saturation voltage	$V_{CE(sat)}$		15		4	$T_j=25^\circ C$ $T_j=150^\circ C$	1,6	1,87 2,21	2,3	V
Collector-emitter cut-off incl diode	I_{CES}		0	1200		$T_j=25^\circ C$ $T_j=150^\circ C$			0,0005	mA
Gate-emitter leakage current	I_{GES}		20	0		$T_j=25^\circ C$ $T_j=150^\circ C$			120	nA
Integrated Gate resistor	R_{gint}							none		Ω
Turn-on delay time	$t_{d(on)}$	$R_{gon}=64 \Omega$ $R_{goff}=64 \Omega$	± 15	600	4	$T_j=25^\circ C$		83		ns
Rise time	t_r					$T_j=150^\circ C$		79		
Turn-off delay time	$t_{d(off)}$					$T_j=25^\circ C$		28		
Fall time	t_f					$T_j=150^\circ C$		32		
Turn-on energy loss per pulse	E_{on}					$T_j=25^\circ C$		178		
Turn-off energy loss per pulse	E_{off}	$T_j=150^\circ C$		243						
Input capacitance	C_{ies}	f=1MHz	0	25		$T_j=25^\circ C$		250		pF
Output capacitance	C_{oss}							25		
Reverse transfer capacitance	C_{rss}							15		
Gate charge	Q_{Gate}		± 15	960	4	$T_j=25^\circ C$		28		nC
Thermal resistance chip to heatsink per chip	R_{thJH}	Thermal grease thickness $\leq 50\mu m$ $\lambda = 1 W/mK$						2,44		K/W
Brake FWD										
Diode forward voltage	V_F				3	$T_j=25^\circ C$ $T_j=150^\circ C$	1	1,67 1,74	2,3	V
Reverse leakage current	I_r			1200		$T_j=25^\circ C$ $T_j=150^\circ C$			250	μA
Peak reverse recovery current	I_{RRM}	$R_{gon}=64 \Omega$ $R_{goff}=64 \Omega$	± 15	600	4	$T_j=25^\circ C$		2,77		A
Reverse recovery time	t_{rr}					$T_j=150^\circ C$		3,62		
Reverse recovered charge	Q_{rr}					$T_j=25^\circ C$		357		
Peak rate of fall of recovery current	$di(rec)max/dt$					$T_j=150^\circ C$		649		
Reverse recovery energy	E_{rec}					$T_j=25^\circ C$		0,44		
		$T_j=150^\circ C$		0,44						
Thermal resistance chip to heatsink per chip	R_{thJH}	Thermal grease thickness $\leq 50\mu m$ $\lambda = 1 W/mK$						3,03		K/W
Thermistor										
Rated resistance	R					T=25 $^\circ C$		22000		Ω
Deviation of R100	$\Delta R/R$	R100=1486 Ω				T=100 $^\circ C$	-5		5	%
Power dissipation	P					T=25 $^\circ C$		200		mW
Power dissipation constant						T=25 $^\circ C$		2		mW/K
B-value	$B_{(25/50)}$	Tol. $\pm 3\%$				T=25 $^\circ C$		3950		K
B-value	$B_{(25/100)}$	Tol. $\pm 3\%$				T=25 $^\circ C$		3996		K
Vincotech NTC Reference									B	

Output Inverter

Figure 1 Output inverter IGBT

Typical output characteristics

$I_C = f(V_{CE})$




At
 $t_p = 250 \text{ } \mu\text{s}$
 $T_j = 25 \text{ } ^\circ\text{C}$
 V_{GE} from 7 V to 17 V in steps of 1 V

Figure 2 Output inverter IGBT

Typical output characteristics

$I_C = f(V_{CE})$




At
 $t_p = 250 \text{ } \mu\text{s}$
 $T_j = 150 \text{ } ^\circ\text{C}$
 V_{GE} from 7 V to 17 V in steps of 1 V

Figure 3 Output inverter IGBT

Typical transfer characteristics

$I_C = f(V_{GE})$




At
 $t_p = 250 \text{ } \mu\text{s}$
 $V_{CE} = 10 \text{ V}$

Figure 4 Output inverter FWD

Typical diode forward current as a function of forward voltage

$I_F = f(V_F)$




At
 $t_p = 250 \text{ } \mu\text{s}$
 \dot{Q}_S

Output Inverter

Figure 5 Output inverter IGBT

Typical switching energy losses
as a function of collector current

$$E = f(I_C)$$




With an inductive load at

$T_J =$	25/150	°C
$V_{CE} =$	600	V
$V_{GE} =$	±15	V
$R_{gon} =$	64	Ω
$R_{goff} =$	64	Ω

Figure 6 Output inverter IGBT

Typical switching energy losses
as a function of gate resistor

$$E = f(R_G)$$




With an inductive load at

$T_J =$	25/150	°C
$V_{CE} =$	600	V
$V_{GE} =$	±15	V
$I_C =$	4	A

Figure 7 Output inverter FWD

Typical reverse recovery energy loss
as a function of collector current

$$E_{rec} = f(I_C)$$




With an inductive load at

$T_J =$	25/150	°C
$V_{CE} =$	600	V
$V_{GE} =$	±15	V
$R_{gon} =$	64	Ω

Figure 8 Output inverter FWD

Typical reverse recovery energy loss
as a function of gate resistor

$$E_{rec} = f(R_G)$$



With an inductive load at


$T_J =$	25/150	°C
$V_{CE} =$	600	V
$V_{GE} =$	±15	V
$I_C =$	4	A

Output Inverter

Figure 9 Output inverter IGBT

Typical switching times as a function of collector current

$$t = f(I_C)$$




With an inductive load at

$T_j =$	150	°C
$V_{\text{CE}} =$	600	V
$V_{\text{GE}} =$	±15	V
$R_{\text{gon}} =$	64	Ω
$R_{\text{goff}} =$	64	Ω

Figure 10 Output inverter IGBT

Typical switching times as a function of gate resistor

$$t = f(R_G)$$




With an inductive load at

$T_j =$	150	°C
$V_{\text{CE}} =$	600	V
$V_{\text{GE}} =$	±15	V
$I_C =$	4	A

Figure 11 Output inverter FWD

Typical reverse recovery time as a function of collector current

$$t_{\text{rr}} = f(I_C)$$




At

$T_j =$	25/150	°C
$V_{\text{CE}} =$	600	V
$V_{\text{GE}} =$	±15	V
$R_{\text{gon}} =$	64	Ω

Figure 12 Output inverter FWD

Typical reverse recovery time as a function of IGBT turn on gate resistor

$$t_{\text{rr}} = f(R_{\text{gon}})$$



At


$T_j =$	25/150	°C
$V_R =$	600	V
$I_F =$	4	A
$V_{\text{GE}} =$	±15	V

Output Inverter

Figure 13 Output inverter FWD

Typical reverse recovery charge as a function of collector current

$$Q_{rr} = f(I_C)$$




At
 $T_j = 25/150$ °C
 $V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $R_{gon} = 64$ Ω

Figure 14 Output inverter FWD

Typical reverse recovery charge as a function of IGBT turn on gate resistor

$$Q_{rr} = f(R_{gon})$$




At
 $T_j = 25/150$ °C
 $V_R = 600$ V
 $I_F = 4$ A
 $V_{GE} = \pm 15$ V

Figure 15 Output inverter FWD

Typical reverse recovery current as a function of collector current

$$I_{RRM} = f(I_C)$$




At
 $T_j = 25/150$ °C
 $V_{CE} = 600$ V
 $V_{GE} = \pm 15$ V
 $R_{gon} = 64$ Ω

Figure 16 Output inverter FWD

Typical reverse recovery current as a function of IGBT turn on gate resistor

$$I_{RRM} = f(R_{gon})$$




At
 $T_j = 25/150$ °C
 $V_R = 600$ V
 $I_F = 4$ A
 $V_{GE} = \pm 15$ V

Output Inverter

Figure 17 Output inverter FWD

Typical rate of fall of forward and reverse recovery current as a function of collector current

$$di_f/dt, di_{rec}/dt = f(I_C)$$




At
 $T_j = 25/150 \text{ } ^\circ\text{C}$
 $V_{CE} = 600 \text{ V}$
 $V_{GE} = \pm 15 \text{ V}$
 $R_{gon} = 64 \text{ } \Omega$

Figure 18 Output inverter FWD

Typical rate of fall of forward and reverse recovery current as a function of IGBT turn on gate resistor

$$di_f/dt, di_{rec}/dt = f(R_{gon})$$




At
 $T_j = 25/150 \text{ } ^\circ\text{C}$
 $V_R = 600 \text{ V}$
 $I_F = 4 \text{ A}$
 $V_{GE} = \pm 15 \text{ V}$

Figure 19 Output inverter IGBT

IGBT transient thermal impedance as a function of pulse width

$$Z_{thJH} = f(t_p)$$



At
 $D = t_p / T$
 $R_{thJH} = 2,42 \text{ K/W}$


IGBT thermal model values

Thermal grease		Phase change material	
R (C/W)	Tau (s)	R (C/W)	Tau (s)
0,09	2,4E+00	0,07	2,0E+00
0,34	2,1E-01	0,27	1,7E-01
0,75	4,8E-02	0,61	3,9E-02
0,41	1,3E-02	0,33	1,1E-02
0,46	2,8E-03	0,37	2,2E-03
0,37	3,9E-04	0,30	3,1E-04

Figure 20 Output inverter FWD

FWD transient thermal impedance as a function of pulse width

$$Z_{thJH} = f(t_p)$$



At
 $D = t_p / T$
 $R_{thJH} = 2,28 \text{ K/W}$

FWD thermal model values


Thermal grease		Phase change material	
R (C/W)	Tau (s)	R (C/W)	Tau (s)
0,05	5,6E+00	0,04	4,5E+00
0,14	7,2E-01	0,12	5,8E-01
0,79	1,2E-01	0,64	9,6E-02
0,71	3,6E-02	0,57	2,9E-02
0,37	7,3E-03	0,30	5,9E-03
0,22	1,5E-03	0,18	1,2E-03

Output Inverter

Figure 21 Output inverter IGBT


Power dissipation as a function of heatsink temperature

$$P_{tot} = f(T_h)$$


At
 $T_j = 175 \text{ } ^\circ\text{C}$
Figure 22 Output inverter IGBT


Collector current as a function of heatsink temperature

$$I_C = f(T_h)$$


At
 $T_j = 175 \text{ } ^\circ\text{C}$
 $V_{GE} = 15 \text{ V}$
Figure 23 Output inverter FWD


Power dissipation as a function of heatsink temperature

$$P_{tot} = f(T_h)$$


At
 $T_j = 175 \text{ } ^\circ\text{C}$
Figure 24 Output inverter FWD

Forward current as a function of heatsink temperature

$$I_F = f(T_h)$$



At
 $T_j = 175 \text{ } ^\circ\text{C}$

Output Inverter

Figure 25 Output inverter IGBT

Safe operating area as a function of collector-emitter voltage

$$I_C = f(V_{CE})$$




At
 D = single pulse
 $T_h = 80$ °C
 $V_{GE} = \pm 15$ V
 $T_j = T_{jmax}$ °C

Figure 26 Output inverter IGBT

Gate voltage vs Gate charge

$$V_{GE} = f(Q_{GE})$$




At
 $I_C = 4$ A

Figure 27 Output inverter IGBT

Short circuit withstand time as a function of gate-emitter voltage

$$t_{sc} = f(V_{GE})$$




At
 $V_{CE} = 600$ V
 $T_j \leq 175$ °C

Figure 28 Output inverter IGBT


Typical short circuit collector current as a function of gate-emitter voltage

$$V_{GE} = f(Q_{GE})$$



At
 $V_{CE} \leq 600$ V
 $T_j = 175$ °C

Figure 29 IGBT

Reverse bias safe operating area

At

$$T_j = T_{jmax} - 25 \text{ } ^\circ\text{C}$$

$$U_{ocminus} = U_{ccplus}$$


Switching mode : 3 level switching

Brake

Figure 1 Brake IGBT

Typical output characteristics

$I_C = f(V_{CE})$




At
 $t_p = 250 \text{ } \mu\text{s}$
 $T_j = 25 \text{ } ^\circ\text{C}$
 V_{GE} from 7 V to 17 V in steps of 1 V

Figure 2 Brake IGBT

Typical output characteristics

$I_C = f(V_{CE})$




At
 $t_p = 250 \text{ } \mu\text{s}$
 $T_j = 150 \text{ } ^\circ\text{C}$
 V_{GE} from 7 V to 17 V in steps of 1 V

Figure 3 Brake IGBT

Typical transfer characteristics

$I_C = f(V_{GE})$




At
 $t_p = 250 \text{ } \mu\text{s}$
 $V_{CE} = 10 \text{ V}$

Figure 4 Brake FWD

Typical diode forward current as a function of forward voltage

$I_F = f(V_F)$




At
 $t_p = 250 \text{ } \mu\text{s}$

Brake

Figure 5 Brake IGBT

Typical switching energy losses
as a function of collector current

$$E = f(I_C)$$




With an inductive load at

$T_j =$	25/150	°C
$V_{CE} =$	600	V
$V_{GE} =$	±15	V
$R_{gon} =$	64	Ω
$R_{goff} =$	64	Ω

Figure 6 Brake IGBT

Typical switching energy losses
as a function of gate resistor

$$E = f(R_G)$$




With an inductive load at

$T_j =$	25/150	°C
$V_{CE} =$	600	V
$V_{GE} =$	±15	V
$I_C =$	4	A

Figure 7 Brake FWD

Typical reverse recovery energy loss
as a function of collector current

$$E_{rec} = f(I_C)$$




With an inductive load at

$T_j =$	25/150	°C
$V_{CE} =$	600	V
$V_{GE} =$	±15	V
$R_{gon} =$	64	Ω

Figure 8 Brake FWD

Typical reverse recovery energy loss
as a function of gate resistor

$$E_{rec} = f(R_G)$$



With an inductive load at


$T_j =$	25/150	°C
$V_{CE} =$	600	V
$V_{GE} =$	±15	V
$I_C =$	4	A

Brake

Figure 9 Brake IGBT

Typical switching times as a function of collector current

$t = f(I_c)$




With an inductive load at

$T_j =$	150	°C
$V_{CE} =$	600	V
$V_{GE} =$	±15	V
$R_{gon} =$	64	Ω
$R_{goff} =$	64	Ω

Figure 10 Brake IGBT

Typical switching times as a function of gate resistor

$t = f(R_g)$




With an inductive load at

$T_j =$	150	°C
$V_{CE} =$	600	V
$V_{GE} =$	±15	V
$I_c =$	4	A

Figure 11 Brake IGBT

IGBT transient thermal impedance as a function of pulse width

$Z_{thJH} = f(t_p)$




At	D =	t_p / T	
Thermal grease		Phase change material	
$R_{thJH} =$	2,44	K/W	$R_{thJH} =$ 1,98 K/W

Figure 12 Brake FWD

FWD transient thermal impedance as a function of pulse width

$Z_{thJH} = f(t_p)$




At	D =	t_p / T	
Thermal grease		Phase change material	
$R_{thJH} =$	3,03	K/W	$R_{thJH} =$ 2,46 K/W

Brake

Figure 13 Brake IGBT

Power dissipation as a function of heatsink temperature

$$P_{tot} = f(T_h)$$




At
 $T_j = 175$ °C

Figure 14 Brake IGBT

Collector current as a function of heatsink temperature

$$I_C = f(T_h)$$




At
 $T_j = 175$ °C
 $V_{GE} = 15$ V

Figure 15 Brake FWD

Power dissipation as a function of heatsink temperature

$$P_{tot} = f(T_h)$$




At
 $T_j = 175$ °C

Figure 16 Brake FWD

Forward current as a function of heatsink temperature

$$I_F = f(T_h)$$




At
 $T_j = 175$ °C

Input Rectifier Bridge

Figure 1 Rectifier diode


Typical diode forward current as a function of forward voltage

$$I_F = f(V_F)$$


At
 $t_p = 250 \text{ } \check{C}$
Figure 2 Rectifier diode


Diode transient thermal impedance as a function of pulse width

$$Z_{thJH} = f(t_p)$$


At
 $D = t_p / T$
 $R_{thJH} = 2,10 \text{ K/W}$
Figure 3 Rectifier diode


Power dissipation as a function of heatsink temperature

$$P_{tot} = f(T_h)$$


At
 $T_j = 150 \text{ } ^\circ\text{C}$
Figure 4 Rectifier diode

Forward current as a function of heatsink temperature

$$I_F = f(T_h)$$



At
 $T_j = 150 \text{ } ^\circ\text{C}$

Thermistor

Figure 1 Thermistor

Typical NTC characteristic
as a function of temperature

$$R_T = f(T)$$




Switching Definitions Output Inverter

General conditions


T_j	=	150 °C
R_{gon}	=	64 Ω
R_{goff}	=	64 Ω

Figure 1 Output inverter IGBT

Turn-off Switching Waveforms & definition of t_{doff} , t_{Eoff}
(t_{Eoff} = integrating time for E_{off})



$V_{GE}(0\%) =$	-15	V
$V_{GE}(100\%) =$	15	V
$V_C(100\%) =$	600	V
$I_C(100\%) =$	4	A
$t_{doff} =$	0,25	Ös
$t_{Eoff} =$	0,67	Ös

Figure 2 Output inverter IGBT

Turn-on Switching Waveforms & definition of t_{don} , t_{Eon}
(t_{Eon} = integrating time for E_{on})



$V_{GE}(0\%) =$	-15	V
$V_{GE}(100\%) =$	15	V
$V_C(100\%) =$	600	V
$I_C(100\%) =$	4	A
$t_{don} =$	0,08	Ös
$t_{Eon} =$	0,36	Ös

Figure 3 Output inverter IGBT

Turn-off Switching Waveforms & definition of t_f


$V_C(100\%) =$	600	V
$I_C(100\%) =$	4	A
$t_f =$	0,12	Ös


Figure 4 Output inverter IGBT

Turn-on Switching Waveforms & definition of t_r


$V_C(100\%) =$	600	V
$I_C(100\%) =$	4	A
$t_r =$	0,03	Ös


Switching Definitions Output Inverter

Figure 5 Output inverter IGBT

Turn-off Switching Waveforms & definition of t_{Eoff}



$P_{off} (100\%) = 2,41 \text{ kW}$
 $E_{off} (100\%) = 0,39 \text{ mJ}$
 $t_{Eoff} = 0,67 \text{ } \mu\text{s}$

Figure 6 Output inverter IGBT

Turn-on Switching Waveforms & definition of t_{Eon}



$P_{on} (100\%) = 2,41 \text{ kW}$
 $E_{on} (100\%) = 0,63 \text{ mJ}$
 $t_{Eon} = 0,36 \text{ } \mu\text{s}$

Figure 7 Output inverter FWD

Gate voltage vs Gate charge (measured)


$V_{GEoff} = -15 \text{ V}$
 $V_{GEon} = 15 \text{ V}$
 $V_C (100\%) = 600 \text{ V}$
 $I_C (100\%) = 4 \text{ A}$
 $Q_g = 40,33 \text{ nC}$

Figure 8 Output inverter IGBT


Turn-off Switching Waveforms & definition of t_{rr}


$V_d (100\%) = 600 \text{ V}$
 $I_d (100\%) = 4 \text{ A}$
 $I_{RRM} (100\%) = -6 \text{ A}$
 $t_{rr} = 0,43 \text{ } \mu\text{s}$

Switching Definitions Output Inverter

Figure 9 Output inverter FWD


Turn-on Switching Waveforms & definition of t_{Qrr}
 (t_{Qrr} = integrating time for Q_{rr})



I_d (100%) = 4 A
 Q_{rr} (100%) = 1,20 \check{C}
 t_{Qrr} = 0,86 \check{S}

Figure 10 Output inverter FWD

Turn-on Switching Waveforms & definition of t_{Erec}
 (t_{Erec} = integrating time for E_{rec})





P_{rec} (100%) = 2,41 kW
 E_{rec} (100%) = 0,43 mJ
 t_{Erec} = 0,86 \check{S}

Ordering Code and Marking - Outline - Pinout
Ordering Code & Marking

Version	Ordering Code	in DataMatrix as	in packaging barcode as
without thermal paste	V23990-P638-A40-PM	P638-A40	P638-A40

Outline

Pin	Pin table	
	X	Y
1	53	0
2	46	0
3	39,5	0
4	32,5	0
5	28,1	0
6	18	0
7	15	0
8	12	0
9	9	0
10	3	0
11	0	0
12	0	7
13	3	7
14	8,5	7
15	11,5	7
16	17	7
17	20	7
18	33	7
19	36	7
20	39	7
21	46	7
22	53	7


Pinout


DISCLAIMER

The information given in this datasheet describes the type of component and does not represent assured characteristics. For tested values please contact Vincotech. Vincotech reserves the right to make changes without further notice to any products herein to improve reliability, function or design. Vincotech does not assume any liability arising out of the application or use of any product or circuit described herein; neither does it convey any license under its patent rights, nor the rights of others.

LIFE SUPPORT POLICY

Vincotech products are not authorised for use as critical components in life support devices or systems without the express written approval of Vincotech.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in labelling can be reasonably expected to result in significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.