

DISCRIMINATOR

Ceramic Discriminator for Communications Equipment

muRata

High Performance Ceramic Discriminator for Various Mobile Communication Equipment


Ceramic discriminator consists of wide band piezoelectric resonator. It is ideal for mobile communication equipments due to its small size and light weight. Standard line include products for wide range of application, from cordless telephone to cellular telephone, making non-adjustment and shrinking of the detection circuit possible.

■FEATURES


1. Small in size and light weight.
2. Realize non-adjustment in detection circuit.
3. High sensitivity and stability.
4. Wide range of standard products are available for various ICs.
5. Operating temperature range : -20°C to $+80^{\circ}\text{C}$
Storage temperature range : -40°C to $+85^{\circ}\text{C}$

■DIMENSIONS


● CDB455C□/CDB455CL□




● CDBM455C□/CDBM455CL□



● CDBM455C□



● CDBC455CX□/CDBC455CLX□



*Refer to the IC list in the next page for suffix number in □.

■ ELECTRICAL CHARACTERISTICS

● Impedance Curve Specification

Character-istics Part Number	Resonant Frequency (Fr)	Antiresonant Frequency (Fa)	$\Delta F(Fa-Fr)$	Resonant Resistance (R1)	Capacitance (C)	I C	Application
CDBM455C2	447±1.5kHz ($ \dot{Z} =2.05k\Omega$) 463±1.5kHz ($ \dot{Z} =10.0k\Omega$)				140pF±20%	TA8104	Pager
CDBC455CX2	447±1.5kHz ($ \dot{Z} =0.80k\Omega$) 463±1.5kHz ($ \dot{Z} =3.65k\Omega$)				280pF±20%		
CDB455C3	—	455 ±1.5kHz	48±5.0kHz	70 Ω max.	600pF±20%	CXA1184M	Pager
CDBM455C3	—	455 ±1.5kHz	46±5.0kHz	70 Ω max.	550pF±20%		
CDBM455C4	—	470 ±1.0kHz	43±2.0kHz	300 Ω max.	140pF±20%	LA8610	Pager
CDB455C10	429±2kHz	—	51±5.0kHz	70 Ω max.	580pF±20%	TA8103F	Cordless Telephone
CDBM455C10	429±2kHz	—	51±5.0kHz	70 Ω max.	580pF±20%		
CDBM455C15	—	463.5±1kHz	43±2.0kHz	300 Ω max.	140pF±20%	CXA1183M	Cordless Telephone
CDBM455C25	—	465 ±1.5kHz	45±4.0kHz	300 Ω max.	135pF±20%	CXA1484	Pager
CDBM455C31	447±1.5kHz ($ \dot{Z} =2.05k\Omega$) 463±1.5kHz ($ \dot{Z} =10.0k\Omega$)				140pF±20%	TA31141	Pager
CDBC455CX31	447±1.5kHz ($ \dot{Z} =0.80k\Omega$) 463±1.5kHz ($ \dot{Z} =3.65k\Omega$)				280pF±20%		
CDBM455C33	—	465±1.5kHz	45±4.0kHz	300 Ω max.	135pF±20%	CXA1474	Pager

● Recovered Audio Curve Specification


Character-istics Part Number	Recovered Audio 3dB Bandwidth (from 455kHz)	Recovered Audio Output (at 455kHz)	Distortion		I C	Application
			at 455kHz	within 455±8kHz		
CDB455C7	±4.0kHzmin.	340±60mV	2.5%max.	—	MC3357	Cordless Telephone, Communications Equipment
CDBM455C7	±4.0kHzmin.	340±60mV	3.0%max.	—		
CDBC455CX7	±4.0kHzmin.	350±60mV	3.0%max.	—		
CDB455C9	±5.0kHzmin.	100mVmin.	1.5%max.	—	NE604N	Cordless Telephone, Cellular Phone, Communications Equipment
CDBM455C9	±5.0kHzmin.	100mVmin.	1.5%max.	—		
CDBC455CX9	±4.0kHzmin.	120±40mV	1.5%max.	—		
CDB455CL9	±15.0kHzmin.	70±20mV	1.5%max.	3.5%max.		
CDBM455CL9	±15.0kHzmin.	70±20mV	1.5%max.	3.5%max.		
CDB455C13A	±4.0kHzmin.	350±50mV	3.0%max.	—	CXA1003BM	Cellular Phone, Communications Equipment
CDBM455C13A	±4.0kHzmin.	350±50mV	3.0%max.	—		
CDBC455CX13	±4.0kHzmin.	330±50mV	4.0%max.	—		
CDB455CL13	±15.0kHzmin.	110±30mV	1.5%max.	5.0%max.		
CDBM455CL13	±15.0kHzmin.	110±30mV	1.5%max.	5.0%max.		
CDBC455CLX13	±13.0kHzmin.	120±30mV	1.5%max.	5.0%max.	MC3372	Cellular Phone, Cordless Telephone, Communications Equipment
CDB455C16	±4.0kHzmin.	185±40mV	2.0%max.	—		
CDBM455C16	±4.0kHzmin.	185±40mV	2.0%max.	—		
CDBC455CX16	±4.0kHzmin.	175±40mV	2.0%max.	—	MC3371	Cordless Telephone, Communications Equipment
CDBM455C18	±3.0kHzmin.	180±40mV	2.0%max.	—		
CDB455C21	±4.0kHzmin.	55±20mV	2.0%max.	—	TA31132	Cordless Telephone, Cellular Phone, Communications Equipment
CDBM455C21	±4.0kHzmin.	55±20mV	2.0%max.	—		
CDBC455CX21	±4.0kHzmin.	55±20mV	2.0%max.	—		
CDB455CL21	±13.0kHzmin.	65±20mV	2.5%max.	5.0%max.		
CDBM455CL21	±13.0kHzmin.	65±20mV	2.5%max.	5.0%max.		
CDBC455CLX21	±11.0kHzmin.	75±25mV	2.5%max.	5.0%max.	TA31136	Cordless Telephone, Communications Equipment
CDB455C24	±4.0kHzmin.	100±40mV	2.0%max.	—		
CDBM455C24	±4.0kHzmin.	100±40mV	2.0%max.	—		
CDBC455CX24	±4.0kHzmin.	100±40mV	2.0%max.	—	TK10487	Cordless Telephone, Communications Equipment
CDB455C27	±4.0kHzmin.	100±40mV	2.0%max.	—		
CDBM455C27	±4.0kHzmin.	100±40mV	2.0%max.	—		
CDBC455CX27	±4.0kHzmin.	90±30mV	2.0%max.	—	TA31142	Pager
CDB455C28	±4.0kHzmin.	40±20mV	3.0%max.	—		
CDBM455C28	±4.0kHzmin.	40±20mV	3.0%max.	—		
CDBC455CX28	±4.0kHzmin.	40±20mV	3.0%max.	—		

Character- istics Part Number	Recovered Audio 3dB Bandwidth (from 455kHz)	Recovered Audio Output (at 455kHz)	Distortion		I C	Application
			at 455kHz	within 455±8kHz		
CDB455C29	±4.0kHzmin.	125±30mV	2.5%max.	—	NE605	Cordless Telephone, Communications Equipment
CDBM455C29	±4.0kHzmin.	125±30mV	2.5%max.	—		
CDBC455CX29	±4.0kHzmin.	100±30mV	2.5%max.	—		
CDB455C30	±4.0kHzmin.	90±30mV	2.0%max.	—	TK14501	Telephone, Communications Equipment
CDBM455C30	±4.0kHzmin.	90±30mV	2.0%max.	—		
CDBC455CX30	±4.0kHzmin.	80±20mV	2.0%max.	—		
CDB455C32	±4.0kHzmin.	40±20mV	3.0%max.	—	TA31143	Pager
CDBM455C32	±4.0kHzmin.	40±20mV	3.0%max.	—		
CDBC455CX32	±4.0kHzmin.	40±20mV	3.0%max.	—		
CDB455C34	±4.0kHzmin.	65±20mV	2.5%max.	—	MC13136	Cordless Telephone, Communications Equipment
CDBM455C34	±4.0kHzmin.	65±20mV	2.5%max.	—		
CDB455C35	±4.0kHzmin.	100±40mV	2.5%max.	—	TK10930	Cordless Telephone, Communications Equipment
CDBM455C35	±4.0kHzmin.	100±40mV	2.5%max.	—		
CDBC455CX35	±4.0kHzmin.	100±40mV	2.5%max.	—		
CDBM455C36	±3.5kHzmin.	100±25mV	3.5%max.	—	NE (SA) 606	Cordless Telephone, Cellular Phone
CDBC455CLX36	±13.0kHzmin.	90±30mV	2.5%max.	5.0%max.	NE (SA) 616	
CDBM455C39	±4.0kHzmin.	85±20mV	2.5%max.	—	NE (SA) 607/617	Cordless Telephone
CDBC455CLX39	±11.0kHzmin.	130±20mV	2.5%max.	7.0%max.	NE607/617	
CDBM455C40	±4.0kHzmin.	40±20mV	3.0%max.	—	TA31145	Pager
CDBC455CX40	±4.0kHzmin.	40±20mV	3.5%max.	—		
CDB455C42	±4.0kHzmin.	40±15mV	3.0%max.	—	TK14590/14591	Pager
CDBM455C42	±4.0kHzmin.	40±15mV	3.0%max.	—		
CDBM455C49	±4.0kHzmin.	45±10mV	3.0%max.	—	MC3361	Cordless Telephone
CDBC455CX49	±4.0kHzmin.	45±10mV	3.0%max.	—		
CDBM455C50	±4.0kHzmin.	64±6.4mV	4.0%max.	—	CXA3117	Pager
CDBC455CX50	±4.0kHzmin.	64±6.4mV	4.0%max.	—		


● S Curve Specification

Character- istics Part Number	Nominal Center Frequency	S Curve Characteristics i) Output Voltage at 450kHz	S Curve Characteristics ii) Difference Voltage Between at 450—4.8kHz and at 450+4.8kHz	I C	Application
CDBM455C47	455kHz	140±20mV	150±15mV	TA31147	Pager
CDBC455CX47	455kHz	130±20mV	150±15mV		
CDBM455C54	455kHz	165±20mV	170±20mV	TA31149	Pager
CDBC455CX54	455kHz	165±20mV	170±20mV		


TA31143




NE (SA) 606/616




TK14590/14591




TA31147




MC3361



CXA3117




TA31149




FREQUENCY CHARACTERISTICS

Impedance Curve Specification


CDBM455C2




CDBC455CX2




CDB (CDBM) 455C3




CDBM455C4




CDB (CDBM) 455C10




CDBM455C15




CDBM455C25




CDBM455C31



CDBC455CX31




CDBM455C33




● Recovered Audio Curve Specification


CDB (CDBM) 455C7/MC3357




CDBC455CX7/MC3357




CDB (CDBM) 455C9/NE604




CDBC455CX9/NE604




CDB (CDBM) 455CL9/NE604




CDB (CDBM) 455C13A/CXA1003BM




CDBC455CX13/CXA1003BM




CDB (CDBM) 455CL13/CXA1003BM




CDBC455CLX13/CXA1003BM




CDB (CDBM) 455C16/MC3372




CDBC455CX16/MC3372




CDBM455C18/MC3371




CDB (CDBM) 455C21/TA31132




CDBC455CX21/TA31132



CDB (CDBM) 455CL21/TA31132




CDBC455CLX21/TA31132




● Recovered Audio Curve Specification


CDB (CDBM) 455C24/TA31136




CDBC455CX24/TA31136




CDB (CDBM) 455C27/TK10487




CDBC455CX27/TK10487




CDB (CDBM) 455C28/TA31142




CDBC455CX28/TA31142




CDB (CDBM) 455C29/NE605




CDBC455CX29/NE605




CDB (CDBM) 455C30/TK14501




CDBC455CX30/TK14501




CDB (CDBM) 455C32/TA31143




CDBC455CX32/TA31143




CDB (CDBM) 455C34/MC13136




CDB (CDBM) 455C35/TK10930






CDBC455CX35/TK10930



CDBM455C36/NE (SA) 606/616



●Recovered Audio Curve Specification



●S Curve Specification

