General Cable Product Data Sheet

Part Number: C3194	Revision Level: 0	Date: 7/7/2007

3C 16 7/.0192 BC FLEX PVDF **TYPE CL2P / CMP**

A. CONSTRUCTION

		DIAMETERS
Conductor:	#16 AWG 7/.0192 Bare Copper	0.058” nom.
Insulation:	0.008" Wall FLEXGUARD*	0.074" nom.
Cable:	3 Conductors @ 4.00" LHL.	0.144" nom.
Jacket:	0.010"Wall PVDF – Natural -Plenum ripcord under jacket.	0.164" +/- 0.008"
Print Legend:	***CAROL (R) 16 AWG -- C3194 -- 60C E60233-8 CL2P OR CMP(UL) C(UL) -- MADE IN USA DATE CODE (PRINT EVERY 2 FT)***	

B. INDUSTRY APPROVALS

National Electrical Code	Article 725
UL Standard 13	Type CL2P
National Electrical Code	Article 800
UL Standard 444	Type CMP

C. ELECTRICAL PROPERTIES

TEMPERATURE:	60C
SUGGESTED WORKING VOLTAGE (Vrms):	150 Vrms (CL2P); 300 Vrms (CMP)
CONDUCTOR D.C. RESISTANCE:	4.1 Ohms/1000 ft. nom. @ 20C

D. COLOR CODE *(Listed as Individual Conductors or Pairs of Conductors)*

1	Black
2	White
3	Red

Note: Data are subject to change without notice. Contact your Customer Service representative for latest information.

**FLEXGUARD is a trademark of General Cable Corporation for polymer alloy insulation and jackets.*