


Type 943C Very High dV/dt, Oval Polypropylene Film Capacitors

Oval, Foil/Metallized Hybrid, Axial Leaded

Type 943C oval, axial film capacitors utilize a hybrid section design of polypropylene film, metal foils and metallized polypropylene dielectric to achieve both high peak current as well as superior rms current ratings. This series is ideal for high pulse operation and high peak current circuits.



Complies with the EU Directive 2002/95/EC requirement restricting the use of Lead (Pb), Mercury (Hg), Cadmium (Cd), Hexavalent chromium (Cr(VI)), PolyBrominated Biphenyls (PBB) and PolyBrominated Diphenyl Ethers (PBDE).

Specifications


Capacitance Range: 0.01 to 2.5 μF

Voltage Range: 600 to 2000 Vdc,
(300 to 500 Vac, 60 Hz)

Capacitance Tolerance: $\pm 10\%$

Operating Temp. Range: -55°C to 105°C *

*Full-rated voltage at 85°C , derate linearly to 50% rated voltage at 105°C



Ratings

Cap. (μF)	Catalog Part Number	T Inches(mm)	W Inches(mm)	L Inches(mm)	d Inches(mm)	Typical ESR (m Ω)	Typical ESL (nH)	dV/dt (V/ms)	I _{peak} (A)	I _{RMS} 70 $^{\circ}\text{C}$ 100 kHz (A)
600 Vdc (300 Vac)										
.15	943C6P15K-F	0.483(12.3)	0.669(17.0)	1.339(34.0)	0.040(1.0)	5	19	1427	214	8.9
.22	943C6P22K-F	0.565(14.3)	0.750(19.0)	1.339(34.0)	0.040(1.0)	7	20	1427	314	8.1
.33	943C6P33K-F	0.672(17.1)	0.857(21.8)	1.339(34.0)	0.040(1.0)	6	22	1427	471	9.6
.47	943C6P47K-F	0.785(19.9)	0.970(24.6)	1.339(34.0)	0.040(1.0)	5	23	1427	671	11.4
.68	943C6P68K-F	0.927(23.5)	1.113(28.3)	1.339(34.0)	0.047(1.2)	4	24	1427	970	14.1
1.00	943C6W1K-F	0.758(19.2)	1.128(28.6)	1.811(46.0)	0.047(1.2)	5	28	800	800	13.4
1.50	943C6W1P5K-F	0.926(23.5)	1.296(32.9)	1.811(46.0)	0.047(1.2)	4	30	800	1200	16.6
2.00	943C6W2K-F	0.947(24.0)	1.318(33.5)	2.126(54.0)	0.047(1.2)	3	33	628	1256	20.6
2.20	943C6W2P2K-F	0.993(25.2)	1.364(34.6)	2.126(54.0)	0.047(1.2)	3	34	628	1382	21.1
2.50	943C6W2P5K-F	1.063(27.0)	1.437(36.5)	2.126(54.0)	0.047(1.2)	3	35	628	1570	21.9
850 Vdc (360 Vac)										
.15	943C8P15K-F	0.548(13.9)	0.733(18.6)	1.339(34.0)	0.040(1.0)	5	20	1712	257	9.4
.22	943C8P22K-F	0.644(16.4)	0.829(21.0)	1.339(34.0)	0.040(1.0)	7	21	1712	377	8.7
.33	943C8P33K-F	0.769(19.5)	0.954(24.2)	1.339(34.0)	0.040(1.0)	6	23	1712	565	10.3
.47	943C8P47K-F	0.902(22.9)	1.087(27.6)	1.339(34.0)	0.047(1.2)	5	24	1712	805	12.4
.68	943C8P68K-F	1.068(27.1)	1.254(31.8)	1.339(34.0)	0.047(1.2)	4	26	1712	1164	15.3
1.00	943C8W1K-F	0.882(22.4)	1.252(31.8)	1.811(46.0)	0.047(1.2)	5	29	960	960	14.5
1.50	943C8W1P5K-F	0.956(24.3)	1.327(33.7)	2.126(54.0)	0.047(1.2)	4	34	754	1131	18.0
2.00	943C8W2K-F	0.972(24.7)	1.346(34.2)	2.520(64.0)	0.047(1.2)	3	38	574	1147	22.4

NOTE: Other capacitance values, sizes and performance specifications are available. Contact us.

Type 943C Very High dV/dt, Oval Polypropylene Film Capacitors

Ratings

Cap. (μ F)	Catalog Part Number	T Inches(mm)	W Inches(mm)	L Inches(mm)	d Inches(mm)	Typical ESR (m Ω)	Typical ESL (nH)	dV/dt (V/ms)	I peak (A)	I _{RMS} 70 °C (A)
1000 Vdc (400 Vac)										
.10	943C10P1K-F	0.569(14.4)	0.755(19.2)	1.339(34.0)	0.040(1.0)	8	20	2283	228	7.6
.15	943C10P15K-F	0.677(17.2)	0.862(21.9)	1.339(34.0)	0.040(1.0)	7	22	2283	342	8.9
.22	943C10P22K-F	0.802(20.4)	0.987(25.1)	1.339(34.0)	0.040(1.0)	6	23	2283	502	10.6
.33	943C10P33K-F	0.654(16.6)	1.025(26.0)	1.811(46.0)	0.040(1.0)	5	27	1280	422	12.5
.47	943C10P47K-F	0.777(19.7)	1.148(29.1)	1.811(46.0)	0.047(1.2)	5	28	1280	601	13.6
.68	943C10P68K-F	0.933(23.7)	1.304(33.1)	1.811(46.0)	0.047(1.2)	5	30	1280	870	14.9
1.00	943C10W1K-F	1.002(25.4)	1.373(34.9)	2.126(54.0)	0.047(1.2)	5	34	1005	1005	16.5
1.40	943C10W1P4K-F	1.035(26.3)	1.417(36.0)	2.520(64.0)	0.047(1.2)	4	39	765	1071	20.1
1200 Vdc (430 Vac)										
.10	943C12P1K-F	0.675(17.1)	0.860(21.8)	1.339(34.0)	0.040(1.0)	5	22	2854	285	10.5
.15	943C12P15K-F	0.807(20.5)	0.992(25.2)	1.339(34.0)	0.040(1.0)	5	23	2854	428	11.6
.22	943C12P22K-F	0.960(24.4)	1.145(29.1)	1.339(34.0)	0.047(1.2)	6	25	2854	628	11.7
.33	943C12P33K-F	0.794(20.2)	1.165(29.6)	1.811(46.0)	0.047(1.2)	6	28	1600	528	12.5
.47	943C12P47K-F	0.946(24.0)	1.317(33.4)	1.811(46.0)	0.047(1.2)	5	30	1600	752	15.0
.68	943C12P68K-F	1.008(25.6)	1.379(35.0)	2.126(54.0)	0.047(1.2)	5	36	1256	854	16.5
.90	943C12P9K-F	1.012(25.7)	1.383(35.1)	2.520(64.0)	0.047(1.2)	5	39	956	860	17.7
1600 Vdc (460 Vac)										
.022	943C16S22K-F	0.416(10.6)	0.602(15.3)	1.339(34.0)	0.040(1.0)	27	19	3425	75	3.5
.033	943C16S33K-F	0.487(12.4)	0.673(17.1)	1.339(34.0)	0.040(1.0)	14	20	3425	113	5.3
.047	943C16S47K-F	0.563(14.3)	0.748(19.0)	1.339(34.0)	0.040(1.0)	8	20	3425	161	7.6
.068	943C16S68K-F	0.659(16.7)	0.844(21.4)	1.339(34.0)	0.040(1.0)	6	21	3425	233	9.5
.10	943C16P1K-F	0.780(19.8)	0.966(24.5)	1.339(34.0)	0.040(1.0)	4	23	3425	342	12.8
.15	943C16P15K-F	0.636(16.1)	1.006(25.5)	1.811(46.0)	0.040(1.0)	5	26	1919	288	12.3
.22	943C16P22K-F	0.765(19.4)	1.136(28.8)	1.811(46.0)	0.040(1.0)	5	28	1919	422	13.5
.33	943C16P33K-F	0.935(23.7)	1.306(33.2)	1.811(46.0)	0.047(1.2)	5	30	1919	633	14.9
.47	943C16P47K-F	0.989(25.1)	1.360(34.5)	2.126(54.0)	0.047(1.2)	5	34	1507	708	16.3
.56	943C16P56K-F	0.957(24.3)	1.327(33.7)	2.520(64.0)	0.047(1.2)	5	38	1147	642	17.2
.68	943C16P68K-F	1.047(26.6)	1.417(36.0)	2.520(64.0)	0.047(1.2)	5	40	1147	780	18.0
2000 Vdc (500 Vac)										
.010	943C20S1K-F	0.411(10.4)	0.596(15.1)	1.339(34.0)	0.040(1.0)	50	19	5137	51	2.6
.015	943C20S15K-F	0.480(12.2)	0.666(16.9)	1.339(34.0)	0.040(1.0)	40	19	5137	77	3.1
.022	943C20S22K-F	0.561(14.2)	0.747(19.0)	1.339(34.0)	0.040(1.0)	20	20	5137	113	4.8
.033	943C20S33K-F	0.667(16.9)	0.852(21.6)	1.339(34.0)	0.040(1.0)	12	22	5137	170	6.8
.047	943C20S47K-F	0.525(13.3)	0.896(22.8)	1.811(46.0)	0.040(1.0)	10	25	2879	135	8.0
.068	943C20S68K-F	0.624(15.8)	0.995(25.3)	1.811(46.0)	0.040(1.0)	6	26	2879	196	11.2
.10	943C20P1K-F	0.752(19.1)	1.122(28.5)	1.811(46.0)	0.047(1.2)	5	28	2879	288	11.47
.15	943C20P15K-F	0.918(23.3)	1.289(32.7)	1.811(46.0)	0.047(1.2)	5	30	2879	432	12.5