



## Plenum N Female to 7/16 DIN Male Low PIM Cable 100 CM Length Using SPP-250-LLPL Coax, RoHS

### RF Cable Assemblies Technical Data Sheet


PE3C4133-100CM

#### Configuration

- Connector 1: N Female
- Connector 2: 7/16 DIN Male
- Cable Type: SPP-250-LLPL

#### Features

- PIM < -160 dBc
- 100% Tested with PIM Test Results Marked on Cable
- UL910 Plenum Rated Cable
- Lightweight and Extremely Flexible
- Low Loss with Excellent VSWR
- IP67 (when mated)



#### Applications

- Distributed Antenna Systems (DAS)
- Plenum Installations
- Multi-Carrier Communication Systems
- PIM Testing

#### Description

Pasternack's low PIM plenum cable assemblies using SPP-250-LLPL coax and N female to 7/16 DIN male connections are part of our full line of RF components available for same-day shipping. These N female to 7/16 DIN male plenum coax cable assemblies deliver low PIM performance to support Distributed Antenna Systems (DAS) and other complex, multi-carrier communication systems. The SPP-250-LLPL coax cable has been certified in accordance with UL910 for plenum coaxial cable installations. Each N female to 7/16 DIN male cable assembly is 100% tested for Passive Intermodulation (PIM) and the tested value is marked directly on the cable.

Our N female to 7/16 DIN male cable datasheet specifications and drawing with dimensions are shown below in this PDF. Whether the need is to provide a low PIM jumper connection, low PIM test cable or simply create a custom cable assembly configuration, Pasternack has the right cable assemblies for the job.

#### Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		6	GHz
VSWR			1.35:1	
Velocity of Propagation		76		%
RF Shielding	100			dB
Passive Intermodulation		-165	-160	dBc
Capacitance		26.7 [87.6]		pF/ft [pF/m]
Operating Voltage (AC)			750	Vrms

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Plenum N Female to 7/16 DIN Male Low PIM Cable 100 CM Length Using SPP-250-LLPL Coax, RoHS PE3C4133-100CM](#)



Plenum N Female to 7/16 DIN Male Low PIM Cable  
100 CM Length Using SPP-250-LLPL Coax, RoHS

RF Cable Assemblies Technical Data Sheet

PE3C4133-100CM

**Specifications by Frequency**

Description	F1	F2	F3	F4	F5	Units
Frequency	0.7	2	6			GHz
Insertion Loss (Max.)	0.25	0.44	0.8			dB
VSWR (Max.)	1.25:1	1.25:1	1.35:1			
Power Handling (Max.)		460	250			Watts

Electrical Specification Notes:  
Values at 25°C, sea level  
PIM test results vary between cables

**Mechanical Specifications**

**Cable Assembly**

Length\* 39.37 in [100 cm]  
Diameter 0.28 in [7.11 mm]

**Cable**

Cable Type SPP-250-LLPL  
Impedance 50 Ohms  
Inner Conductor Type Solid  
Inner Conductor Material and Plating Copper, Bare  
Dielectric Type PTFE  
Number of Shields 1  
Shield Layer 1 Helically Corrugated Copper Tube  
Outer Conductor Diameter 0.25 in [6.35 mm]  
Jacket Material FEP  
Jacket Diameter 0.28 in [7.11 mm]

One Time Minimum Bend Radius 1.5 in [38.1 mm]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Plenum N Female to 7/16 DIN Male Low PIM Cable 100 CM Length Using SPP-250-LLPL Coax, RoHS PE3C4133-100CM](#)





Plenum N Female to 7/16 DIN Male Low PIM Cable  
 100 CM Length Using SPP-250-LLPL Coax, RoHS

## RF Cable Assemblies Technical Data Sheet

PE3C4133-100CM

### Connectors

Description	Connector 1	Connector 2
Type	N Female	7/16 DIN Male
Impedance	50 Ohms	50 Ohms
Contact Material and Plating	Beryllium Copper, Silver	Brass, Silver
Dielectric Type	PTFE	PTFE
Body Material and Plating	Brass, Tri-Metal	Brass, Tri-Metal
Seal Gasket Material	Silicone Rubber	Silicone Rubber

#### Mechanical Specification Notes:

\*All cable assemblies have a length tolerance of 1.5% or  $\pm 3/8$ ", whichever is greater.

### Environmental Specifications

#### Temperature

Operating Range  
 Plenum Rating

-55 to +125 deg C  
 UL910

### Compliance Certifications (see [product page](#) for current document)

### Plotted and Other Data

#### Notes:

- Values at 25°C, sea level.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Plenum N Female to 7/16 DIN Male Low PIM Cable 100 CM Length Using SPP-250-LLPL Coax, RoHS PE3C4133-100CM](#)



Plenum N Female to 7/16 DIN Male Low PIM Cable  
100 CM Length Using SPP-250-LLPL Coax, RoHS

RF Cable Assemblies Technical Data Sheet

PE3C4133-100CM

Typical Performance Data



Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Plenum N Female to 7/16 DIN Male Low PIM Cable 100 CM Length Using SPP-250-LLPL Coax, RoHS PE3C4133-100CM](#)





Plenum N Female to 7/16 DIN Male Low PIM Cable  
100 CM Length Using SPP-250-LLPL Coax, RoHS

## RF Cable Assemblies Technical Data Sheet

PE3C4133-100CM

### How to Order

Part Number Configuration:

**PE3C4133**

- **xx**

**uu**

Unit of Measure:

cm = Centimeters

<blank> = Inches

Length

Base Number

Example: PE3C4133-12 = 12 inches long cable  
PE3C4133-100cm = 100 cm long cable


Plenum N Female to 7/16 DIN Male Low PIM Cable 100 CM Length Using SPP-250-LLPL Coax, RoHS from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [Plenum N Female to 7/16 DIN Male Low PIM Cable 100 CM Length Using SPP-250-LLPL Coax, RoHS PE3C4133-100CM](https://www.pasternack.com/n-female-7-16-din-male-spp250llpl-cable-assembly-pe3c4133-100cm-p.aspx)

URL: <https://www.pasternack.com/n-female-7-16-din-male-spp250llpl-cable-assembly-pe3c4133-100cm-p.aspx>


The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Pasternack does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Pasternack does not assume any liability arising out of the use of any part or documentation.

**PE3C4133-100CM CAD Drawing**  
 Plenum N Female to 7/16 DIN Male Low PIM Cable 100 CM  
 Length Using SPP-250-LLPL Coax, RoHS



STANDARD TOLERANCES
.X ±0.2
.XX ±0.01
.XXX ±0.005

\*STANDARD TOLERANCES APPLY ONLY TO DIMENSIONS IN INCHES

 <b>THE ENGINEER'S RF SOURCE</b> Pasternack Enterprises, Inc. P.O. Box 16759   Irvine   CA   92623 Phone: (949) 261-1920   Fax: (949) 261-7451 Website: www.pasternack.com   E-Mail: sales@pasternack.com	DWG TITLE PE3C4133	NOTES: 1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL. 2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME 3. DIMENSIONS ARE IN INCHES [mm].		
	CAGE CODE 53919	CAD FILE 080417	SCALE N/A	SIZE A