


### Features

- Supports up to 40 W Power
- Low Insertion Loss:
  - 0.2 dB @ 2.7 GHz
  - 0.4 dB @ 8.0 GHz
- High Isolation:
  - 55 dB to 2.7 GHz
- RoHS\* Compliant



(2615)  
Molded Plastic DFN

### Description

A broadband, high linearity, medium power shunt switch element in a 2.6 x 1.5 mm DFN package.

This PIN diode switch element is designed for wireless telecommunications infrastructure and test instrument applications. It is also suited for other applications in 0.05 ~ 10 GHz.

### Electrical Specifications: $T_A = +25^\circ\text{C}$


Parameter	Test Conditions	Units	Min.	Typ.	Max.
Breakdown Voltage ( $V_B$ )	$I_R = 10 \mu\text{A}$	V	300	—	—
Insertion Loss ( $I_L$ )	$V_R = 50 \text{ V}$ 2.3 - 2.7 GHz <6.0 GHz	dB	—	0.20 0.40	0.30 0.50
Isolation ( $I_{SO}$ )	$V_R = -10 \text{ V}$ 2.3 - 2.7 GHz <6.0 GHz	dB	50 35	55 40	—
Input / Output Return Loss ( $R_L$ )	$I_F = 100 \text{ mA}$ 2.3 - 2.7 GHz <6.0 GHz	dB	20 14	25 16	—
Minority Carrier Lifetime ( $T_L$ )	$I_F = 10 \text{ mA}, I_R = 6 \text{ mA}, @ 50\%$	ns	—	3000	—

### Absolute Maximum Ratings


Parameter	Absolute Maximum
Breakdown Voltage	300 V
Forward Current	200 mA
Thermal Resistance	9°C/W
Junction Temperature	+175°C
Storage Temperature	-65°C to +150°C
Assembly Temperature	+260°C, Per JEDEC STD-J-20C

1 \* Restrictions on Hazardous Substances, European Union Directive 2011/65/EU.


### Printed Circuit Board Layout




**Junction Temperature vs. Power  
Mounted on Heatsink, +25°C, 1.3 GHz**




### Insertion Loss




### Isolation<sup>1</sup>



### Input Return Loss




### Series Resistance vs. Bias, 500 MHz



1. Resonant frequencies vary with PCB layout. This performance measured on 20 mils Rogers RO3006 and with the printed circuit board layout shown above.

### Outline (2615)



MACOM Technology Solutions Inc. All rights reserved.

Information in this document is provided in connection with MACOM Technology Solutions Inc ("MACOM") products. These materials are provided by MACOM as a service to its customers and may be used for informational purposes only. Except as provided in MACOM's Terms and Conditions of Sale for such products or in any separate agreement related to this document, MACOM assumes no liability whatsoever. MACOM assumes no responsibility for errors or omissions in these materials. MACOM may make changes to specifications and product descriptions at any time, without notice. MACOM makes no commitment to update the information and shall have no responsibility whatsoever for conflicts or incompatibilities arising from future changes to its specifications and product descriptions. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document.

THESE MATERIALS ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, RELATING TO SALE AND/OR USE OF MACOM PRODUCTS INCLUDING LIABILITY OR WARRANTIES RELATING TO FITNESS FOR A PARTICULAR PURPOSE, CONSEQUENTIAL OR INCIDENTAL DAMAGES, MERCHANTABILITY, OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT. MACOM FURTHER DOES NOT WARRANT THE ACCURACY OR COMPLETENESS OF THE INFORMATION, TEXT, GRAPHICS OR OTHER ITEMS CONTAINED WITHIN THESE MATERIALS. MACOM SHALL NOT BE LIABLE FOR ANY SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, INCLUDING WITHOUT LIMITATION, LOST REVENUES OR LOST PROFITS, WHICH MAY RESULT FROM THE USE OF THESE MATERIALS.

MACOM products are not intended for use in medical, lifesaving or life sustaining applications. MACOM customers using or selling MACOM products for use in such applications do so at their own risk and agree to fully indemnify MACOM for any damages resulting from such improper use or sale.