



NOTES:

1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: X.X = ± 0.4  
X.XX = ± 0.25
3. ELECTRICAL LIFE: 6,000 [cURus]  
10,000 [VDE]
4. CONTACT RESISTANCE: 20 mΩ MAX. INITIAL
5. INSULATION RESISTANCE: 100 MΩ AT 500VDC
6. OPERATING TEMPERATURE: -20°C to +65°C [cURus]  
-20°C to +125°C [VDE]
7. CONTACT RATING: 16A, 125VAC/250VAC, [cURus]  
16(4)A, 250VAC, 1E4 T125/55 [VDE]
8. DIELECTRIC STRENGTH: 1000V FOR 1 MINUTE
9. ACTUATION FORCE: 500 +/- 200 g
10. TRAVEL: TO LOCK POSITION: 3.0mm  
FULL TRAVEL: 5.0mm
11. ▲ DENOTES CRITICAL PARAMETER
12. 2011/65/EU (RoHS) COMPLIANT



A	22543	NEW RELEASE	10/19/16	MW
REV	PCR NO	DESCRIPTION	DATE	BY

TITLE PA5F32C				
SCALE	DATE	DR	DWG	REV
3:2	10/11/2016	MW	14-PA5F32C	A

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED