

KEY FEATURES

- Switching Power Module for PCB Mountable
- 4000VAC Input to Output 2MOPP Insulation
- Cooling by Free Air Convection
- High Efficiency up to 90%
- With P.F.C. Function >0.9
- <0.3W No Load Input Power
- EMI for Both Class I (with PE) and Class II (without PE) Configuration
- Suitable for BF Application with Appropriate System Consideration
- UL / IEC / EN 60601 3.1 Edition Safety Approvals
- 3-Year Product Warranty



ELECTRICAL SPECIFICATIONS

All specifications valid at 230VAC input voltage, full load and +25°C after warm-up time unless otherwise stated.

Model No.		MQCS100-12S	MQCS100-24S	MQCS100-48S
Max Output Wattage (W)		100 W		
Input	Voltage (Note 3)	90-264 VAC		
	Frequency (Hz)	47-63 Hz		
	Current (Full load)	< 2.0 A max. (115 VAC) / < 1.0 A max. (230 VAC)		
	Inrush Current (<2ms)	< 45 A max. (115 VAC) / < 90 A max. (230 VAC)		
	Leakage Current	< 0.1mA / 264 VAC (Touch Current)		
	Power Factor	PF>0.97 (115 VAC) / PF>0.9 (230 VAC) at Full Load		
Output	Voltage (V.DC.)	12V	24V	48V
	Voltage Accuracy	±2%		
	Current (A) max	8.333	4.167	2.083
	Line Regulation	±1%		
	Load Regulation (10-100%)	±1%		
	Minimum Load	0%		
	Maximum Capacitive Load	3000μF	1500μF	500μF
	Ripple & Noise (max.) (Note 1)	160mV	1% Vout	
	Efficiency (at 230VAC)	90%	90%	90%
Protection	Hold-up Time (at 115 VAC) (Note 2)	10 ms min.		
	Over Power Protection	Auto recovery, Hiccup mode		
	Over Voltage Protection	Auto recovery, Hiccup mode		
	Over Temperature Protection	Latch off		
Isolation	Short Circuit Protection	Auto recovery, Hiccup mode		
	Input-Output	4000VAC or 5656VDC		
	Input-FG	2000VAC or 2828VDC		
Environment	Output-FG	1500VAC or 2121VDC		
	Operating Temperature	-30°C...+70°C (with derating)		
	Storage Temperature	-30°C...+85°C		
	Temperature Coefficient	±0.05%/°C		
	Altitude During Operation	5000m		
	Humidity	95% RH		
	Atmospheric Pressure	54 kPa to 106 kPa		
	MTBF	>250,000 h @ 25°C (MIL-HDBK-217F, Notice 1)		
	Vibration	10~500Hz, 5G 10min./1cycle, 60min. each along X, Y, Z axes.		

ELECTRICAL SPECIFICATIONS

All specifications valid at 230VAC input voltage, full load and +25°C after warm-up time unless otherwise stated.



Model No.		MQCS100-12S	MQCS100-24S	MQCS100-48S
Physical	Dimension (L x W x H)	3.3 x 2.3 x 1.38 Inches (83.9 x 58.5 x 35.0 mm) Tolerance ± 0.5 mm		
	Weight	In Progress		
	Cooling Method	Free convection		
Safety	Approval	UL / IEC / EN 60601 3.1 rd Edition		
EMC	Conducted EMI (Note 4)	EN55011 Conducted & Radiated Class B (In Progress)		
	Radiated EMI (Note 4)	EN55011 Class I class B / Class II class A (In Progress)		
	EMS	EN60601-1-2 4th edition (In Progress)		

NOTE


1. Ripple & Noise are measured at 20MHz of bandwidth with 0.1uF & 47uF parallel capacitor.
2. Hold-up Time measured at 90% Vout.
3. Please check the derating curve for more details.
4. Please secure the power supply unit to your metal case by using the four screw holes in the corners for either Class I or Class II equipment
5. Please refer to our PDF file "AC-DC Application" on our website: www.archcorp.com.tw

DERATING

If the input voltage is below 99VAC, we can only use it under the environment of higher than -10 celsius degree



MECHANICAL DIMENSION (Top View)




PIN#	Φ	Single
1	1.2±0.1%mm	PE
2	1.2±0.1%mm	AC IN (N)
3	1.2±0.1%mm	AC IN (L)
4	1.2±0.1%mm	ON / OFF
(Provide +5Vdc Controlled)		
5	1.8±0.1%mm	+DC OUT
6	1.8±0.1%mm	-DC OUT
7	1.2±0.1%mm	Trim

Remark:

Please reserve the pin 4 hole on PCB.

If the remote on/off function is not required, please connect the pin 4 circuit layout with pin6, or keep pin 4 floating.

BLOCK DIAGRAM



TRIM

	12S		24S		48S	
Trim → -V	+5%	0%	+5%	0%	+5%	0%
	32K Ω	~ 10M	36K Ω	~ 10M	33K Ω	~ 10M
Trim → +V	0%	-5%	0%	-5%	0%	-5%
	10M Ω	~ 80K Ω	10M Ω	~ 205K Ω	10M Ω	~ 480K Ω