AUK Semiconductor

SHE124MD / SHE124MD-(B)

High Efficiency LED Lamp

Features

- Yellow-Green Colored lens type
- ϕ5mm(T-13/4) all plastic mold type
- Super luminosity


Application

- Massage Board
- Variable message signs(VMS)


Outline Dimensions

unit : mm

STRAIGHT TYPE



STOPPER TYPE




PIN Connections

1. Anode
2. Cathode

Absolute maximum ratings

Characteristic	Symbol	Ratings	Unit
Power Dissipation	P_D	100	mW
Forward Current	I_F	40	mA
*[1]Peak Forward Current	I_{FP}	65	mA
Reverse Voltage	V_R	4	V
Operating Temperature	T_{opr}	-20～85	℃
Storage Temperature	T_{stg}	-30～100	℃
*[2]Soldering Temperature	T_{sol}	260℃ for 5 seconds	

*1.Duty ratio = 1/16, Pulse width = 0.1ms
*2.Keep the distance more than 2.0mm from PCB to the bottom of LED package



Electrical Characteristics

Ta=25°C

Characteristic	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Forward Voltage	V_F	I_F= 20mA	1.6	2.0	2.5	V
*[4]Luminous Intensity	I_V	I_F= 20mA	155	350	780	mcd
Peak Wavelength	λ_P	I_F= 20mA	-	570	-	nm
Spectrum Bandwidth	$\Delta\lambda$	I_F= 20mA	-	30	-	nm
Reverse Current	I_R	V_R=4V	-	-	10	uA
*[3]Half Angle	$\theta 1/2$	I_F= 20mA	-	±20	-	deg

*3. $\theta 1/2$ is the off-axis angle where the luminous intensity is 1/2 the peak intensity

*4. Luminous Intensity Maximum tolerance for each Grade Classification limit is ±18%

*4. Luminous Intensity classification

M	N	O	P
155~230	230~350	350~520	520~780

Characteristic Diagrams

Fig. 1 I_F - V_F




Fig. 2 I_V - I_F




Fig. 3 I_F – Ta




Fig.4 Spectrum Distribution





Fig. 5 Radiation Diagram



These AUK products are intended for usage in general electronic equipments(Office and communication equipment, measuring equipment, domestic electrification, etc.).

Please make sure that you consult with us before you use these AUK products in equipments which require high quality and/or reliability, and in equipments which could have major impact to the welfare of human life(atomic energy control, airplane, spaceship, traffic signal, combustion central, all types of safety device, etc.).

AUK cannot accept liability to any damage which may occur in case these AUK products were used in the mentioned equipments without prior consultation with AUK.