Connector - C-SCF 1/2,8X0,8 - 3240153

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://download.phoenixcontact.com)



The figure shows a version of the article

Slip-on sleeve, non-insulated, 0.5 - 1 mm², 2.8 x 0.8

Product Features

- The uninsulated slip-on sleeves and flat plugs are made from electrolytically tin-plated brass
- They round out the product range in terms of connectors

Key commercial data

Packing unit	1 1
Minimum order quantity	100 1
Weight per Piece (excluding packing)	0.5 GRM
Custom tariff number	85366990
Country of origin	Germany

Technical data

Dimensions

Length (b)	12.5 mm
Width (a)	2.8 mm
Material thickness (g)	0.3 mm

Ambient conditions

Ambient temperature (operation)	110 °C

General

Color	silver
Stripping length	7 mm
Components	Halogen-free

Connector - C-SCF 1/2,8X0,8 - 3240153

Technical data

General

Material	Brass

Classifications

eCl@ss

eCl@ss 4.0	27060701
eCl@ss 4.1	27060701
eCl@ss 5.0	27400201
eCl@ss 5.1	27400201
eCl@ss 6.0	27400201
eCl@ss 7.0	27400201
eCl@ss 8.0	27400201

ETIM


ETIM 2.0	EC000005
ETIM 3.0	EC000005
ETIM 4.0	EC001052
ETIM 5.0	EC001052

UNSPSC

UNSPSC 6.01	30211923
UNSPSC 7.0901	27121703
UNSPSC 11	27121703
UNSPSC 12.01	27121703
UNSPSC 13.2	27121703

Drawings

Dimensioned drawing



© Phoenix Contact 2013 - all rights reserved
http://www.phoenixcontact.com