molex
one company > a world of innovation

This document was generated on 05/17/2010

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0850039036
Status: Active
Overview: din_41612
Description: 2.54mm (.100") Pitch DIN 41612 C Style Male Header, Right Angle, Through Hole, 0.80µm (32µ") Selective Gold (Au) Plating, 96 Circuits, with Mounting Clips, No Flux Proof, Lead free, High Temperature version

Documents:
Drawing (PDF)
RoHS Certificate of Compliance (PDF)

Agency Certification

CSA	LR19980
UL	E29179

General

Product Family	Backplane Connectors
Series	85003
Application	Backplane
Comments	With Mounting Clips. No Flux Proof. 4.2mm(.165") Last-Mate-First- Break Contacts. 5.2mm(.204") First-Mate-Last-Break Contacts. 4.8mm (.189") Normal Contacts
Component Type	PCB Header
Overview	din_41612
Product Name	IEC 603-2/DIN 41612
Style	C

Physical

Circuits (Loaded)	96
Circuits (maximum)	96
Circuits Detail	Standard Contacts at: A:a13,a22,a32,c12,c21; . First-Mate-Last-Break Contacts at: X:c1,c32; Y:b1,b32; Z:a1. Last-Mate-First-Break Contacts at: D:a2-a12,a14-a21,a23-a31; b2-b31; c2-c11,c13-c20,c22-c31
Color - Resin	Natural
Durability (mating cycles max)	400
First Mate / Last Break	Yes
Flammability	94V-0
Guide to Mating Part	No
Keying to Mating Part	Yes
Material - Metal	Brass
Material - Plating Mating	Gold
Material - Plating Termination	Tin
Material - Resin	High Temperature Thermoplastic
Number of Columns	16
Number of Pairs	Open Pin Field
Number of Rows	3
Orientation	Right Angle
PC Tail Length (in)	0.118 In
PC Tail Length (mm)	3.00 mm
PCB Locator	No
PCB Retention	Yes
PCB Thickness Recommended (in)	0.062 In
PCB Thickness Recommended (mm)	1.60 mm
Packaging Type	Carton
Pitch - Mating Interface (in)	0.100 In
Pitch - Mating Interface (mm)	2.54 mm

EU RoHS
ELV and RoHS Compliant
REACH SVHC
Not Reviewed
Halogen-Free Status
Not Reviewed

China RoHS

Need more information on product environmental compliance?

Email productcompliance@molex.com
For a multiple part number RoHS Certificate of Compliance, click here

Please visit the Contact Us section for any non-product compliance questions.

Search Parts in this Series
85003Series

Pitch - Term. Interface (in)	0.100 In
Pitch - Term. Interface (mm)	2.54 mm
Plating min: Mating (µin)	32
Plating min: Mating (µm)	0.80
Plating min: Termination (µin)	98
Plating min: Termination (µm)	2.5
Polarized to PCB	Yes
Stackable	No
Temperature Range - Operating	-55°C to +125°C
Termination Interface: Style	Through Hole

Electrical

Current - Maximum per Contact	1A
Data Rate	622.0 Mbps
Voltage - Maximum	250V AC (RMS)

Solder Process Data

Duration at Max. Process Temperature (seconds)	50
Lead-free Process Capability	SMC & Wave Capable (TH only)
Max. Cycles at Max. Process Temperature	1
Process Temperature max. C	230

Material Info

Reference - Drawing Numbers

Packaging Specification	PK-85003-001
Sales Drawing	SD-85003-0001, SD-85003-9036



WITH MOUNTING CLIPS

8:1





NOTES:

1) MATERIALS: THERMX (PCT), GLASS FILLED, UL94V-0, COLOR : NATURAL
   TERMINAL - BRASS
   MOUNTING CLIP: STEEL
2) FINISH: CONTACT AREA
   1. PERFORMANCE LEVEL 1: SELECTIVE GOLD (Au), THICKNESS = 1.1 MICROMETER OVER NICKEL, THICKNESS = 1.25 MICROMETER
   2. PERFORMANCE LEVEL 2: SELECTIVE GOLD (Au), THICKNESS = 0.6 MICROMETER OVER NICKEL, THICKNESS = 1.25 MICROMETER
   3. PERFORMANCE LEVEL 3: SELECTIVE GOLD (Au), THICKNESS = 0.3 MICROMETER OVER NICKEL, THICKNESS = 1.25 MICROMETER

   TERMINATION AREA : SELECTIVE TIN, THICKNESS = 2.5 MICROMETER OVER NICKEL, THICKNESS = 1.25 MICROMETER OVERALL
3) MOUNTING CLIP:-
   TIN (Sn), THICKNESS = 5-10 MICROMETER,
   OVER NICKEL (Ni), THICKNESS = 2.5 MICROMETER
4) FOR NON MOUNTING CLIP OPTION, CONNECTOR TO BE SECURED WITH RIVETS: 2 TUBULAR RIVETS 2.5 x 0.3 ... DIN 7340
   SCREWS: 2 CHEESEHEAD SCREWS M2.5 x .... DIN 84 AND 2 HEXAGONAL NUTS M2.5 DIN 934
5) STANDARD MARKING : MOLEX, MATERIAL NUMBER, BATCH CODE
6) CUT FACE OF TIP WITHOUT PLATING PERMITTED
7) PRODUCT SPECIFICATION PS : 85003-0001

RECOMMENDED PCB LAYOUT
COMPONENT SIDE



LMFB CONTACTS	4.2
FMLB CONTACTS	5.2
NORMAL CONTACTS	4.8
	M

RoHS COMPLIANT

EC NO: I2007-0172
DRWN:JAYENGG 2008/06/19
CHKD:SSUDHIR 2008/06/19
APPR:KPRASAD 2009/01/22
DESCRIPTION
REV
A1

QUALITY SYMBOLS
▼=0
⌀=0

GENERAL TOLERANCES (UNLESS SPECIFIED)

	mm	INCH
4 PLACES	± ---	± ---
3 PLACES	± 0.05	± ---
2 PLACES	± 0.1	± ---
1 PLACE	± 0.15	± ---
ANGULAR ± 2 °		

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE: MM ONLY
SCALE: 2:1
DESIGN UNITS: METRIC
THIRD ANGLE PROJECTION

DRAWN BY	SSUDHIR	DATE 2005/04/22
CHECKED BY	KPRASAD	DATE 2005/04/22
APPROVED BY	KPRASAD	DATE 2005/04/22
MATERIAL NO.	SEE CHART	

TITLE: 96 POS. MALE CONNECTOR ACC. DIN 41612 STYLE C CONTACTS, HIGH TEMP CONN

MOLEX INCORPORATED

DOCUMENT NO. SD-85003-0001
SHEET NO. 11 OF 12

SIZE A1

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

VIEW ON MATING SIDE

	32	31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	1
c	X	D	D	D	D	D	D	D	D	D	D	A	D	D	D	D	D	D	D	A	D	D	D	D	D	D	D	D	D	D	D	X
b	Y	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	D	Y
a	A	D	D	D	D	D	D	D	D	D	A	D	D	D	D	D	D	D	D	A	D	D	D	D	D	D	D	D	D	D	D	Z

A = 5 STANDARD CONTACTS L=3
X = 2 FMLB CONTACTS +0.4 L=3
Y = 2 FMLB CONTACTS +0.4 L=3
Z = 1 FMLB CONTACT +0.4 L=3
D = 86 LMFB CONTACTS -0.6 L=3

S= 96 TOTAL NUMBER OF CONTACTS

MARKING	STANDARD
PERFORMANCE LEVEL	G2/0 = CONTACT AREA LEVEL2 / TERMINATION TIN
FLUX PROOF	NO
FIXING CLIP	YES
DIMENSIONS	SD-85003-0001 SHT 11 (HIGH TEMP CONNECTOR)

CONTACT SYMBOL	PERFORMANCE LEVEL	CONTACT POSITION NUMBER
D	G2/0	a2-12, a14-21, a23-31, b2-31, c2-11, c13-20, c22-31
Z	G2/0	a1
Y	G2/0	b1, b32
X	G2/0	c1, c32
A	G2/0	a13, a22, a32, c12, c21

EC NO: 12005-0552 2005/04/25
DRW:NSSUDHIR 2005/04/25
CHK:DKPRASAD 2005/04/25
APPR:KPRASAD 2005/04/25
DESCRIPTION
REV B

QUALITY SYMBOLS
▼=0
▽=0

GENERAL TOLERANCES (UNLESS SPECIFIED)

	mm	INCH
4 PLACES	±---	±---
3 PLACES	±---	±---
2 PLACES	±---	±---
1 PLACE	±---	±---

ANGULAR ±---°

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE: MM ONLY
SCALE: NTS
DESIGN UNITS: METRIC
THIRD ANGLE PROJECTION

DRAWN BY: SIVAKUMA DATE: 2004/01/27
CHECKED BY: GJLOWE DATE: 2004/01/27
APPROVED BY: GJLOWE DATE: 2004/01/27

TITLE: 96 POS MALE CONNECTOR ACCORDING DIN 41612 STYLE C CONTACTS ARRANGE

molex MOLEX INCORPORATED

MATERIAL NO.: 85003-9036
DOCUMENT NO.: SD-85003-9036
SHEET NO.: 1 OF 1
SIZE: A1

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION