

	13	12	11	10	9	8	7	6	5	4	3	2	1																																																																																																					
J	<table><thead><tr><th>CATALOG NUMBER</th><th>MATERIAL NUMBER</th><th>CABLE RANGE</th><th>NOMINAL ROD DIAMETER</th><th>LENGTH "M"</th><th>LENGTH "B"</th><th>APPROXIMATE BREAK STRENGTH* (LBS / N)</th><th><div><div>UL</div><div>UL LISTED</div></div></th><th><div><div>CSA</div><div>CSA APPROVED</div></div></th><th>PRODUCT SELECTION NUMBER</th></tr></thead><tbody><tr><td>35850</td><td>1300950122</td><td>.50-.61 / 12.7-15.5</td><td>.55 / 14.0</td><td>11.00±1.50 / 279.4±38.1</td><td>5.00±0.50 / 127.0±12.7</td><td>5600 / 24910</td><td rowspan="10">NO</td><td rowspan="10">YES</td><td>PS050-1</td></tr><tr><td>35851</td><td>1300950123</td><td>.62-.74 / 15.7-18.8</td><td>.68 / 17.3</td><td>11.00±1.50 / 279.4±38.1</td><td>5.00±0.50 / 127.0±12.7</td><td>6800 / 30248</td><td>PS062-1</td></tr><tr><td>35867</td><td>1300950126</td><td>.75-.99 / 19.1-25.1</td><td>.87 / 22.1</td><td>20.00±2.00 / 508.0±50.8</td><td>6.00±0.50 / 152.4±12.7</td><td>9600 / 42703</td><td>PS075-2</td></tr><tr><td>35868</td><td>1300950127</td><td>1.00-1.24 / 25.4-31.5</td><td>1.12 / 28.4</td><td>20.00±2.00 / 508.0±50.8</td><td>7.00±1.00 / 177.8±25.4</td><td>16400 / 72951</td><td>PS100-2</td></tr><tr><td>35869</td><td>1300950128</td><td>1.25-1.49 / 31.8-37.8</td><td>1.37 / 34.8</td><td>21.00±2.50 / 533.4±63.5</td><td>7.00±1.00 / 177.8±25.4</td><td>16400 / 72951</td><td>PS125-2</td></tr><tr><td>35870</td><td>1300950129</td><td>1.50-1.99 / 38.1-50.5</td><td>1.74 / 44.2</td><td>25.00±2.50 / 635.0±63.5</td><td>7.00±1.00 / 177.8±25.4</td><td>27200 / 120992</td><td>PS150-2</td></tr><tr><td>35871</td><td>1300950130</td><td>2.00-2.49 / 50.8-63.2</td><td>2.24 / 56.9</td><td>26.00±2.50 / 660.4±63.5</td><td>8.00±1.00 / 203.2±25.4</td><td>33000 / 146791</td><td>PS200-2</td></tr><tr><td>35872</td><td>1300950131</td><td>2.50-2.99 / 63.5-75.9</td><td>2.74 / 69.6</td><td>28.00±2.50 / 711.2±63.5</td><td>10.00±1.00 / 254.0±25.4</td><td>41000 / 182377</td><td>PS250-2</td></tr><tr><td>35873</td><td>1300950132</td><td>3.00-3.49 / 76.2-88.6</td><td>3.24 / 82.3</td><td>30.00±3.50 / 762.0±88.9</td><td>10.00±1.00 / 254.0±25.4</td><td>48000 / 213515</td><td>PS300-2</td></tr><tr><td>35874</td><td>1300950133</td><td>3.50-3.99 / 88.9-101.3</td><td>3.74 / 95.0</td><td>32.00±3.50 / 812.8±88.9</td><td>10.00±1.00 / 254.0±25.4</td><td>48000 / 213515</td><td>PS350-2</td></tr><tr><td>35875</td><td>1300950134</td><td>4.00-4.49 / 101.6-114.0</td><td>4.24 / 107.7</td><td>33.00±3.50 / 838.2±88.9</td><td>10.00±1.00 / 254.0±25.4</td><td>48000 / 213515</td><td>PS400-2</td></tr></tbody></table>													CATALOG NUMBER	MATERIAL NUMBER	CABLE RANGE	NOMINAL ROD DIAMETER	LENGTH "M"	LENGTH "B"	APPROXIMATE BREAK STRENGTH* (LBS / N)	<div><div>UL</div><div>UL LISTED</div></div>	<div><div>CSA</div><div>CSA APPROVED</div></div>	PRODUCT SELECTION NUMBER	35850	1300950122	.50-.61 / 12.7-15.5	.55 / 14.0	11.00±1.50 / 279.4±38.1	5.00±0.50 / 127.0±12.7	5600 / 24910	NO	YES	PS050-1	35851	1300950123	.62-.74 / 15.7-18.8	.68 / 17.3	11.00±1.50 / 279.4±38.1	5.00±0.50 / 127.0±12.7	6800 / 30248	PS062-1	35867	1300950126	.75-.99 / 19.1-25.1	.87 / 22.1	20.00±2.00 / 508.0±50.8	6.00±0.50 / 152.4±12.7	9600 / 42703	PS075-2	35868	1300950127	1.00-1.24 / 25.4-31.5	1.12 / 28.4	20.00±2.00 / 508.0±50.8	7.00±1.00 / 177.8±25.4	16400 / 72951	PS100-2	35869	1300950128	1.25-1.49 / 31.8-37.8	1.37 / 34.8	21.00±2.50 / 533.4±63.5	7.00±1.00 / 177.8±25.4	16400 / 72951	PS125-2	35870	1300950129	1.50-1.99 / 38.1-50.5	1.74 / 44.2	25.00±2.50 / 635.0±63.5	7.00±1.00 / 177.8±25.4	27200 / 120992	PS150-2	35871	1300950130	2.00-2.49 / 50.8-63.2	2.24 / 56.9	26.00±2.50 / 660.4±63.5	8.00±1.00 / 203.2±25.4	33000 / 146791	PS200-2	35872	1300950131	2.50-2.99 / 63.5-75.9	2.74 / 69.6	28.00±2.50 / 711.2±63.5	10.00±1.00 / 254.0±25.4	41000 / 182377	PS250-2	35873	1300950132	3.00-3.49 / 76.2-88.6	3.24 / 82.3	30.00±3.50 / 762.0±88.9	10.00±1.00 / 254.0±25.4	48000 / 213515	PS300-2	35874	1300950133	3.50-3.99 / 88.9-101.3	3.74 / 95.0	32.00±3.50 / 812.8±88.9	10.00±1.00 / 254.0±25.4	48000 / 213515	PS350-2	35875	1300950134	4.00-4.49 / 101.6-114.0	4.24 / 107.7	33.00±3.50 / 838.2±88.9	10.00±1.00 / 254.0±25.4	48000 / 213515	PS400-2	J
CATALOG NUMBER	MATERIAL NUMBER	CABLE RANGE	NOMINAL ROD DIAMETER	LENGTH "M"	LENGTH "B"	APPROXIMATE BREAK STRENGTH* (LBS / N)	<div><div>UL</div><div>UL LISTED</div></div>	<div><div>CSA</div><div>CSA APPROVED</div></div>	PRODUCT SELECTION NUMBER																																																																																																									
35850	1300950122	.50-.61 / 12.7-15.5	.55 / 14.0	11.00±1.50 / 279.4±38.1	5.00±0.50 / 127.0±12.7	5600 / 24910	NO	YES	PS050-1																																																																																																									
35851	1300950123	.62-.74 / 15.7-18.8	.68 / 17.3	11.00±1.50 / 279.4±38.1	5.00±0.50 / 127.0±12.7	6800 / 30248			PS062-1																																																																																																									
35867	1300950126	.75-.99 / 19.1-25.1	.87 / 22.1	20.00±2.00 / 508.0±50.8	6.00±0.50 / 152.4±12.7	9600 / 42703			PS075-2																																																																																																									
35868	1300950127	1.00-1.24 / 25.4-31.5	1.12 / 28.4	20.00±2.00 / 508.0±50.8	7.00±1.00 / 177.8±25.4	16400 / 72951			PS100-2																																																																																																									
35869	1300950128	1.25-1.49 / 31.8-37.8	1.37 / 34.8	21.00±2.50 / 533.4±63.5	7.00±1.00 / 177.8±25.4	16400 / 72951			PS125-2																																																																																																									
35870	1300950129	1.50-1.99 / 38.1-50.5	1.74 / 44.2	25.00±2.50 / 635.0±63.5	7.00±1.00 / 177.8±25.4	27200 / 120992			PS150-2																																																																																																									
35871	1300950130	2.00-2.49 / 50.8-63.2	2.24 / 56.9	26.00±2.50 / 660.4±63.5	8.00±1.00 / 203.2±25.4	33000 / 146791			PS200-2																																																																																																									
35872	1300950131	2.50-2.99 / 63.5-75.9	2.74 / 69.6	28.00±2.50 / 711.2±63.5	10.00±1.00 / 254.0±25.4	41000 / 182377			PS250-2																																																																																																									
35873	1300950132	3.00-3.49 / 76.2-88.6	3.24 / 82.3	30.00±3.50 / 762.0±88.9	10.00±1.00 / 254.0±25.4	48000 / 213515			PS300-2																																																																																																									
35874	1300950133	3.50-3.99 / 88.9-101.3	3.74 / 95.0	32.00±3.50 / 812.8±88.9	10.00±1.00 / 254.0±25.4	48000 / 213515			PS350-2																																																																																																									
35875	1300950134	4.00-4.49 / 101.6-114.0	4.24 / 107.7	33.00±3.50 / 838.2±88.9	10.00±1.00 / 254.0±25.4	48000 / 213515	PS400-2																																																																																																											
I														I																																																																																																				
H														H																																																																																																				
G	<div><div><div>*TO DETERMINE RECOMMENDED WORKING LOAD, DIVIDE BREAK STRENGTH BY 5.</div></div><div><div>ROTATING EYE DIMENSIONS - REFERENCE</div><table><thead><tr><th>CATALOG NUMBER</th><th>DIAMETER "C"</th><th>LENGTH "D"</th><th>LENGTH "E"</th><th>LENGTH "F"</th><th>LENGTH "G"</th><th>LENGTH "H"</th></tr></thead><tbody><tr><td>35850</td><td>.875 / 22.23</td><td>.187 / 4.75</td><td>2.750 / 69.85</td><td>.281 / 7.14</td><td>.250 / 6.35</td><td>.875 / 22.23</td></tr><tr><td>35851</td><td>.875 / 22.23</td><td>.187 / 4.75</td><td>2.750 / 69.85</td><td>.281 / 7.14</td><td>.250 / 6.35</td><td>.875 / 22.23</td></tr><tr><td>35867</td><td>1.000 / 25.40</td><td>.219 / 5.56</td><td>3.625 / 92.08</td><td>.500 / 12.70</td><td>.312 / 7.92</td><td>.906 / 23.01</td></tr><tr><td>35868</td><td>1.375 / 34.93</td><td>.344 / 8.74</td><td>4.625 / 117.48</td><td>.500 / 12.70</td><td>.375 / 9.53</td><td>1.000 / 25.40</td></tr><tr><td>35869</td><td>1.375 / 34.93</td><td>.344 / 8.74</td><td>4.625 / 117.48</td><td>.500 / 12.70</td><td>.375 / 9.53</td><td>1.000 / 25.40</td></tr><tr><td>35870</td><td>1.375 / 34.93</td><td>.344 / 8.74</td><td>4.625 / 117.48</td><td>.500 / 12.70</td><td>.375 / 9.53</td><td>1.000 / 25.40</td></tr><tr><td>35871</td><td>1.625 / 41.275</td><td>.375 / 9.53</td><td>5.437 / 138.10</td><td>.625 / 15.88</td><td>.500 / 12.70</td><td>1.187 / 30.15</td></tr><tr><td>35872</td><td>1.875 / 47.625</td><td>.437 / 11.1</td><td>6.250 / 158.75</td><td>.656 / 16.66</td><td>.500 / 12.70</td><td>1.375 / 34.93</td></tr><tr><td>35873</td><td>1.875 / 47.625</td><td>.437 / 11.1</td><td>6.250 / 158.75</td><td>.656 / 16.66</td><td>.500 / 12.70</td><td>1.375 / 34.93</td></tr><tr><td>35874</td><td>1.875 / 47.625</td><td>.437 / 11.1</td><td>6.250 / 158.75</td><td>.656 / 16.66</td><td>.500 / 12.70</td><td>1.375 / 34.93</td></tr><tr><td>35875</td><td>1.875 / 47.625</td><td>.437 / 11.1</td><td>6.250 / 158.75</td><td>.656 / 16.66</td><td>.500 / 12.70</td><td>1.375 / 34.93</td></tr></tbody></table></div></div>													CATALOG NUMBER	DIAMETER "C"	LENGTH "D"	LENGTH "E"	LENGTH "F"	LENGTH "G"	LENGTH "H"	35850	.875 / 22.23	.187 / 4.75	2.750 / 69.85	.281 / 7.14	.250 / 6.35	.875 / 22.23	35851	.875 / 22.23	.187 / 4.75	2.750 / 69.85	.281 / 7.14	.250 / 6.35	.875 / 22.23	35867	1.000 / 25.40	.219 / 5.56	3.625 / 92.08	.500 / 12.70	.312 / 7.92	.906 / 23.01	35868	1.375 / 34.93	.344 / 8.74	4.625 / 117.48	.500 / 12.70	.375 / 9.53	1.000 / 25.40	35869	1.375 / 34.93	.344 / 8.74	4.625 / 117.48	.500 / 12.70	.375 / 9.53	1.000 / 25.40	35870	1.375 / 34.93	.344 / 8.74	4.625 / 117.48	.500 / 12.70	.375 / 9.53	1.000 / 25.40	35871	1.625 / 41.275	.375 / 9.53	5.437 / 138.10	.625 / 15.88	.500 / 12.70	1.187 / 30.15	35872	1.875 / 47.625	.437 / 11.1	6.250 / 158.75	.656 / 16.66	.500 / 12.70	1.375 / 34.93	35873	1.875 / 47.625	.437 / 11.1	6.250 / 158.75	.656 / 16.66	.500 / 12.70	1.375 / 34.93	35874	1.875 / 47.625	.437 / 11.1	6.250 / 158.75	.656 / 16.66	.500 / 12.70	1.375 / 34.93	35875	1.875 / 47.625	.437 / 11.1	6.250 / 158.75	.656 / 16.66	.500 / 12.70	1.375 / 34.93	G																
CATALOG NUMBER	DIAMETER "C"	LENGTH "D"	LENGTH "E"	LENGTH "F"	LENGTH "G"	LENGTH "H"																																																																																																												
35850	.875 / 22.23	.187 / 4.75	2.750 / 69.85	.281 / 7.14	.250 / 6.35	.875 / 22.23																																																																																																												
35851	.875 / 22.23	.187 / 4.75	2.750 / 69.85	.281 / 7.14	.250 / 6.35	.875 / 22.23																																																																																																												
35867	1.000 / 25.40	.219 / 5.56	3.625 / 92.08	.500 / 12.70	.312 / 7.92	.906 / 23.01																																																																																																												
35868	1.375 / 34.93	.344 / 8.74	4.625 / 117.48	.500 / 12.70	.375 / 9.53	1.000 / 25.40																																																																																																												
35869	1.375 / 34.93	.344 / 8.74	4.625 / 117.48	.500 / 12.70	.375 / 9.53	1.000 / 25.40																																																																																																												
35870	1.375 / 34.93	.344 / 8.74	4.625 / 117.48	.500 / 12.70	.375 / 9.53	1.000 / 25.40																																																																																																												
35871	1.625 / 41.275	.375 / 9.53	5.437 / 138.10	.625 / 15.88	.500 / 12.70	1.187 / 30.15																																																																																																												
35872	1.875 / 47.625	.437 / 11.1	6.250 / 158.75	.656 / 16.66	.500 / 12.70	1.375 / 34.93																																																																																																												
35873	1.875 / 47.625	.437 / 11.1	6.250 / 158.75	.656 / 16.66	.500 / 12.70	1.375 / 34.93																																																																																																												
35874	1.875 / 47.625	.437 / 11.1	6.250 / 158.75	.656 / 16.66	.500 / 12.70	1.375 / 34.93																																																																																																												
35875	1.875 / 47.625	.437 / 11.1	6.250 / 158.75	.656 / 16.66	.500 / 12.70	1.375 / 34.93																																																																																																												
F	<div><div><div>ROTATING EYE</div><div><div><div>LENGTH "G"</div><div>LENGTH "H"</div><div>DIAMETER "C"</div><div>LENGTH "F"</div><div>LENGTH "E"</div></div></div><div>SECTION Z-Z</div></div><div><div><div><div>6</div><div>5</div><div>4</div><div>3</div><div>2</div><div>1</div></div><div><div>LENGTH "D"</div><div>LENGTH "B"</div><div>LENGTH "M" MEASURED WITH NOMINAL ROD DIAMETER</div></div></div><div><div>DOUBLE WEAVE MESH CONSTRUCTION</div></div></div></div>													F																																																																																																				
E														E																																																																																																				
D														D																																																																																																				
C														C																																																																																																				
B	<div><div>INSTRUCTION SHEET TO BE INCLUDED WITH GRIP.</div><table><thead><tr><th>ITEM</th><th>DESCRIPTION</th><th>MATERIAL</th></tr></thead><tbody><tr><td>1</td><td>WIRE MESH</td><td>GALVANIZED STEEL</td></tr><tr><td>2</td><td>SHOULDER PROTECTOR</td><td>ALUMINUM</td></tr><tr><td>3</td><td>THREADED INSERT</td><td>STEEL</td></tr><tr><td>4</td><td>FLAT WASHERS</td><td>NYLATRON</td></tr><tr><td>5</td><td>SWAGING FERRULE</td><td>STEEL</td></tr><tr><td>6</td><td>ROTATING EYE</td><td>STEEL</td></tr></tbody></table><div><div><div>RELEASE SALES DRAWING</div><div>EC NO: IPG2014-1924</div><div>DRWN: HRUIZ01 2014/09/03</div><div>CHKD: HKNEELAN 2014/09/03</div><div>APPR: JFMURPHY 2015/03/23</div></div><div><div>QUALITY SYMBOL</div><div><div>▽=0</div><div>▽C=0</div></div></div><div><div>GENERAL TOLERANCES (UNLESS SPECIFIED)</div><table><thead><tr><th></th><th>mm</th><th>INCH</th></tr></thead><tbody><tr><td>4 PLACES</td><td>±---</td><td>±---</td></tr><tr><td>3 PLACES</td><td>±---</td><td>±.005</td></tr><tr><td>2 PLACES</td><td>±.13</td><td>±.010</td></tr><tr><td>1 PLACE</td><td>±.25</td><td>±.020</td></tr></tbody></table><div>ANGULAR ±1/2°</div><div>DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS</div></div><div><div>DIMENSION STYLE INCH/MM</div><table><thead><tr><th>DRAWN BY</th><th>DATE</th></tr></thead><tbody><tr><td>HRUIZ01</td><td>2014/09/03</td></tr><tr><th>CHECKED BY</th><th>DATE</th></tr><tr><td>HKNEELAN</td><td>2014/09/03</td></tr><tr><th>APPROVED BY</th><th>DATE</th></tr><tr><td>JFMURPHY</td><td>2015/03/23</td></tr></tbody></table><div>MATERIAL NO. SEE TABLE</div><div>SIZE C</div><div>THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION</div></div><div><div>SCALE NTS</div><div>DESIGN UNITS INCH</div><div><div>THIRD ANGLE PROJECTION</div></div><div><div>PULLING GRIPS HEAVY DUTY K-TYPE SHORT LENGTH MOLEX INCORPORATED</div></div><div><div>DOCUMENT NO. SD-130095-106</div><div>SHEET NO. 1 OF 1</div></div></div></div></div>													ITEM	DESCRIPTION	MATERIAL	1	WIRE MESH	GALVANIZED STEEL	2	SHOULDER PROTECTOR	ALUMINUM	3	THREADED INSERT	STEEL	4	FLAT WASHERS	NYLATRON	5	SWAGING FERRULE	STEEL	6	ROTATING EYE	STEEL		mm	INCH	4 PLACES	±---	±---	3 PLACES	±---	±.005	2 PLACES	±.13	±.010	1 PLACE	±.25	±.020	DRAWN BY	DATE	HRUIZ01	2014/09/03	CHECKED BY	DATE	HKNEELAN	2014/09/03	APPROVED BY	DATE	JFMURPHY	2015/03/23	B																																																				
ITEM	DESCRIPTION	MATERIAL																																																																																																																
1	WIRE MESH	GALVANIZED STEEL																																																																																																																
2	SHOULDER PROTECTOR	ALUMINUM																																																																																																																
3	THREADED INSERT	STEEL																																																																																																																
4	FLAT WASHERS	NYLATRON																																																																																																																
5	SWAGING FERRULE	STEEL																																																																																																																
6	ROTATING EYE	STEEL																																																																																																																
	mm	INCH																																																																																																																
4 PLACES	±---	±---																																																																																																																
3 PLACES	±---	±.005																																																																																																																
2 PLACES	±.13	±.010																																																																																																																
1 PLACE	±.25	±.020																																																																																																																
DRAWN BY	DATE																																																																																																																	
HRUIZ01	2014/09/03																																																																																																																	
CHECKED BY	DATE																																																																																																																	
HKNEELAN	2014/09/03																																																																																																																	
APPROVED BY	DATE																																																																																																																	
JFMURPHY	2015/03/23																																																																																																																	
A														A																																																																																																				
	13	12	11	10	9	8	7	6	5	4	3	2	1																																																																																																					