

Preliminary Datasheet

top view

CASING

GSA 3000, Hirschmann
 colour black / *Farbe schwarz*

CIRCUIT DIAGRAM

MARKING

MEDER-Label, Type
 Production code EN60062/
 Factory code, circuit diagram

MEDER-Logo, Typ
 Produktionscode
 EN60062/Fertigungsstätte
 Schaltbild

dimensions / Abmessungen (mm)
 unspecified tolerances acc. to DIN ISO 2768-m

Magnetic properties	Conditions	Min	Typ	Max	Unit
Pull in	at 20 °C				VDC
Test equipment				PK 082+KMS-19	

Special Product Data	Conditions	Min	Typ	Max	Unit
Contact - form				A - NO	
Contact rating	Any DC combination of V & A not to exceed their individual max.'s			10	W
operating voltage	DC or Peak AC			180	VDC
operating ampere	DC or Peak AC			1	A
Switching current	DC or Peak AC			0,5	A
Housing material				mineral-filled epoxy	
Case color				black	
Sealing compound				Polyurethan	

Environmental data	Conditions	Min	Typ	Max	Unit
Ambient temperature		-20		85	°C
Storage temperature		-35		85	°C

Customer side	Conditions	Min	Typ	Max	Unit
connector design				GSA 3000, Hirschmann	