
## INSULATED PC SPACERS/SUPPORTS

 Board will be electrically insulated, eliminates need for insulating washers 

#### ADHESIVE LOCK-IN RELEASE SUPPORTS

- One end attaches to chassis with self adhesive pads
- · No drilling to chassis required leaving outside in perfect condition
- Other end snap into .062 (1.57) board
- · Board is easily releasable for repair or upgrade



LENGTH 9080 .187 (4.7) 9081 .250 (6.4) 9082 .375 (9.5) 9083 .500 (12.7) 9084 .625 (15.9)

CAT.

NO.

8822

8823

8824

8825

8826

8827

8828

LENGTH

.187 (4.7)

.250 (6.4)

.375 (9.5)


.500 (12.7)

.625 (15.9)

.750 (19.1)

.875 (22.2)

Material: Nylon 6/6, UL Rated 94V-0



CAT NO.	-	L Length
907	0	.187 (4.7)
907	1	.250 (6.4)
907	2	.375 (9.5)
907	3	.500 (12.7)
907	4	.625 (15.9)

Material: Nylon 6/6, UL Rated 94V-0


#### PC SPACER SUPPORTS

- One end locks into chassis Other end supports the PC Board Ideal for mid supports of large boards
- · Simplifies assembly for multiple support applications · Reduces the amount of holes required in PC board


### STURDY SUPPORT



.187 (4.8)



- Accommodates varying board thicknesses
- Sturdy support due to large contact area




Material: Nylon 6/6, UL Rated 94V-0



.100 (2.8)

#### SLIMLINE SUPPORT

- One end permanently attaches to .062 (1.57) chassis
- · Low protrusion under chassis
- · Small diameter frees up space on PC board



Material: Nylon 6/6, UL Rated 94V-0

#### CAT. NO. LENGTH 9055 .125 (3.2) 9056 .187 (4.7) 9057 .250 (6.4) 9058 .375 (9.5) 9059 .500 (12.7) 9060 .625 (15.9)

#### REVERSE CHASSIS MOUNT SUPPORTS

Permanently attaches to .059 (1.51) - .065 (1.65) thick case from outside


• Provides flat clean cosmetic appearance • Ideal for low clearance applications or for mounting directly to case walls

# .156 (4.0)

.213 (5.4)

#### **LOCK-IN RELEASE** • End locks onto .062 (1.57) PC board

- · Board is positively locked until manually released
- Board is easily releasable for repairs or upgrades




Material: Nylon 6/6, UL Rated 94V-0



.187 (4.8)

- SLIMLINE LOCK-IN • End permanently attaches to .062 (1.57) PC board
- · Small footprint frees up PC board space



CAT. LENGTH NO. 9065 .250 (6.4) 9066 .375 (9.5) 9067 .500 (12.7) 9068 .625 (15.9)

Material: Nylon 6/6, UL Rated 94V-0

.625 (15.9)

LENGTH

.250 (6.4)

.375 (9.5)

.500 (12.7)

9061

9062

9063

9064

# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

# **Keystone Electronics:**

<u>8827</u> <u>8823</u> <u>8825</u> <u>8826</u> <u>8824</u> <u>8828</u> <u>8822</u> <u>9070</u> <u>9071</u> <u>9072</u> <u>9073</u> <u>9074</u> <u>9080</u> <u>9081</u> <u>9082</u> <u>9083</u> <u>9084</u> <u>9055</u> 9056 9057 9058 9059 9060 9061 9062 9063 9064 9065 9066 9067 9068