N-Channel 20-V (D-S) 175 °C MOSFET

PRODUCT SUMMARY		
$V_{(BR)DSS}$ (V)	$r_{DS(on)}$ (Ω)	I_D (A)[a]
20	0.0039 at V_{GS} = 10 V	60
	0.0052 at V_{GS} = 4.5 V	60

FEATURES


- TrenchFET® Power MOSFET
- 175 °C Junction Temperature
- 100 % R_g Tested
- 100 % UIS Tested

RoHS COMPLIANT

APPLICATIONS


- OR-ing

TO-263



Top View

DRAIN connected to TAB



N-Channel MOSFET

Ordering Information: SUM60N02-3m9P-E3 (Lead (Pb)-free)

ABSOLUTE MAXIMUM RATINGS T_A = 25 °C, unless otherwise noted				
Parameter		**Symbol**	**Limit**	**Unit**
Drain-Source Voltage		V_{DS}	20	V
Gate-Source Voltage		V_{GS}	± 20	
Continuous Drain Current (T_J = 175 °C)	T_C = 25 °C	I_D	60[a]	A
	T_C = 100 °C		60[a]	
Pulsed Drain Current		I_{DM}	120	
Single Pulse Avalanche Current	L = 0.1 mH	I_{AS}	50	
Single Pulse Avalanche Energy		E_{AS}	125	mJ
Maximum Power Dissipation[b]	T_C = 25 °C	P_D	120[c]	W
	T_A = 25 °C[d]		3.75	
Operating Junction and Storage Temperature Range		T_J, T_{stg}	- 55 to 175	°C

THERMAL RESISTANCE RATINGS			
Parameter	**Symbol**	**Limit**	**Unit**
Junction-to-Ambient (PCB Mount)[d]	R_{thJA}	40	°C/W
Junction-to-Case	R_{thJC}	1.25	


Notes:
a. Package limited.
b. Duty cycle ≤ 1 %.
c. See SOA curve for voltage derating.
d. When mounted on 1" square PCB (FR-4 material).

SPECIFICATIONS T_J = 25 °C, unless otherwise noted						
Parameter	**Symbol**	**Test Conditions**	**Min.**	**Typ.**	**Max.**	**Unit**
Static						
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	V_{DS} = 0 V, I_D = 250 µA	20			V
Gate-Threshold Voltage	$V_{GS(th)}$	V_{DS} = V_{GS}, I_D = 250 µA	1.0		3	
Gate-Body Leakage	I_{GSS}	V_{DS} = 0 V, V_{GS} = ± 20 V			± 100	nA
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS} = 20 V, V_{GS} = 0 V			1	µA
		V_{DS} = 20 V, V_{GS} = 0 V, T_J = 125 °C			50	
		V_{DS} = 20 V, V_{GS} = 0 V, T_J = 175 °C			250	
On-State Drain Current[a]	$I_{D(on)}$	$V_{DS} \geq$ 5 V, V_{GS} = 10 V	100			A
Drain-Source On-State Resistance[a]	$r_{DS(on)}$	V_{GS} = 10 V, I_D = 20 A		0.0031	0.0039	Ω
		V_{GS} = 10 V, I_D = 20 A, T_J = 125 °C			0.0059	
		V_{GS} = 10 V, I_D = 20 A, T_J = 175 °C			0.007	
		V_{GS} = 4.5 V, I_D = 20 A		0.0042	0.0052	
Forward Transconductance[a]	g_{fs}	V_{DS} = 10 V, I_D = 20 A		95		S
Dynamic[b]						
Input Capacitance	C_{iss}	V_{GS} = 0 V, V_{DS} = 10 V, f = 1 MHz		5950		pF
Output Capacitance	C_{oss}			985		
Reverse Transfer Capacitance	C_{rss}			365		
Total Gate Charge[b]	Q_g	V_{DS} = 10 V, V_{GS} = 4.5 V, I_D = 50 A		33	50	nC
Gate-Source Charge[b]	Q_{gs}			18		
Gate-Drain Charge[b]	Q_{gd}			7		
Gate Resistance	R_g		0.75	1.5	2.3	Ω
Turn-On Delay Time[b]	$t_{d(on)}$	V_{DD} = 10 V, R_L = 0.2 Ω $I_D \cong$ 50 A, V_{GEN} = 10 V, R_g = 1.0 Ω		15	25	ns
Rise Time[b]	t_r			7	11	
Turn-Off Delay Time[b]	$t_{d(off)}$			35	55	
Fall Time[b]	t_f			8	12	
Source-Drain Diode Ratings and Characteristics T_C = 25 °C[c]						
Continuous Current	I_S				60	A
Pulsed Current	I_{SM}				100	
Forward Voltage[a]	V_{SD}	I_F = 20 A, V_{GS} = 0 V		0.85	1.5	V
Reverse Recovery Time	t_{rr}	I_F = 20 A, di/dt = 100 A/µs		45	90	ns
Peak Reverse Recovery Current	I_{RM}			1.7	3.4	A
Reverse Recovery Charge	Q_{rr}			0.039	0.155	µC


Notes:
a. Pulse test; pulse width ≤ 300 µs, duty cycle ≤ 2 %
b. Independent of operating temperature.
c. Guaranteed by design, not subject to production testing.

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.


TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted




Output Characteristics




Transfer Characteristics




Transconductance



On-Resistance vs. Drain Current




On-Resistance vs. Gate-to-Source Voltage




Capacitance


TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted




Gate Charge




On-Resistance vs. Junction Temperature




Source-Drain Diode Forward Voltage



Threshold Voltage




Typical Drain-Source Brakdown Voltage vs. Junction Temperature




Single Pulse Avalanche Current vs. Time


TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted



Drain Current vs. Ambient Temperature



Safe Operating Area



Normalized Thermal Transient Impedance, Junction-to-Case

Vishay Siliconix maintains worldwide manufacturing capability. Products may be manufactured at one of several qualified locations. Reliability data for Silicon Technology and Package Reliability represent a composite of all qualified locations. For related documents such as package/tape drawings, part marking, and reliability data, see http://www.vishay.com/ppg?69820.

Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, “Vishay”), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay’s terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.