

Pb Free Plating Product

F16C20A thru F16C60A



16.0 Ampere Heatsink Common Anode Fast Recovery Rectifier Diode

Feature


- * Fast switching for high efficiency
- * Low forward voltage drop
- * High current capability
- * Low reverse leakage current
- * High surge current capability

Application

- * Automotive Environment(Inverters/Converters)
- * Plating Power Supply,Adaptor,SMPS and UPS
- * Car Audio Amplifiers and Sound Device System

Mechanical Data

- * Case:TO-220AB Heatsink
- * Epoxy: UL 94V-0 rate flame retardant
- * Terminals: Solderable per MIL-STD-202 method 208
- * Polarity: As marked on diode body
- * Mounting position: Any
- * Weight: 2.2 gram approximately



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Rating at 25°C ambient temperature unless otherwise specified.
 Single phase, half wave, 60Hz, resistive or inductive load.
 For capacitive load, derate current by 20%.

| | SYMBOL | F16C20C F16C20A F16C20D | F16C40C F16C40A F16C40D | F16C60C F16C60A F16C60D | UNIT |
|---|----------|-------------------------------|-------------------------------|-------------------------------|------|
| Maximum Recurrent Peak Reverse Voltage | VRRM | 200 | 400 | 600 | V |
| Maximum RMS Voltage | VRMS | 140 | 280 | 420 | V |
| Maximum DC Blocking Voltage | VDC | 200 | 400 | 600 | V |
| Maximum Average Forward Rectified Current Tc=100°C | IF(AV) | 16.0 | | | A |
| Peak Forward Surge Current, 8.3ms single Half sine-wave superimposed on rated load (JEDEC method) | IFSM | 175 | 150 | | A |
| Maximum Instantaneous Forward Voltage @ 8.0 A | VF | 0.98 | 1.3 | 1.7 | V |
| Maximum DC Reverse Current @Tj=25°C At Rated DC Blocking Voltage @Tj=125°C | IR | 10.0 | | | uA |
| | | 250 | | | uA |
| Maximum Reverse Recovery Time (Note 1) | Trr | 35 | | | nS |
| Typical junction Capacitance (Note 2) | CJ | 90 | | | pF |
| Typical Thermal Resistance (Note 3) | RθJC | 2.2 | | | °C/W |
| Operating Junction and Storage Temperature Range | TJ, TSTG | -55 to + 150 | | | °C |

NOTES : (1) Reverse recovery test conditions IF = 0.5A, R = 1.0A, Irr = 0.25A.
 (2) Measured at 1.0 MHz and applied reverse voltage of 4.0 Volts DC.
 (3) Thermal Resistance junction to case.

FIG.1 - FORWARD CURRENT DERATING CURVE




FIG.2 - MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG.3 - TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG.4 - TYPICAL REVERSE CHARACTERISTICS




FIG.5 - TYPICAL JUNCTION CAPACITANCE

