MINIATURE

Miniature Fuses are typically used to protect electronic devices, laboratory and measurement instruments, stereos, TV's, VCR's etc. They are available in four sizes with a current range of 20mA to 20 Amps.

Miniature Fuses are manufactured according to VDE 0820 part 1, VDE 0820 part 2, IEC publication 127, CEE publication 4 and actual DIN standards.

Slow
Typical Marking: "T"
Medium
Typical Marking: "M"
Fast
Typical Marking: "F"
Super Fast
Typical Marking: "FF"



5 x 20




5 x 25


Ordering Information

Current	Voltage 250V DIN 41662 IEC-127-2/III Cat. No. Slow	DIN 41571-2 Cat. No. Medium	DIN 41661 IEC-127-2/II Cat. No. Fast	Voltage 250V DIN 41571-2 Cat. No. Medium
20mA		0.02M5x20M		
32mA		0.032M5x20M		0.032M5x25M
40mA				0.04M5x25M
50mA	0.05M5x20T[4]	0.05M5x20M	0.05M5x20F[4]	0.05M5x25M
63mA		0.063M5x20M		0.063M5x25M
80mA	0.08M5x20T[4]	0.08M5x20M		0.08M5x25M
100mA	0.1M5x20T[4]	0.1M5x20M	0.1M5x20F[4]	0.1M5x25M
125mA	0.125M5x20T[4]	0.125M5x20M	0.125M5x20F[4]	0.125M5x25M
160mA	0.16M5x20T[4]	0.16M5x20M	0.16M5x20F[4]	0.16M5x25M
200mA	0.2M5x20T[4]	0.2M5x20M	0.2M5x20F[4]	0.2M5x25M
250mA	0.25M5x20T[4]	0.25M5x20M	0.25M5x20F[4]	0.25M5x25M
315mA	0.315M5x20T[4]	0.315M5x20M	0.315M5x20F[4]	0.315M5x25M
400mA	0.4M5x20T[4]	0.4M5x20M	0.4M5x20F[4]	0.4M5x25M
500mA	0.5M5x20T[4]	0.5M5x20M	0.5M5x20F[4]	0.5M5x25M
630mA	0.63M5x20T[4]	0.63M5x20M	0.63M5x20F[4]	0.63M5x25M
700mA	0.7M5x20T	0.7M5x20M	0.7M5x20F	
800mA	0.8M5x20T[4]	0.8M5x20M	0.8M5x20F[4]	0.8M5x25M
1.0A	1.0M5x20T[4]	1.0M5x20M	1.0M5x20F[4]	1.0M5x25M
1.25A	1.25M5x20T[4]	1.25M5x20M	1.25M5x20F[4]	1.25M5x25M
1.4A	1.4M5x20T	1.4M5x20M		
1.6A	1.6M5x20T[4]	1.6M5x20M	1.6M5x20F[4]	1.6M5x25M
2.0A	2.0M5x20T[4]	2.0M5x20M	2.0M5x20F[4]	2.0M5x25M
2.5A	2.5M5x20T[4]	2.5M5x20M	2.5M5x20F[4]	2.5M5x25M
3.15A	3.15M5x20T[4]	3.15M5x20M	3.15M5x20F[4]	3.15M5x25M
4.0A	4.0M5x20T[4]	4.0M5x20M	4.0M5x20F[4]	4.0M5x25M
5.0A	5.0M5x20T[4]	5.0M5x20M	5.0M5x20F[4]	5.0M5x25M
6.3A	6.3M5x20T[4]	6.3M5x20M	6.3M5x20F[4]	6.3M5x25M
7.0A				
8.0A	8.0M5x20T*	8.0M5x20M	8.0M5x20F*	8.0M5x25M *
10.0A	10.0M5x20T*	10.0M5x20M	10.0M5x20F*	10.0M5x25M *
12.5A	12.5M5x20T*	12.5M5x20M*	12.5M5x20F*	
16.0A	16.0M5x20T*	16.0M5x20M*	16.0M5x20F*	16.0M5x25M *
20.0A	20.0M5x20T*	20.0M5x20M*	20.0M5x20F*	
	Std. Pk. 10			Std. Pk. 10

All fuses listed are low breaking capacity. For high breaking capacity fuses please contact Altech.

* Not standard rating.
[1] Rated Voltage 500V.
[2] Rated Voltage 150V.
[3] Rated Voltage 60V.





Altech Corp.® • 35 Royal Road Flemington NJ 08822-6000 • Phone (908) 806-9400 • Fax (908) 806-9490 • www.altechcorp.com




5 x 25
with Indicator

Voltage 250V
DIN 41576-1, -2

Cat. No.	
Medium	Fast
0.08M5x25M/I	
0.1M5x25M/I	
0.125M5x25M/I	
0.16M5x25M/I	
0.2M5x25M/I	
0.25M5x25M/I	
0.315M5x25M/I	
0.4M5x25M/I	
0.5M5x25M/I	
0.63M5x25M/I	
0.8M5x25M/I	
1.0M5x25M/I	
1.25M5x25M/I	
1.6M5x25M/I	1.6M5x25F/I
2.0M5x25M/I	2.0M5x25F/I
2.5M5x25M/I	2.5M5x25F/I
3.15M5x25M/I	3.15M5x25F/I
4.0M5x25M/I	4.0M5x25F/I
5.0M5x25M/I	5.0M5x25F/I
6.3M5x25M/I	6.3M5x25F/I
8.0M5x25M/I*	8.0M5x25F/I*
10.0M5x25M/I*	10.0M5x25F/I*

Std. Pk. 10






5 x 30

Voltage 500V
DIN 41571-2

Cat. No.
Medium
0.032M5x30M
0.04M5x30M
0.05M5x30M
0.063M5x30M
0.08M5x30M
0.1M5x30M
0.125M5x30M
0.16M5x30M
0.2M5x30M
0.25M5x30M
0.315M5x30M
0.4M5x30M
0.5M5x30M
0.63M5x30M
0.8M5x30M
1.0M5x30M
1.25M5x30M
1.6M5x30M
2.0M5x30M
2.5M5x30M
3.15M5x30M
4.0M5x30M
5.0M5x30M
6.3M5x30M
8.0M5x30M*
10.0M5x30M*
16.0M5x30M*

Std. Pk. 10






6.3 x 32

Voltage 250V

Cat. No.	
Slow	Fast
0.032M6.3x32T[4]	
0.04M6.3x32T[4]	
0.05M6.3x32T[4]	0.05M6.3x32F
0.063M6.3x32T[4]	0.063M6.3x32F
0.08M6.3x32T[4]	0.08M6.3x32F
0.1M6.3x32T[4]	0.1M6.3x32F
0.125M6.3x32T[4]	0.125M6.3x32F
0.16M6.3x32T[4]	0.16M6.3x32F
0.2M6.3x32T[4]	0.2M6.3x32F
0.25M6.3x32T[4]	0.25M6.3x32F
0.315M6.3x32T[4]	0.315M6.3x32F
0.4M6.3x32T[4]	0.4M6.3x32F
0.5M6.3x32T[4]	0.5M6.3x32F
0.63M6.3x32T[4]	0.63M6.3x32F
0.7M6.3x32T	0.7M6.3x32F
0.8M6.3x32T[4]	0.8M6.3x32F
1.0M6.3x32T[4]	1.0M6.3x32F[4]
1.25M6.3x32T[4]	1.25M6.3x32F[4]
1.6M6.3x32T[4]	1.6M6.3x32F[4]
2.0M6.3x32T[4]	2.0M6.3x32F[4]
2.5M6.3x32T[4]	2.5M6.3x32F[2,4]
3.15M6.3x32T[4]	3.15M6.3x32F[2,4]
4.0M6.3x32T[4]	4.0M6.3x32F[2,4]
5.0M6.3x32T[4]	5.0M6.3x32F[3,4]
6.3M6.3x32T[4]	6.3M6.3x32F[3,4]
7.0M6.3x32T	7.0M6.3x32F[3]
8.0M6.3x32T	8.0M6.3x32F[3]
10.0M6.3x32T	10.0M6.3x32F[3]
12.5M6.3x32T	12.5M6.3x32F[3]
16.0M6.3x32T	16.0M6.3x32F[3]
20.0M6.3x32T	20.0M6.3x32F[3]

Std. Pk. 10



Non Stocked
By request only.