



RECOMMENDED HOLE LAYOUT

- 1 POINT OF MEASUREMENT FOR PLATING THICKNESS
- 2. ASSEMBLY MAY BE BROKEN TO THE DESIRED NUMBER OF POSITIONS.
- 3. TRUE POSITION TOLERANCE OF THE POST TIPS APPLIES WHEN THE HEADERS ARE HELD FLAT AGAINST THE PRINTED CIRCUIT BOARD
- 4 .000030 GOLD IN CONTACT AREA, .000100-.000200 MATTE TIN-LEAD ON SOLDER TAIL, ALL OVER .000050 NICKEL
- 5 BREAKAWY NOTCH ANGLE CAN BE ORIENTED TO THE RIGHT (AS SHOWN) OR TO THE LEFT
- 6 .000030 GOLD IN CONTACT AREA, .000100-.000200 MATTE TIN ON SOLDER TAIL, ALL OVER .000050 NICKEL
- 7 HIGH TEMPERATURE CONFIGURATION
- 8 OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

REV	DESCRIPTION	DATE	DWN	APVD
1	9-103765-0			
2	8-35			
3	8-30			
4	8-25			
5	7-20			
6	7-15			
7	6-14			
8	6-13			
9	6-12			
10	6-11			
11	6-10			
12	6-9			
13	6-8			
14	6-7			
15	6-5			
16	6-4			
17	6-3			
18	6-2			
19	6-1			
20	5-1			
21	5-103765-1			
22	4-40			
23	4-39			
24	4-38			
25	4-37			
26	4-36			
27	4-35			
28	4-34			
29	4-33			
30	4-32			
31	4-31			
32	4-30			
33	4-29			
34	4-28			
35	4-27			
36	4-26			
37	4-25			
38	4-24			
39	4-23			
40	4-22			
41	4-21			
42	4-20			
43	4-19			
44	4-18			
45	4-17			
46	4-16			
47	4-15			
48	4-14			
49	4-13			
50	4-12			
51	4-11			
52	4-10			
53	4-9			
54	4-8			
55	4-7			
56	4-6			
57	4-5			
58	4-4			
59	4-3			
60	4-2			
61	4-1			
62	103765-1			

8 SUPERCEDED BY 6-103765-4
8 OBSOLETE

8 SUPERCEDED BY 6-103765-1
8 OBSOLETE

REMARKS	PLATING	C	B	A	NO OF POS	ASSEMBLY PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIN L. D. RINGLEY 24JUL85
CHK R. FLICKER 24JUL85
APVD R. FLICKER 24JUL85

TE Connectivity

ASSEMBLY, MOD II, HEADER, BREAKAWAY, SINGLE ROW, RIGHT ANGLE 100, WITH .025 SQUARE POSTS

SIZE: A1 CAGE CODE: 00779 DRAWING NO: 103765

WEIGHT: --

CUSTOMER DRAWING SCALE: 4:1 SHEET 1 OF 1 REV G3