
This document was generated on 04/16/2010

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: 0541020204

Status: Active

Description: 0.50mm (.020") Pitch SlimStack™ Receptacle, Surface Mount, Dual Row, Vertical, 2.50mm (.098") Stacking Height, Gold Plating with Nickel Barrier, 20 Circuits



Series image - Reference only

Documents:

3D Model
Drawing (PDF)
Product Specification PS-54102-010 (PDF)
Product Specification PS-54102-011 (PDF)
RoHS Certificate of Compliance (PDF)

General

Product Family	PCB Receptacles
Series	54102
Application	Board-to-Board
Product Name	SlimStack™

Physical

Circuits (Loaded)	20
Color - Resin	Black
Durability (mating cycles max)	30
Glow-Wire Compliant	No
Lock to Mating Part	Yes
Mated Height (in)	0.098 In
Mated Height (mm)	2.50 mm
Material - Metal	Phosphor Bronze
Material - Plating Mating	Gold
Material - Plating Termination	Gold
Number of Rows	2
Orientation	Vertical
PCB Locator	No
PCB Retention	None
Packaging Type	Embossed Tape on Reel
Pitch - Mating Interface (in)	0.020 In
Pitch - Mating Interface (mm)	0.50 mm
Polarized to Mating Part	No
Polarized to PCB	No
Stackable	No
Temperature Range - Operating	-40°C to +85°C
Termination Interface: Style	Surface Mount

Electrical

Current - Maximum per Contact	0.5A
Voltage - Maximum	50V

Material Info

Reference - Drawing Numbers

Product Specification	PS-54102-010, PS-54102-011, RPS-54102-012, RPS-54102-013, RPS-54102-015, RPS-54102-017
Sales Drawing	SD-54102-006, SD-54102-007

EU RoHS
ELV and RoHS Compliant
REACH SVHC
Not Reviewed
Halogen-Free Status
Not Reviewed

China RoHS

Need more information on product environmental compliance?

Email productcompliance@molex.com
For a multiple part number RoHS Certificate of Compliance, click here


Please visit the Contact Us section for any non-product compliance questions.


Search Parts in this Series
54102Series

Mates With
500334 PCB Header, 53885 PCB Header


This document was generated on 04/16/2010


PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION






参考基板レイアウト（マウント面）
P.C.BOARD PATTERN DIMENSION (REF.)
(MOUNTING AREA)







SECT.Z-Z

注記 NOTES:

1. 使用材料 MATERIAL
   ハウジング：ポリフタルアミド（ＰＰＡ），
   ガラス充填。UL94V-0，色：黒
   HOUSING:POLYPHUTAL AMIDO(PPA),GLASS FILLED
   UL94V-0,COLOR:BLACK
   ターミナル：リン青銅（ｔ＝0．15）
   TERMINAL:PHOSPHOR BRONZE(t=0.15)
2. メッキ仕様PLATING
   金メッキ 0.25マイクロメートル以上（コンタクト部）
   GOLD(Au) 0.25 MICROMETER MINIMUM
   (CONTACT AREA)
   金メッキ 0.05マイクロメートル以上（テール部）
   GOLD(Au) 0.05 MICROMETER MINIMUM (TAIL AREA)
   下地メッキ：ニッケルメッキ 1.5 マイクロメートル以上
   UNDER PLATING
   : NICKEL 1.5 MICROMETER MINIMUM
   ＊コンタクト部とテール部はニッケルメッキによって
   分断されている金メッキです。
   DIVIDE INTO PARTS THE GOLD PLATING OF
   THE CONTACT PART AND THE TAIL PART BY
   THE NICKEL PLATING.
3. （全極数／2）＝偶数の場合に適用。
   APPLY FOR (CIRCUIT/2)=EVEN.
4. 嵌合相手：53885 /500334 シリーズ
   MATE WITH : 53885 / 500334 SERIES.
5. テール平坦度は、0.1MAX.
   TAIL COPLANARITY TO BE 0.1 MAXIMUM.

C	B	A	MATERIAL No.	極数 CIRCUIT
18.0	17.0	20.1	54102-0703	70
15.5	14.5	17.6	-0603	60
13.0	12.0	15.1	-0503	50
10.5	9.5	12.6	-0403	40
8.0	7.0	10.1	-0303	30
5.5	4.5	7.6	-0203	20
4.5	3.5	6.6	54102-0163	16

MODEL No. 54102-***3

REVISED
EC NO: J2005-1175 2004/10/29
DRWN:MUMEDA 2004/10/29
CHKD:KTOYODA 2004/11/01
APPR:NUKITA
REV A
DESCRIPTION

GENERAL TOLERANCES (UNLESS SPECIFIED)


10 UNDER	±0.2
10 OVER 30 UNDER	±0.25
30 OVER	±0.3
ANGULAR ±3 °	


DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS


DIMENSION STYLE: MM ONLY	SCALE: ---	DESIGN UNITS: METRIC	THIRD ANGLE PROJECTION
DRAWN BY: Y.SAKIYA	DATE: 2004/05/06	TITLE: 0.5 B-TO-B CONN REC HSG ASSY(HGT=2.5) [NI BARRIER]-LEAD FREE-	
CHECKED BY: M.SASAO	DATE: 2004/05/06		
APPROVED BY: M.SASAO	DATE: 2004/05/06	molex MOLEX INCORPORATED	
MATERIAL NO.: SEE CHART		DOCUMENT NO.: SD-54102-006	SHEET NO.: 1 OF 1


SIZE A3

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION










DETAIL F

NOTES

1. 製品詳細寸法については図面 SD-54102-006 を参照下さい。
   RE DETAILED DIMENSION, SEE SD-54102-006.
2. 梱包数量：３０００個／リール
   NUMBER OF CONNECTORS : 3000PCS/REEL
3. リードテープ長さ LEAD TAPE LENGTH

4. トップテープの剥離強度： 0.1 ～1.3N {10 ～130gf}
   （剥離方向は下図参照）
   尚、本規格値は出荷時に適用。（但し、輸送時に剥離が発生しないこと。）
   PEELING OFF FORCE OF TOP TAPE : 0.1～1.3N {10 ～130gf}
   (PEELING DIRECTION AS SHOWN IN FOLLOWING FIG,)
   THIS REQUIREMENT SHOULD BE APPLIED AT SHIPMENT.
   PEEL OFF SHOULD NOT BE ALLOWED , DURING TRANSPORTATION.



5. 材料(MATERIAL)
   キャリアテープ(CARRIER TAPE)：ポリプロピレン(POLYPROPYLENE)
   トップテープ(TOPTAPE)： PET , PE , PEF
   リール(REEL)：ポリスチレン（PS）<リサイクル材を含む>
   POLYSTYRENE(PS)<RECYCLE MATERIAL CONTAINED>

REVISED			
EC NO: J2005-1175	2004/10/29		
DRWN:MUMEDA	2004/10/29		
CHKD:KTOYODA	2004/11/01		
APPR:NUKITA			
REV	A	DESCRIPTION	


GENERAL TOLERANCES (UNLESS SPECIFIED)

10 UNDER	±0.2
10 OVER 30 UNDER	±0.25
30 OVER	±0.3
ANGULAR	±3 °

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE: MM ONLY	SCALE: ---	DESIGN UNITS: METRIC	THIRD ANGLE PROJECTION
DRAWN BY: Y.SAKIYA	DATE: 2004/05/06	TITLE: EMBSTP PKG FOR 0.5 B/B REC HSG ASSY (H=2.5) [NI BARRIER]-LEAD FREE-	
CHECKED BY: M.SASAO	DATE: 2004/05/06		
APPROVED BY: M.SASAO	DATE: 2004/05/06	molex MOLEX INCORPORATED	
MATERIAL NO.: SEE CHART		DOCUMENT NO.: SD-54102-007	SHEET NO.: 1 OF 3

SIZE A3 THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION



16mm幅キャリアテープ

16mm WIDTH CARRIER TAPE

キャリアテープ幅 CARRIER TAPE WIDTH	E	D	(A)	MATERIAL NO.	極数 CIRCUITS
16	21.4	17.4	7.8	54102-0204	20
			6.8	54102-0164	16

MODEL NO. 54102-***4

REVISED
EC NO: J2005-1175 2004/10/29
DRWN:MUMEDA 2004/10/29
CHKD:KTOYODA 2004/11/01
APPR:NUKITA
DESCRIPTION
REV A

GENERAL TOLERANCES (UNLESS SPECIFIED)

10 UNDER	±0.2
10 OVER 30 UNDER	±0.25
30 OVER	±0.3
ANGULAR ±3 °	

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE: MM ONLY
SCALE: ---
DESIGN UNITS: METRIC
THIRD ANGLE PROJECTION

DRAWN BY: Y.SAKIYA DATE: 2004/05/06
CHECKED BY: M.SASAO DATE: 2004/05/06
APPROVED BY: M.SASAO DATE: 2004/05/06


TITLE: EMBSTP PKG FOR 0.5 B/B REC HSG ASSY (H=2.5) [NI BARRIER]-LEAD FREE-

molex MOLEX INCORPORATED


MATERIAL NO.: SEE CHART
DOCUMENT NO.: SD-54102-007
SHEET NO.: 2 OF 3

SIZE A3

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION



32mm幅キャリアテープ
32mm WIDTH CARRIER TAPE



24mm幅キャリアテープ
24mm WIDTH CARRIER TAPE

キャリアテープ幅 CARRIER TAPE WIDTH	E	D	(A)	MATERIAL NO.	極数 CIRCUITS
32	37.4	33.4	20.3	54102-0704	70
			17.8	54102-0604	60
24	29.4	25.4	15.3	54102-0504	50
			12.8	54102-0404	40
			10.3	54102-0304	30

MODEL NO. 54102-***4

REVISED
EC NO: J2005-1175 2004/10/29
DRWN:MUMEDA 2004/10/29
CHKD:KTOYODA 2004/11/01
APPR:NUKITA
DESCRIPTION
REV A

GENERAL TOLERANCES (UNLESS SPECIFIED)

10 UNDER	±0.2
10 OVER 30 UNDER	±0.25
30 OVER	±0.3
ANGULAR ±3 °	

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE: MM ONLY	SCALE: ---	DESIGN UNITS: METRIC	THIRD ANGLE PROJECTION
DRAWN BY: Y.SAKIYA DATE: 2004/05/06	TITLE: EMBSTP PKG FOR 0.5 B/B REC HSG ASSY (H=2.5) [NI BARRIER]-LEAD FREE-		
CHECKED BY: M.SASAO DATE: 2004/05/06			
APPROVED BY: M.SASAO DATE: 2004/05/06	molex MOLEX INCORPORATED		
MATERIAL NO.: SEE CHART	DOCUMENT NO.: SD-54102-007		SHEET NO.: 3 OF 3

SIZE A3

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION