

SPECIFICATION SHEET
JFW MODEL 50KFA-014
FIXED ATTENUATOR KIT

JFW Industries, Inc.
 Phone: 317-887-1340
 sales@jfwindustries.com
 www.jfwindustries.com

Description Kit of fixed attenuators supplied together in a case

Frequency Range DC-18 GHz

Impedance 50 Ohms nominal

RF Connectors SMA male/female

RF Input Power 2 Watts average @ +25°C
 Derate to 0.5 Watts @ +125°C

Parts Included (1 piece) 3dB fixed attenuator, SMA male/female
 (1 piece) 6dB fixed attenuator, SMA male/female
 (1 piece) 10dB fixed attenuator, SMA male/female
 (1 piece) 20dB fixed attenuator, SMA male/female

Model Numbers for Each Individual Part 50HF-003 SMA (3dB Fixed Attenuator, SMA male/female)
 50HF-006 SMA (6dB Fixed Attenuator, SMA male/female)
 50HF-010 SMA (10dB Fixed Attenuator, SMA male/female)
 50HF-020 SMA (20dB Fixed Attenuator, SMA male/female)

Calibration Frequencies Each fixed attenuator has its attenuation recorded at each of the following frequencies:
 DC, 4 GHz, 8GHz, 12.4 GHz, 18GHz

ECR/ECN #	DATE	REV	APPR / DATE	ECR/ECN #	DATE	REV	APPR / DATE
	09/24/2014		TRS 09/24/2014				