



**60 Watt Universal 3-Wire Input Adapter**  
**PSAC60M Power Adapter Meets Level V Efficiency Requirements**



**Features**

- Low Cost
- Efficiency Level V Compliance
- Class B EMI
- Ecodesign ErP Directive 2009/125/EC Compliant
- Non-vented/Spill Proof Case
- No Load Power Consumption < 0.5W
- Low Profile Design
- EISA Compliant

**Applications**

- Portable Equipment
- Peripherals
- Networking
- Gaming Machines

**Safety Approvals**

- CE
- cUL/UL

**Mechanical Characteristics**

- Length: 130mm (5.12in)
- Width: 60mm (2.36in)
- Height: 32mm (1.30in)
- Weight: 305g (10.76oz)

**Output Specifications**

Model	DC Output Voltage	Load		Ripple <sup>(1)</sup> P-P (max.)	Regulation Line & Load	Efficiency Level
		Min.	Max.			
PSAC60M-120	+12V	0A	5.0A	200mV	±5%	V
PSAC60M-240	+24V	0A	2.5A	350mV	±5%	V
PSAC60M-480	+48V	0A	1.25A	480mV	±5%	V
PSAC60M-560	+56V	0A	1.08A	560mV	±5%	V

(1) Measured with a 10uF capacitor and a 0.1uF capacitor at output connector terminal and oscilloscope set at 20MHz.

Phihong is not responsible for any error, and reserves the right to make changes without notice. Please visit our website at [www.phihong.com](http://www.phihong.com) for the most up-to-date specifications and contact information.

**Input:**

**AC Input Voltage Rating**

100 to 240V AC

**AC Input Frequency**

47 to 63Hz

**Input Current**

1.5A at 120V AC

0.7A at 240V AC

**Inrush Current**

90A maximum at 100V AC

150A maximum at 240V AC

(Cold Start at ambient 25°C)

**Leakage Current**

3.5mA maximum at 254V AC and 60Hz

**Input Power Saving**

< 0.5W at no load

**Output:**

**Output Power**

60W maximum

**Efficiency**

Meets requirements for Level V marking

**Environmental:**

**Temperature**

Operation 0 to +40°C

Non-operation -20 to +70°C

Humidity 5 to 90%

**Emissions**

FCC Part 15 Class B

EN55022 Class B

**Immunity**

IEC61000-4-2 Level 4

IEC61000-4-5 Level 3

**Over-Voltage Protection**

Circuit will latch the auto-restart.

**Over-Current Protection**

Circuit will latch

**Short-Circuit Protection**

If output shorts then circuit will auto-restart

**Isolation**

Primary to Secondary: 500V DC >7M OHM

**Dielectric Withstand (Hi-pot) Test**

Primary to Secondary: 3000V AC for 1 min., 10mA

**Dimension Diagram Unit: mm**

