
STC08IE120HV

Emitter Switched Bipolar Transistor
ESBT® 1200 V - 8 A - 0.10 Ω

General features

$V_{CS(ON)}$	I_C	$R_{CS(ON)}$
0.8 V	8 A	0.10 Ω

- High voltage / high current Cascode configuration
- Low equivalent on resistance
- very fast-switch up to 150 kHz
- Squared RBSOA up to 1200V
- Very low C_{iss} driven by R_G = 47Ω
- Very low turn-off cross over time



TO247-4L HV

Applications


- Flyback / forward SMPS
- Sepic PFC

Description

The STC08IE120HV is manufactured in Monolithic ESBT Technology, aimed to provide best performances in high frequency / high voltage applications.

It is designed for use in Gate Driven based topologies.

Internal schematic diagrams



Order codes

Part Number	Marking	Package	Packaging
STC08IE120HV	C08IE120HV	TO247-4L HV	Tube

Contents

1 **Electrical ratings** 3

2 **Electrical characteristics** 4

2.1 Electrical characteristics (curves) 5

2.2 Test circuits 7

3 **Package mechanical data** 8

4 **Revision history** 10

1 Electrical ratings

Table 1. Absolute maximum rating

Symbol	Parameter	Value	Unit
$V_{CS(SS)}$	Collector-source voltage (V_{BS} = V_{GS} = 0 V)	1200	V
$V_{BS(OS)}$	Base-source voltage (I_C = 0, V_{GS} = 0 V)	30	V
$V_{SB(OS)}$	Source-base voltage (I_C = 0, V_{GS} = 0 V)	17	V
V_{GS}	Gate-source voltage	± 17	V
I_C	Collector current	8	A
I_{CM}	Collector peak current (t_P < 5ms)	24	A
I_B	Base current	6	A
I_{BM}	Base peak current (t_P < 5ms)	12	A
P_{tot}	Total dissipation at T_c = 25°C	208	W
T_{stg}	Storage temperature	-40 to 150	°C
T_J	Max. operating junction temperature	150	°C

Table 2. Thermal data

Symbol	Parameter		Value	Unit
$R_{thj\text{-}case}$	Thermal resistance junction-case	max	0.6	°C/W

2 Electrical characteristics

(T_{case} = 25°C unless otherwise specified)

Table 3. Electrical characteristics

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
$I_{CS(SS)}$	Collector-source current (V_{BS} = V_{GS} = 0)	V_{CE} = 1200V			100	µA
$I_{BS(OS)}$	Base-source current (I_C = 0, V_{GS} = 0)	$V_{BS(OS)}$ = 30V			10	µA
$I_{SB(OS)}$	Source-base current (I_C = 0, V_{GS} = 0)	$V_{SB(OS)}$ = 17V			100	µA
$I_{GS(OS)}$	Gate-source leakage	V_{GS} = ± 17V			100	nA
$V_{CS(ON)}$	Collector-source ON voltage	V_{GS} = 10V I_C = 8A I_B = 1.6A V_{GS} = 10V I_C = 4A I_B = 0.4A		0.8 0.5	1 1.2	V V
h_{FE}	DC current gain	V_{GS} = 10V I_C = 8A V_{CS} = 1V V_{GS} = 10V I_C = 4A V_{CS} = 1V	5 7			
$V_{BS(ON)}$	Base Source ON voltage	V_{GS} = 10V I_C = 8A I_B = 1.6A V_{GS} = 10V I_C = 4A I_B = 0.4A		1.5 1.5		V V
$V_{GS(th)}$	Gate threshold voltage	V_{BS} = V_{GS} I_B = 250µA	2	3	4	V
C_{ISS}	Input capacitance	V_{CS} = 25V f = 1MHz V_{GS} = 0		550		pF
$Q_{GS(tot)}$	Gate-source charge	V_{GS} = 10V		26		nC
t_s t_f	INDUCTIVE LOAD Storage time Fall time	I_C = 4A I_B = 0.8A V_{GS} = 10V V_{Clamp} = 960V R_G = 47Ω t_p = 4µs		670 15		ns ns
t_s t_f	INDUCTIVE LOAD Storage time Fall time	I_C = 4A I_B = 0.4A V_{GS} = 10V V_{Clamp} = 960V R_G = 47Ω t_p = 4µs		340 10.2		ns ns
V_{CSW}	Maximum collector-source voltage switched without snubber	R_G = 47Ω h_{FE} = 5A I_C = 8A	1200			V
$V_{CS(dyn)}$	Collector-source dynamic voltage (500ns)	V_{CC} = V_{Clamp} = 400V V_{GS} = 10V R_G = 47Ω I_C = 4A I_B = 0.8A I_{Bpeak} = 4A t_{peak} = 500ns		5.75		V
$V_{CS(dyn)}$	Collector-source dynamic voltage (1 µs)	V_{CC} = V_{Clamp} = 400V V_{GS} = 10V R_G = 47Ω I_C = 4A I_B = 0.8A I_{Bpeak} = 4A t_{peak} = 500ns		3.35		V

2.1 Electrical characteristics (curves)

Figure 1. Output characteristics




Figure 2. DC current gain




Figure 3. Collector-source On voltage




Figure 4. Collector-source On voltage




Figure 5. Base-source On voltage




Figure 6. Base-source On voltage




Figure 7. Reverse biased safe operting area




Figure 8. Gate threshold voltage vs temperature




Figure 9. Dynamic collector-emitter saturation voltage




Figure 10. Inductive load switching time






Figure 11. Inductive load switching time



2.2 Test circuits

Figure 12. Inductive load switching and RBSOA test circuit




3 Package mechanical data

In order to meet environmental requirements, ST offers these devices in ECOPACK® packages. These packages have a Lead-free second level interconnect. The category of second level interconnect is marked on the package and on the inner box label, in compliance with JEDEC Standard JESD97. The maximum ratings related to soldering conditions are also marked on the inner box label. ECOPACK is an ST trademark. ECOPACK specifications are available at: www.st.com

TO247-4LHV MECHANICAL DATA

DIM.	mm.		
	MIN.	TYP	MAX.
A	4.85		5.15
A1	2.20	2.50	2.60
A2		1.27	
b	0.95	1.10	1.30
b2	2.50		2.90
c	0.40		0.80
D	23.85	24	24.15
D1		21.50	
E	15.45	15.60	15.75
e	2.54		
e1	5.08		
L	10.20		10.80
L1	2.20	2.50	2.80
L2		18.50	
L3		3	
∅P	3.55		3.65
S		5.50	



4 Revision history

Table 4. Revision history

Date	Revision	Changes
11-May-2006	1	Initial release.
16-Oct-2006	2	The lower temperature storage limit has been modified on page 3.
12-Jan-2007	3	The device's commercial code has been changed from preliminary to full.

Please Read Carefully:

IInformation in this document is provided solely in connection with ST products. STMicroelectronics NV and its subsidiaries (“ST”) reserve the right to make changes, corrections, modifications or improvements, to this document, and the products and services described herein at any time, without notice.

All ST products are sold pursuant to ST’s terms and conditions of sale.

Purchasers are solely responsible for the choice, selection and use of the ST products and services described herein, and ST assumes no liability whatsoever relating to the choice, selection or use of the ST products and services described herein.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted under this document. If any part of this document refers to any third party products or services it shall not be deemed a license grant by ST for the use of such third party products or services, or any intellectual property contained therein or considered as a warranty covering the use in any manner whatsoever of such third party products or services or any intellectual property contained therein.

UNLESS OTHERWISE SET FORTH IN ST’S TERMS AND CONDITIONS OF SALE ST DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY WITH RESPECT TO THE USE AND/OR SALE OF ST PRODUCTS INCLUDING WITHOUT LIMITATION IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION), OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT.

UNLESS EXPRESSLY APPROVED IN WRITING BY AN AUTHORIZE REPRESENTATIVE OF ST, ST PRODUCTS ARE NOT RECOMMENDED, AUTHORIZED OR WARRANTED FOR USE IN MILITARY, AIR CRAFT, SPACE, LIFE SAVING, OR LIFE SUSTAINING APPLICATIONS, NOR IN PRODUCTS OR SYSTEMS, WHERE FAILURE OR MALFUNCTION MAY RESULT IN PERSONAL INJURY, DEATH, OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE. ST PRODUCTS WHICH ARE NOT SPECIFIED AS “AUTOMOTIVE GRADE” MAY ONLY BE USED IN AUTOMOTIVE APPLICATIONS AT USER’S OWN RISK.

Resale of ST products with provisions different from the statements and/or technical features set forth in this document shall immediately void any warranty granted by ST for the ST product or service described herein and shall not create or extend in any manner whatsoever, any liability of ST.

ST and the ST logo are trademarks or registered trademarks of ST in various countries.

Information in this document supersedes and replaces all information previously supplied.

The ST logo is a registered trademark of STMicroelectronics. All other names are the property of their respective owners.

© 2007 STMicroelectronics - All rights reserved

STMicroelectronics group of companies

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan - Malaysia - Malta - Morocco - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States of America

www.st.com