Product data sheet Characteristics

8502SCO5V02S

NEMA Contactor, Type S, nonreversing, Size 1, 27A, 3 HP at 230 VAC, 1 phase, up to 100 kA, 1 pole, 120 VAC coil, open

Product availability: Non-Stock - Not normally stocked in distribution facility





Main

Product Type	Contactor		
Туре	8502S		
Control Circuit Type	Separate control circuit		
Control Circuit Voltage	120 V AC 60 Hz 110 V AC 50 Hz	reilea Geilea	
Contactor Type	Non-reversing	<u> </u>	
Current Rating	27 A		
Number of Poles	1P		
Phase	1 phase		
Horsepower Rating	3 HP 230 V AC 2 HP 115 V AC		
Maximum Voltage Rating	600 V AC	9	
SCCR	Circuit-breaker 70 A maximum, SCCR: 100 kA at 480 V AC Fuse J 60 A maximum, SCCR: 100 kA at 600 V AC Fuse T 60 A maximum, SCCR: 100 kA at 600 V AC Fuse RK1 60 A maximum, SCCR: 100 kA at 600 V AC Fuse RK5 60 A maximum, SCCR: 100 kA at 600 V AC	s. substitute for and is not to be used for determining suitshillity or reliability of these non	
Control Units	No control units	94	
Pilot Light	No indicator		
Auxiliary Contacts	Without	4	
Control Circuit Fusing	Fuse not supplied	<u> </u>	
Electrical Connection	Screw clamp terminals	<u>.</u> <u>9</u>	
Enclosure Type	Not rated (open device)		
Certifications	UL listed file E78351 CCN NLDX CSA	lainer. This chorumentation is not intended as	
NEMA Size	1		
Height	4.34 in (110.24 mm)		

Depth	4.22 in (107.19 mm)
Width	3.22 in (81.79 mm)

Ordering and shipping details

Category	21192 - 8502,36 SC,SD(NOT S*R,T,W)
Discount Schedule	CP1
GTIN	00785901764106
Nbr. of units in pkg.	1
Package weight(Lbs)	2.92 lb(US) (1.32 kg)
Returnability	No
Country of origin	MX

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Not compliant	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information.	

Contractual warranty

	•		
Warranty	18	months	