

FEATURES :

- 15 Watt Package
- 4:1Wide Input Voltage
- 100% Burned In
- High Efficiency To 86%
- Customized Solutions Available
- UL94V-0 Package Material
- Operating Temperature:-40°C TO +85°C
- 3 Years Warranty

Specifications typical at TA=25°C, nominal input voltage and rated output current unless otherwise specified

Part Number	Input Voltage	Input Current		Output Voltage	Output Current	Efficiency	Capacitor Load
	Vdc	No-Load (mA TYP)	Full Load (mA TYP)	Vdc	Full Load (mA)	%TYP	uF TYP
67DW-24S05RNL	9-36	25	753	5	3000	83	3300
67DW-24S09RNL	9-36	25	744	9	1666	84	680
67DW-24S12RNL	9-36	25	735	12	1250	85	680
67DW-24S15RNL	9-36	25	726	15	1000	86	470
67DW-24D05RNL	9-36	25	753	±5	±1500	83	±2200
67DW-24D09RNL	9-36	25	744	±9	±833	84	±470
67DW-24D12RNL	9-36	25	735	±12	±625	85	±470
67DW-24D15RNL	9-36	25	726	±15	±500	86	±330
67DW-48S05RNL	18-72	20	376	5	3000	83	3300
67DW-48S09RNL	18-72	20	372	9	1666	84	680
67DW-48S12RNL	18-72	20	367	12	1250	85	680
67DW-48S15RNL	18-72	20	363	15	1000	86	470
67DW-48D05RNL	18-72	20	376	±5	±1500	83	±2200
67DW-48D09RNL	18-72	20	372	±9	±833	84	±470
67DW-48D12RNL	18-72	20	367	±12	±625	85	±470
67DW-48D15RNL	18-72	20	363	±15	±500	86	±330

Input Specifications

Parameters	Conditions	Min	Typ	Max	Units
Voltage Types				4:1	
Filter	PI TYPE				

Output Specifications

Parameters	Conditions	Min	Typ	Max	Units
Voltage Tolerance	Full load@Vin(nom.)			±2	%
Short Circuit Protection	Hiccup, automatic recovery				
Line Regulation				±0.5	%
Load Regulation	Single (25% to 100%)			±1.0	%
Load Regulation	Dual (25% to 100%,Balance Load)			±2.0	%
Cross Regulation	DUAL (25% to 100% F.L)			±5.0	%
Ripple & Noise	BW=DC To 20MHz			100	mVp-p
Transient response setting time	25% load step change		350		us

YUAN DEAN SCIENTIFIC



DC-DC Converter

67DW SERIES

15Watt 1.5KV Isolated


4 : 1 Input Voltage Range

Single & Dual Output

2" x 1"



Temperature Derating Graph



www.yds.com.tw




TEL : 886-6-3842899 FAX : 886-6-3843288
E-MAIL : ydsweb@yds.com.tw

Rev:0 2018/10/31


Tolerance Envelope Graph

Output Current (%)	Output Voltage (%)
10	120
20	119.5
30	119
40	118.5
50	118
60	117.5
70	117
80	116.5
90	116
100	115.5
110	115
120	108

Part Number



Recommended Test Circuit



PIN Connection

www.yds.com.tw

