

The scalable compact rack server

NEC Express5800/R120g-2M



Key Features

- Support for the latest Intel® Xeon® E5-2600 v4 product family
- Up to 1.5 TB of high speed DDR4 memory
- 8 PCIe slots for various needs and future expansion
- Graphics Card Installation Kit allows 300W GPU card installation
- Agent-less management with improved EXPRESSSCOPE Engine 3
- Wide range of operating ambient temperature from 5 to 45°C (41 to 113°F)

Overview

The NEC Express5800/R120g-2M, a scalable dual-socket 2U rack server, provides outstanding performance, scalability, and flexibility. Powered by the high performance and energy efficient Intel® Xeon® processor E5-2600 v4 product family, combining up to two 22-core and 145 watt processors, 24 DIMM slots, 16 hot-plug drive bays, and 8 PCIe

3.0 slots, the R120g-2M provides a massive resource pool for memory-, processor-, and storage-intensive applications in mid-size to large enterprises, or the most demanding applications such as virtualization solutions and large database servers.

Features

Distinguished Performance and Capability

Featuring the Intel® Xeon® Processor E5-2600 v4 product family with up to 22-core and 55 MB last level cache, up to 1.5 TB memory with 2400 MHz speed, and up to 32 TB of storage capacity, the R120g-2M is ideal for memory-, processor-, and storage-intensive applications in mid-size to large enterprises, or the most demanding applications such as virtualization solutions and large database servers.

Flexibility for Various Workloads

The R120g-2M delivers enterprise-class flexibility, expandability, and reliability to meet your business needs. The platform features a wide range of server and upgrade options with 24 memory slots, 16 2.5-inch drive bays, 1 PCIe slot for a flexible integrated NIC, 1 PCIe slot for a dedicated RAID controller, and 6 PCIe slots for various computing needs and future business growth. The redundant storage, fan, and power supply options make the system reliable to support business continuity. Also, an optional Graphics Card Installation Kit allows 300W GPU card installation for high performance applications.

Operational Cost Savings and Efficiency

NEC's innovative green design concepts and industry leading fan control technology allows the R120g-2M to operate at temperatures up to 45°C (113°F), therefore reducing cooling requirements. In addition, dual hot plug power supplies with cold-standby mode enable further energy savings.

Manage easy setup and deployment with NEC EXPRESSBUILDER and leverage easy management with NEC's EXPRESSSCOPE Engine 3 together with NEC ESM PRO. The extensive remote management capabilities untangle the complexities in operating and maintaining the server to alleviate the burden of administrative tasks.

Hardware Specifications

MODEL	Express5800/R120g-2M
Form factor / height	2U Rack
Number of processors	1 to 2
Processors	Intel® Xeon® Processor E5-2603 v4 (1.70 GHz/6-core/15 MB) Intel® Xeon® Processor E5-2620 v4 (2.10 GHz/8-core/20 MB) Intel® Xeon® Processor E5-2623 v4 (2.60 GHz/4-core/10 MB) Intel® Xeon® Processor E5-2630 v4 (2.20 GHz/10-core/25 MB) Intel® Xeon® Processor E5-2637 v4 (3.50 GHz/4-core/15 MB) Intel® Xeon® Processor E5-2640 v4 (2.40 GHz/10-core/25 MB) Intel® Xeon® Processor E5-2643 v4 (3.40 GHz/6-core/20 MB) Intel® Xeon® Processor E5-2650 v4 (2.20 GHz/12-core/30 MB) Intel® Xeon® Processor E5-2667 v4 (3.20 GHz/8-core/25 MB) Intel® Xeon® Processor E5-2680 v4 (2.40 GHz/14-core/35 MB) Intel® Xeon® Processor E5-2690 v4 (2.60 GHz /14-core/35 MB) Intel® Xeon® Processor E5-2697 v4 (2.30 GHz/18-core/45 MB) Intel® Xeon® Processor E5-2697A v4 (2.60 GHz/16-core/40 MB) Intel® Xeon® Processor E5-2698 v4 (2.20 GHz/20-core/50 MB) Intel® Xeon® Processor E5-2699 v4 (2.20 GHz/22-core/55 MB)
Memory type	DDR4-2400 ECC RDIMM
Memory slots	24
Maximum memory	1.5 TB
Storage type	Hot plug 2.5-inch SAS HDD Hot plug 2.5-inch SATA HDD Hot plug 2.5-inch SAS SSD Hot plug 2.5-inch SATA SSD
Maximum internal drive bays	8 to 16 with optional drive cage
Maximum internal storage	32 TB
Removable media	1 bay for optical drive 1 bay for internal removable drive
Expansion slots	6 PCIe x8 Gen 3 1 PCIe x8 Gen 3 for a RAID controller 1 PCIe x8 Gen 3 for a flexible integrated NIC * The slot mix changes by installing optional riser cards
Video (VRAM)	Integrated in the server management controller (32 MB)
Network	Flexible integrated NIC plus 1 1000BASE-T for management
Redundant power supply	Optional, hot plug
Redundant cooling fan	Standard, hot plug
Power supplies	460 Watt, 800 Watt, 1000 Watt 100-240 VAC ± 10% 50 / 60 Hz ± 3 Hz
Systems management	EXPRESSSCOPE Engine 3
Interface	2 VGA, 1 to 2 serial, 4 USB 3.0 (plus 1 internal), 2 USB 2.0 (plus 1 internal), Flexible integrated NIC, 1 management LAN
Dimensions (W x D x H) and maximum weight	448.0 x 735.8 x 87.2 mm / 17.6 x 28.9 x 3.4 in 32.3 kg / 71.21 lbs.
Temperature and humidity conditions (non-condensing)	Operating: 5 to 40 °C / 41 to 104 °F or 5 to 45°C / 41 to 113 °F (Optional), 20 to 80% Non-operating: -10 to 55 °C / 14 to 131 °F, 20 to 80%
Operating systems and virtualization software	Microsoft® Windows Server® 2008 R2 Standard / Enterprise Microsoft® Windows Server® 2012 Standard / Datacenter Microsoft® Windows Server® 2012 R2 Standard / Datacenter Red Hat® Enterprise Linux® 6 Red Hat® Enterprise Linux® 7 VMware® ESXi™ 5.5 VMware® ESXi™ 6

Note: For Linux support, visit the NEC website at <http://www.nec.com/en/global/prod/express/linux/>, or contact your sales representative

For further information please contact your local NEC representative or:

Corporate Headquarters (Japan)
NEC Corporation
www.nec.com

North America (USA, Canada)
NEC Corporation of America
www.necam.com

APAC (South Asia, South East Asia, Oceania)
NEC Asia Pacific Pte. Ltd.
sg.nec.com

EMEA (Europe, Middle East, Africa)
NEC Enterprise Solutions
www.nec-enterprise.com