





1. Mechanical Dimensions:




PAD LAYOUT

Notes:

1. Solderability: Leads shall meet MIL-STD-202G, Method 208H for solderability.
2. Flammability: UL94V-0
3. ASTM oxygen index: $> 28\%$
4. Insulation System: Class F 155°C . UL file E151556
5. Operating Temperature Range: All listed parameters are to be within tolerance from -40°C to $+85^{\circ}\text{C}$
6. Storage Temperature Range: -55°C to $+125^{\circ}\text{C}$
7. Aqueous wash compatible
8. SMD Lead Coplanarity: $\pm 0.004'' (0.102\text{mm})$
9. Electrical and mechanical specifications 100% tested
10. RoHS Compliant Component
11. Recommended IR Reflow peak temp of 250C Max
12. Outsourced item processed & controlled under XFMRs QA system

DOC. REV: A/9

2. Schematic:




3. Electrical Specifications: @25°C

Impedance: $60 \text{ Ohms} \pm 20\%$ @25MHz
 Impedance: $96 \text{ Ohms} \pm 20\%$ @100MHz
 DC Res.: 0.90 mOhms Max
 Rated Current: 10Amps

PROPRIETARY

Document is the property of XFMRs Group & is not allowed to be duplicated without authorization.

XFMRs Inc www.XFMRs.com		Title: SURFACE MOUNT BEADS	
UNLESS OTHERWISE SPECIFIED TOLERANCES: N/A Dimensions in MM	P/N: XFBPH-C8-853025		REV. A
	DWN.	Yuan	Jun-09-14
	CHK.	YK Liao	Jun-09-14
SHEET 1 OF 2		APP.	DDC Jun-09-14



DOC. REV: A/9

XFMRs Inc www.XFMRs.com	Title: SURFACE MOUNT BEADS		
	UNLESS OTHERWISE SPECIFIED TOLERANCES: N/A Dimensions in MM		P/N: XFBPH-C8-853025 REV. A
SHEET 2 OF 2	DWN.	Yuan	Jun-09-14
	CHK.	YK Liao	Jun-09-14
	APP.	DDC	Jun-09-14

PROPRIETARY

Document is the property of XFMRs Group & is not allowed to be duplicated without authorization.