


# PoE\* Plus Gigabit Transformer Modules

\*Power over Ethernet



- RoHS reflow temperature rating 245°C
- Meets IEEE 802.3at specification

Electrical Specifications @ 25°C - Operating Temperature -40°C to +125°C



| Part Number               | PoE | Turns Ratio |     | Number of Ports | Insertion Loss (dB Max) |         |         | Return Loss (Zout = 100 Ω ±15%) |        |        |         | Crosstalk (adjacent channels dB MIN) |        |         | Hipot (Vrms MIN) |
|---------------------------|-----|-------------|-----|-----------------|-------------------------|---------|---------|---------------------------------|--------|--------|---------|--------------------------------------|--------|---------|------------------|
|                           |     | Tx          | Rx  |                 | 0.1 MHz                 | 100 MHz | 125 MHz | 30 MHz                          | 60 MHz | 80 MHz | 100 MHz | 30 MHz                               | 60 MHz | 100 MHz |                  |
| H6096NL <sup>2a</sup>     | Yes | 1:1         | 1:1 | 1               | -1.1                    | -1.0    | -2.0    | -18                             | -14.4  | -12    | -10     | -41                                  | -37    | -33     | 1500             |
| HX6096NL <sup>1, 2a</sup> | Yes | 1:1         | 1:1 | 1               | -1.1                    | -1.0    | -2.0    | -18                             | -14.4  | -12    | -10     | -41                                  | -37    | -33     | 1500             |

## Notes:

- HX = Extended temperature version -40°C tp +85°C
- MSL = Moisture Sensitivity Level a=1 b=2 c=3 d=4 e=5
- For Tape & Reel packaging, add a "T" suffix to the end of the part number when ordering, e.g. H6096NLT

## Mechanicals

### H6096NL, HX6096NL



Weight .....1.6 grams  
Tape & Reel .....250/reel  
Tube .....25/tube

Dimensions:  $\frac{\text{Inches}}{\text{mm}}$  Unless otherwise specified, all tolerances are  $\pm \frac{.010}{0.25}$

USA 858 674 8100

Germany 49 7032 7806 0

Singapore 65 6287 8998

Shanghai 86 21 62787060

China 86 755 33966678


Taiwan 886 3 4356768

# PoE\* Plus Gigabit Transformer Modules

\*Power over Ethernet

## Schematic

### H6096NL, HX6096NL



## For More Information

**Pulse Worldwide Headquarters**  
12220 World Trade Drive  
San Diego, CA  
92128  
U.S.A.

Tel: 858 674 8100

**Pulse Europe**  
Einsteinstrasse 1  
D-71083 Herrenberg  
Germany

Tel: 49 7032 7806

**Pulse China Headquarters**  
B402, Shenzhen Academy of  
Aerospace Technology Bldg.  
10th Kejinan Road  
High-Tech Zone  
Nanshan District  
Shenzhen, PR China  
518057

**Pulse North China**  
Room 2704/2705  
Super Ocean Finance Ctr.  
2067 Yan An Road  
West  
Shanghai 200336  
China

**Pulse South Asia**  
135 Joo Seng Road  
#03-02  
PM Industrial Bldg.  
Singapore 368363

Tel: 65 6287 8998  
Fax: 65 6287 8998

**Pulse North Asia**  
3F, No. 198  
Zhongyuan Road  
Zhongli City  
Taoyuan County 320  
Taiwan R. O. C.  
Tel: 886 3 4356768  
Fax: 886 3 4356823  
(Pulse)

Performance warranty of products offered on this data sheet is limited to the parameters specified. Data is subject to change without notice. Other brand and product names mentioned herein may be trademarks or registered trademarks of their respective owners. © Copyright, 2011. Pulse Electronics, Inc. All rights reserved.