

EPA2099 & EPA2099-RC




- Optimized for Universal Line Interface Applications
- Add “-RC” after part number for RoHS Compliant
- Surface Mount in a Small (SOIC) Package
- Operating Temperature : 0°C to +70°C
- 500 Vrms Isolation (Winding to Winding)


Electrical Parameters @ 25°C

Inductance (μ H Min.)	Leakage Inductance (μ H Max.)	Insulation Resistance (Meg Min.)	Cw-w (pF Typ.)	Turns Ratio	DCR (Max.)
@ 100 KHz, 20m Vrms		@ 500 Vdc			
85	0.250	10,000	4.5	1:1:1:1	0.2


Package



Schematics



Typical Impedance Graph



Notes :	EPA2099	EPA2099-RC
1. Lead Finish	SnPb	Hot Tin Dip (Sn) †
2. Peak Temperature Rating	225°C	245°C
3. Moisture Sensitive Levels	MSL = 3 (168 Hours, 30°C/60%RH)	MSL = 4 (72 Hours, 30°C/60%RH)
4. Weight	0.8 grams	0.8 grams
5. Packaging Information	(Tube)	43 pieces/tube
	(Tape & Reel)	500 pieces/13" reel

† Lead Material : Ni Barrier over Cu

Unless Otherwise Specified Dimensions are in Inches /mm ± .010 / .25