



Price\* : 5,432.00 USD



## Main

Product or component type	Circuit breaker
Range of product	PowerPact J
Trip unit technology	Thermal-magnetic
Breaking capacity code	J

## Complementary

Line Rated Current	175 A
Number of poles	3
Poles description	3P
Breaking capacity	100 kA 240 V AC 65 kA 480 V AC 25 kA 600 V AC 20 kA 250 V DC
[Ue] rated operational voltage	600 V AC 250 V DC
Continuous current rating	80 %
Mounting mode	Unit mount
Electrical connection	Busbar connection line Busbar connection load
Magnetic hold current	875 A
Magnetic tripping current	1750 A
Maximum Height	7.52 in (191.01 mm)
Maximum Width	4.12 in (104.65 mm)
Maximum Depth	5 in (127.00 mm)
Tightening torque	230.12 lbf.in (26 N.m) 0.04...0.15 in <sup>2</sup> (25...95 mm <sup>2</sup> ) AWG 4...AWG 4/0

\* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

## Environment

Product certifications	CCC CSA UL Listed CE IEC
Ambient air temperature for operation	104 °F (40 °C)

## Ordering and shipping details

Category	01115-HG,HJ,JG,JJ UNIT MT BREAKER/SWITCH
Discount Schedule	DE2
GTIN	00785901602491
Package weight(Lbs)	4.50 lb(US) (2.041 kg)
Returnability	Yes
Country of origin	US

## Offer Sustainability

Sustainable offer status	Green Premium product
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
PVC free	Yes

## Contractual warranty

Warranty	18 months
----------	-----------