PASTERNACK®
www.pasternack.com

DC Block on Outer Conductor 50 Ohm N Male to N Female Operating From 10 MHz to 18 GHz

TECHNICAL DATA SHEET PE8214

DC Block on Outer Conductor 50 Ohm N Male to N Female Operating From 10 MHz to 18 GHz

Configuration

Design	Outer DC Block
Body Style	Straight
Impedance	50 Ohms
Connector 1	N Male
Connector Specification 1	MIL-STD-348
Connector 2	N Female
Connector Specification 2	MIL-STD-348

Electrical Specifications

Frequency Range, GHz	0.01 to 18
Impedance, Ohms	50
Maximum VSWR	1.35:1
Maximum Insertion Loss, dB	0.6
Maximum Operating Voltage, Vrms	200

Mechanical Specifications

Size

Length, in [mm]	1.91 [48.51]
Width/Dia., in [mm]	0.8 [20.32]

Connector 1

Type	N Male

Connector 2

Type	N Female

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant	Yes

Click the following link (or enter part number in “SEARCH” on website) to obtain additional part information including price, inventory and certifications: DC Block on Outer Conductor 50 Ohm N Male to N Female Operating From 10 MHz to 18 GHz PE8214

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623
Phone: (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451
Sales@Pasternack.com • Techsupport@Pasternack.com

ISO 9001 : 2008 Registered

© 2013 Pasternack Enterprises All Rights Reserved

PASTERNACK®
www.pasternack.com

DC Block on Outer Conductor 50 Ohm N Male to N Female Operating From 10 MHz to 18 GHz

TECHNICAL DATA SHEET PE8214

Plotted and Other Data

Notes: Values at 25 °C, sea level

DC Block on Outer Conductor 50 Ohm N Male to N Female Operating From 10 MHz to 18 GHz from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in “SEARCH” on website) to obtain additional part information including price, inventory and certifications: DC Block on Outer Conductor 50 Ohm N Male to N Female Operating From 10 MHz to 18 GHz PE8214

URL: http://www.pasternack.com/50-ohm-n-outer-dc-block-0.1-18-ghz-pe8214-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623
Phone: (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451
Sales@Pasternack.com • Techsupport@Pasternack.com

ISO 9001 : 2008 Registered

© 2013 Pasternack Enterprises All Rights Reserved

PE8214 CAD Drawing

DC Block on Outer Conductor 50 Ohm N Male to N Female Operating From 10 MHz to 18 GHz



NOTES:
1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.
3. DIMENSIONS ARE IN INCHES [mm].

DWG TITLE **PE8214**

CAD FILE 110812-A | SCALE N/A | SIZE A | 2233

FSCM NO. 53919

PASTERNACK®
Pasternack Enterprises, Inc.
P.O. Box 16759 | Irvine | CA | 92623
Phone: (949) 261-1920 | **Fax:** (949) 261-7451
Website: www.pasternack.com | **E-Mail:** sales@pasternack.com

© 2013 Pasternack Enterprises All Rights Reserved