



# TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,  
Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: [tstsales@mail.taisaw.com](mailto:tstsales@mail.taisaw.com) Web: [www.taisaw.com](http://www.taisaw.com)

## Approval Sheet For Product Specification

Issued Date: Dec, 24, 2008

Product Name: SAW Filter 626 MHz SMD 3.8X3.8 mm

TST Parts No.: TA0962A

Customer Parts No.: \_\_\_\_\_

Company: \_\_\_\_\_

Division: \_\_\_\_\_

Approved by : \_\_\_\_\_

Date: \_\_\_\_\_

Checked by: \_\_\_\_\_ Bob Chau *Bob Chau*

Approval by: \_\_\_\_\_ Francis Chen *FCM*

Date: \_\_\_\_\_ 12, 24, 2008



# TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,

Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: [tstsales@mail.taisaw.com](mailto:tstsales@mail.taisaw.com)

Web: [www.taisaw.com](http://www.taisaw.com)

## SAW Filter 626 MHz

MODEL NO.:TA0962A

REV. NO.:1

### A. MAXIMUM RATING:

1. Input Power Level: 10 dBm
2. DC Voltage : 3V
3. Operating Temperature: -20°C to +75°C
4. Storage Temperature: -40°C to +85°C


RoHS Compliant  
Lead free  
Lead-free soldering

### B. ELECTRICAL CHARACTERISTICS:


| Item                                    | Unit   | Min. | Typ. | Max. | Note |
|-----------------------------------------|--------|------|------|------|------|
| Center Frequency Fc                     | MHz    | -    | 626  | -    | -    |
| Insertion loss (614~638MHz) IL          | dB     | -    | 2.3  | 4.5  | -    |
| Amplitude Ripple (614 ~ 638 MHz)        | dB     | -    | 0.9  | 3    | -    |
| Group Delay Variation (614~638 MHz)     | ns     | -    | 38   | 100  | -    |
| Attenuation (Reference level from 0 dB) |        |      |      |      |      |
| 0 ~ 543 MHz                             | dB     | 35   | 57   | -    | -    |
| 545 ~ 565 MHz                           | dB     | 40   | 57   | -    | -    |
| 668 ~ 690 MHz                           | dB     | 30   | 40   | -    | -    |
| 690 ~ 1000 MHz                          | dB     | 35   | 50   | -    | -    |
| 1000 ~ 1500 MHz                         | dB     | 30   | 44   | -    | -    |
| Temperature Coefficient of Frequency    | Ppm/°C | -    | -35  | -    | -    |

### C. MEASUREMENT CIRCUIT:

HP Network analyzer



## D.OUTLINE DRAWING:



2 : Input


6: Output

1,3,4,5,7,8: Ground



□ : Date Code (W01->A, W02->B,...W52->z)

Unit: mm

## E. PCB Footprint:




F. Frequency Characteristics :




## G. PACKING:

### 1. REEL DIMENSION

(Reel Count : 7''=1000 ; 13''=3000 )



### 2.TAPE DIMENSION



**H. RECOMMENDED REFLOW PROFILE :**

