PTAC210802FC


Thermally-Enhanced High Power RF LDMOS FET
80 W, 28 V, 2110 – 2170 MHz

Description

The PTAC210802FC is an 80-watt LDMOS FET with an asymmetrical design intended for use in multi-standard cellular power amplifier applications in the 2110 to 2170 MHz frequency band. Features include dual-path design, input matching, high gain and thermally-enhanced package with earless flange. Manufactured with Infineon's advanced LDMOS process, this device provides excellent thermal performance and superior reliability.

PTAC210802FC
Package H-37248-4





Features

- Asymmetrical design
  - Main : P1dB = 19 W Typ
  - Peak : P1dB = 60 W Typ
- Broadband internal matching
- Wide video bandwidth
- Typical CW pulsed performance, 2170 MHz, 28 V (Doherty fixture)
  - Output power @ P_{3dB} = 75 W
  - Efficiency = 48%
  - Gain @ P3dB = 14 dB
- Capable of handling 10:1 VSWR @28 V, 80 W (CW) output power
- Integrated ESD protection : Human Body Model, Class 1C (per JESD22-A114)
- Low thermal resistance
- Pb-free and RoHS compliant

RF Characteristics

Two-carrier WCDMA Specifications (tested in Infineon Doherty test fixture)
V_{DD} = 28 V, I_{DQ} = 85 mA, V_{GS1} = 1.3 V, P_{OUT} = 5 W avg, f_1 = 2165 MHz, f_2 = 2175 MHz, 3GPP signal, channel bandwidth = 3.84 MHz, peak/average = 8 dB @ 0.01% CCDF, 10 MHz carrier spacing

Characteristic	Symbol	Min	Typ	Max	Unit
Linear Gain	G_{ps}	15	17	—	dB
Drain Efficiency	η_D	39	43	—	%
Intermodulation Distortion	IMD	—	–31	–26	dBc

All published data at T_{CASE} = 25°C unless otherwise indicated

ESD: Electrostatic discharge sensitive device—observe handling precautions!

DC Characteristics (each side)

Characteristic		Conditions	Symbol	Min	Typ	Max	Unit
Drain-Source Breakdown Voltage		V_{GS} = 0 V, I_{DS} = 10 mA	$V_{(BR)DSS}$	65	—	—	V
Drain Leakage Current		V_{DS} = 28 V, V_{GS} = 0 V	I_{DSS}	—	—	1	µA
		V_{DS} = 63 V, V_{GS} = 0 V	I_{DSS}	—	—	10	µA
On-State Resistance	(main)	V_{GS} = 10 V, V_{DS} = 0.1 V	$R_{DS(on)}$	—	0.6	—	Ω
	(peak)	V_{GS} = 10 V, V_{DS} = 0.1 V	$R_{DS(on)}$	—	0.19	—	Ω
Operating Gate Voltage	(main)	V_{DS} = 28 V, I_{DQ} = 0.1 A	V_{GS}	—	2.6	—	V
Operating Gate Voltage	(peak)	V_{DS} = 28 V, I_{DQ} = 0 A	V_{GS}	—	1.35	—	V
Gate Leakage Current		V_{GS} = 10 V, V_{DS} = 0 V	I_{GSS}	—	—	1	µA

Maximum Ratings


Parameter	Symbol	Value	Unit
Drain-Source Voltage	V_{DSS}	65	V
Gate-Source Voltage	V_{GS}	–6 to +10	V
Operating Voltage	V_{DD}	0 to +32	V
Junction Temperature	T_J	225	°C
Storage Temperature Range	T_{STG}	–65 to +150	°C
Thermal Resistance (main, T_{CASE} = 70°C, 19 W CW)	$R_{\theta JC}$	2.5	°C/W
Thermal Resistance (peak, T_{CASE} = 70°C, 60 W CW)	$R_{\theta JC}$	0.8	°C/W

Ordering Information


Type and Version	Order Code	Package Description	Shipping
PTAC210802FC V1	PTAC210802FCV1XWSA1	H-37248-4, earless flange	Tray
PTAC210802FC V1 R250	PTAC210802FCV1R250XTMA1	H-37248-4, earless flange	Tape & Reel, 250 pcs

Typical Performance (data taken in a production Doherty test fixture)


Two-carrier WCDMA Drive-up
V_{DD} = 28 V, I_{DQ} = 100 mA, V_{GS1} = 1.3 V,
3GPP WCDMA signal, PAR = 8 dB,
10 MHz carrier spacing, BW 3.84 MHz




Two-carrier WCDMA Drive-up
V_{DD} = 28 V, I_{DQ} = 100 mA, V_{GS1} = 1.3 V,
f = 2170 MHz, 3GPP WCDMA signal,
PAR = 8 dB, 10 MHz carrier spacing,
BW 3.84 MHz




Single-carrier WCDMA Drive-up
V_{DD} = 28 V, I_{DQ} = 100 mA, V_{GS1} = 1.3 V
3GPP WCDMA signal, PAR = 10 dB,
BW 3.84 MHz




Single-carrier WCDMA Drive-up
V_{DD} = 28 V, I_{DQ} = 100 mA, V_{GS1} = 1.3 V,
3GPP WCDMA signal, PAR = 10 dB,
BW 3.84 MHz




Typical Performance (cont.)





Load Pull Performance




Main Side Load Pull Performance – Pulsed CW signal: 16 µsec, 10% duty cycle; V_{DD} = 28 V, 100 mA

		P_{1dB}									
		Max Output Power					Max PAE				
Freq [MHz]	Zs [Ω]	Zl [Ω]	Gain [dB]	P_{OUT} [dBm]	P_{OUT} [W]	PAE [%]	Zl [Ω]	Gain [dB]	P_{OUT} [dBm]	P_{OUT} [W]	PAE [%]
2110	28.4 – j28.1	15.1 – j11.9	20.8	43.40	22	50	4.6 – j5.2	23.6	41.3	13	68.1
2140	32.4 – j27.7	7.7 – j10	22.0	43.50	22	61	4.15 – j6	23.9	41.3	13	71.9
2170	45.1 – j33.3	10.8 – j10.6	21.6	43.64	23	58	5.2 – j7.2	23.4	42.1	16	68.6

Peak Side Load Pull Performance – Pulsed CW signal: 16 µsec, 10% duty cycle; V_{DD} = 28 V, V_{GS1} = 1.41 V, Doherty Class C

		P_{3dB}									
		Max Output Power					Max PAE				
Freq [MHz]	Zs [Ω]	Zl [Ω]	Gain [dB]	P_{OUT} [dBm]	P_{OUT} [W]	PAE [%]	Zl [Ω]	Gain [dB]	P_{OUT} [dBm]	P_{OUT} [W]	PAE [%]
2110	14.8 – j14.6	2.4 – j7.4	14.1	49.60	91	62.0	1.6 – j6.0	15.3	48.3	68	72.5
2140	20.6 – j13.6	2.7 – j7.8	14.0	49.50	89	58.8	1.8 – j6.5	15.2	48.7	74	68.5
2170	24.5 – j9.8	2.6 – j8.1	13.9	49.60	91	57.7	2.0 – j6.6	15.3	48.6	72	67.9

Reference Circuit



*Reference circuit assembly diagram (not to scale)**


Reference Circuit Assembly	
DUT	PTAC210802FC
Test Fixture Part No.	LTA/PTAC210802FC
PCB	Rogers 4350, 0.762 mm [0.030"] thick, 2 oz. copper, ε_r = 3.66
Find Gerber files for this test fixture on the Infineon Web site at *http://www.infineon.com/rfpower*	

Reference Circuit (cont.)

Components Information

Component	Description	Suggested Supplier	P/N
Input			
C101, C102, C103, C109	Chip capacitor, 24 pF	ATC	ATC800A240JT250XB
C104, C110	Capacitor, 100 µF	Digi-Key	PCE4442TR-ND
C105, C108	Chip capacitor, 0.1 µF	Digi-Key	399-1267-2-ND
C106, C107	Capacitor, 10 µF	Digi-Key	587-1818-2-ND
R101, R102, R104	Resistor, 10 Ω	Digi-Key	P10GCT-ND
R103	Resistor, 50 Ω	Anaren	C16A50Z4
R105, R106	Resistor, 1000 Ω	Digi-Key	P1.0KECT-ND
S1	Hybrid coupler	Anaren	X3C21P1-03S
Output			
C201, C208, C210, C211	Capacitor, 10 µF	Digi-Key	587-1818-2-ND
C202, C209	Capacitor, 220 µF	Digi-Key	PCE4444TR-ND
C203, C204, C205, C206, C207	Chip capacitor, 24 pF	ATC	ATC800A240JT250XB

Pinout Diagram (top view)



Pin	Description
D1	Drain device 1 (Peak)
D2	Drain device 2 (Main)
G1	Gate device 1 (Peak)
G2	Gate device 2 (Main)
S	Source (flange)

Lead connections for PTAC210802FC

Package Outline Specifications

Package H-37248-4




Diagram Notes—unless otherwise specified:

1. Interpret dimensions and tolerances per ASME Y14.5M-1994.
2. Primary dimensions are mm. Alternate dimensions are inches.
3. All tolerances ± 0.127 [.005] unless specified otherwise.
4. Pins: D1, D2 – drains; G1, G2 – gates; S – source.
5. Lead thickness: 0.10 + 0.076/–0.025 mm [0.004+0.003/–0.001 inch].
6. Gold plating thickness: 1.14 ± 0.38 micron [45 ± 15 microinch].

Find the latest and most complete information about products and packaging at the Infineon Internet page
http://www.infineon.com/rfpower

Revision History

Revision	Date	Data Sheet Type	Page	Subjects (major changes since last revision)
01	2013-06-11	Advance	All	Data Sheet reflects advance specification for product development
01.1	2012-06-12	Advance	2	Updated power level measured for thermal data
02	2013-10-17	Production	All	Data Sheet reflects released product specification
03	2013-12-17	Production	1 2 7	Added ESD classification, revised two-carrier WCDMA Specifications Added operating voltage in Maximum Ratings table Updated package outline
04	2014-05-14	Production	2	Revised juntion temperature in Maximum Ratings table

We Listen to Your Comments

Any information within this document that you feel is wrong, unclear or missing at all?
Your feedback will help us to continuously improve the quality of this document.
Please send your proposal (including a reference to this document) to:

highpowerRF@infineon.com

To request other information, contact us at:
+1 877 465 3667 (1-877-GO-LDMOS) USA
or +1 408 776 0600 International

Edition 2014-05-14

Published by
Infineon Technologies AG
81726 Munich, Germany

© 2014 Infineon Technologies AG
All Rights Reserved.

Legal Disclaimer

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation, warranties of non-infringement of intellectual property rights of any third party.

Information

For further information on technology, delivery terms and conditions and prices, please contact the nearest Infineon Technologies Office (**www.infineon.com/rfpower**).

Warnings

Due to technical requirements, components may contain dangerous substances. For information on the types in question, please contact the nearest Infineon Technologies Office.

Infineon Technologies components may be used in life-support devices or systems only with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support device or system or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.