

2.Cable test condition :

Open / Short : 100%

Insulation resistance : 5M ohms

Contact resistance : 2 ohm

Hipot : DC 300V / 1 sec

3.Each pcs with PE polybag.

1.Wiring Diagram.



NO.	PART NO.	DESCRIPTION	QTY	UNIT/REF
8	BRACKET	BRACKET W/2*USB NICKEL PLATED	1	
7	SCREW	#4-40UNC 2.8*14.1 NICKEL PLATED	4	
6	NUT	HEX NUT #4-40UNC 4.75*1.75 NICKEL PLATED	4	
5	CONN.	USB3.0 20P FEMALE PIN G/F INSULATION BLUE	2	P1
4	PVC	45P PVC BLACK OVERMOLD	50g	
3	PE	LLDPE 500026 6201 INSIDE MOLDING	16g	
2	CONN	USB3.0 A TYPE FEMALE PIN G/F ,SHELL PLATED G/F, INSULATION BLUE	2	P2,P3
1	CABLE	USB3.0 UL2725 (28AWG*1P+D+ALMLY)*2+28AWG*1P+24WG*2C AL+B+D (16/4/0.12AL) OD5.5 BLACK	2	250MM

BILL OF MATERIAL

REV	ECN#	DESCRIPTION	DATE
A		INITAL RELEASE	2016/08/25

CnC Tech,LLC

TITLE: USB3.0 A/F 2 PORT CABLE

DWN NO. 103-1050-BL-00025 REV A

CUSTOMER P/N: REV

DRAWN	EDWINLAI	DATE 08/23/16
CHECKED	Win.C	08/25/16
APPROVAL		

CUSTOMER:

SHEET 1 OF 1