

**Models 7140, 7142, 7148, 7150, 7151, 7152, 7153  
Cable Mounted 1/4" Phone Plugs and Jack**



Model 7140 1/4" Phone Plug 2 Conductor (Mono)



Model 7142 1/4" Phone Plug 3 Conductor (Stereo)



Model 7148 1/4" Phone Jack-Locking (Stereo or Mono)



Model 7150 1/4" Phone Plug 2 Conductor (Mono)-Long Handle



Model 7151 1/4" Phone Plug 2 Conductor (Mono)-Right Angle



Model 7152 1/4" Phone Plug 3 Conductor (Stereo)



Model 7153 1/4" Phone Plug 2 Conductor (Mono)-Large Diameter Cable

Use for optimal audio signal transfer and secure connection.

### Features

- Available in mono and stereo versions
- Two and three conductor versions
- Quick to assemble
- Rugged all metal housing

### Materials

- Body for models, 7140, 7142, 7148, 7151 is diecast zinc alloy with tarnish resistant nickel-plating
- Sturdy strain relief clamp (7140, 7142, 7148): POM.
- Plugs are nickel-plated brass

### Ordering Information

Model: 7140, 7142, 7148, 7150, 7151, 7152, 7153.

### Specifications

| MODEL | WIRE SIZE (AWG)              | O.D.    | POLES                   |
|-------|------------------------------|---------|-------------------------|
| 7140  | 18 AWG / 1 mm <sup>2</sup>   | 4-7 mm  | 2 (Mono)                |
| 7142  | 18 AWG / 1 mm <sup>2</sup>   | 4-7 mm  | 3 (Stereo)              |
| 7148  | 18 AWG / 1 mm <sup>2</sup>   | 4-7 mm  | 2 or 3 (Mono or Stereo) |
| 7150  | 18 AWG / 1 mm <sup>2</sup>   | 12 mm   | 2 (Mono)                |
| 7151  | 18 AWG / 1 mm <sup>2</sup>   | 4-7 mm  | 2 (Mono)                |
| 7152  | 16 AWG / 1.5 mm <sup>2</sup> | 12 mm   | 3 (Stereo)              |
| 7153  | 16 AWG / 1.5 mm <sup>2</sup> | 17.5 mm | 2 (Mono)                |

**USA:** Sales: 800-490-2361 Technical Support: 800-241-2060 Fax: 888-403-3360

**Europe:** 31-(0) 40 2675 150 **International:** 425-446-5500

**e-mail:** [technicalsupport@pomonatest.com](mailto:technicalsupport@pomonatest.com)

**Where to Buy:** [www.pomonaelectronics.com](http://www.pomonaelectronics.com)

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ±.005" (.127 mm). All specifications are to the latest revisions. Specifications are subject to change without notice. Registered trademarks are the property of their respective companies.