



**SPECIFICATION:**  
 Current Rating: 2.0AMP  
 Contact Resistance: 20m Ω (max)  
 Insulation Resistance: 1000M Ω Min at 500V DC  
 Dielectric Strength: 500V AC Per 1 Minute  
 Operating Temperature: -40°C TO +105°C

**MATERIALS:**  
 Insulator: Nylon 6T Glass Fibre (UL 94V-0)  
 Contact: Brass  
 Contact plated: Gold Over Nickel

CONTACTS	PART NO.	A	B	C
10	310-2S-10P 长耳	10.0	25.9	8.0
12	310-2S-12P 长耳	12.0	27.9	10.0
14	310-2S-14P 长耳	14.0	29.9	12.0
16	310-2S-16P 长耳	16.0	31.9	14.0
20	310-2S-20P 长耳	20.0	35.9	18.0
22	310-2S-22P 长耳	22.0	37.9	20.0
24	310-2S-24P 长耳	24.0	39.9	22.0
26	310-2S-26P 长耳	26.0	41.9	24.0
30	310-2S-30P 长耳	30.0	45.9	28.0
32	310-2S-32P 长耳	32.0	47.9	30.0
34	310-2S-34P 长耳	34.0	49.9	32.0
40	310-2S-40P 长耳	40.0	55.9	38.0
44	310-2S-44P 长耳	44.0	59.9	42.0
50	310-2S-50P 长耳	50.0	65.9	48.0

TOLERANCE TABLE

.0	±0.30
.00	±0.20
.000	±0.05

APPROVED:	DATE:	TITLE: 310-2S-XP 长耳			
CHECKED:	DATE:	CLIENT P/N B-3102SXXP-A000			
DRAWN: YAN	DATE: 2011-12-12	UNIT mm	SCALE Free	REV. A	

**深圳市灿科盟实业有限公司**  
 CHANKEMENG INDUSTRY CO., LTD