

USB-C to DisplayPort Adapter Cable (M/M) - 3.1, Gen 1, Locking Connector, 4K @ 60 Hz, 4:4:4, Black, 3 ft.

MODEL NUMBER: U444-003-DP-BE











USB-C to DisplayPort cable directly connects a DP monitor to your MacBook, Chromebook or smartphone's USB-C or Thunderbolt 3 port.

Features

USB-C to DisplayPort Adapter Connects to Your Computer's USB-C or Thunderbolt 3 PortThis USB Type-C to DisplayPort adapter (M/M) connects a DP monitor, projector or television to the USB-C or Thunderbolt 3 port on your desktop computer, tablet, laptop, notebook, MacBook, Chromebook or smartphone. It's an ideal connector for multitasking, presenting video at trade shows and conferences, editing documents, playing online games and watching 4K movies on a larger screen. No other adapter or cable is needed to complete your 4K connection.

Supports USB-C DisplayPort Alternate Mode for Converting Audio/Video SignalsBy connecting the USB-C cable to a source device that supports USB DisplayPort Alt Mode, you can output 4K video and digital audio to a DP monitor, television or projector without installing special software drivers.

Enjoy the Clarity of True 4K Video with Audio and 4:4:4 ColorThis 4K DisplayPort cable supports Ultra HD video resolutions up to 3840 x 2160 (4K x 2K) at 60 Hz for crystal-clear picture and sound. It's compatible with HDCP 2.2 and DisplayPort 1.2 standards for carrying HDR (high dynamic range) signals. It also supports 4:4:4 chroma subsampling for top-level PC gaming or using your HDTV as a PC monitor, as well as 36-bit Deep Color (12 bits per channel). The cable is backward compatible with non-4K displays, so you can use a 1080p monitor if one is available.

Locking DP Connector Helps Prevent Accidental Disconnection and Expensive DowntimeHaving a cable come loose accidentally can mean costly and time-consuming signal loss. The locking DisplayPort connector helps you avoid such danger, protecting your audio/video transmission by maintaining a secure link without failure. The locking cable is also invaluable when moving equipment in a rack or removing equipment from tight areas, ensuring the cord always stays connected.

Reversible USB-C Connector Attaches in Either DirectionUnlike traditional USB cables that connect in only one direction, the reversible USB-C male connector plugs into a USB-C or Thunderbolt 3 port in either direction for a fumble-free connection every time.

Ready to Use Right from the Package, So You Can Plug and Play Immediately The plug-and-play USB Type-C to DisplayPort cable requires no software or external power. Just connect the USB-C plug to the USB-C or Thunderbolt 3 port on a source device that supports USB DisplayPort Alternate Mode, and connect the DP plug to your display. The three-foot USB 3.1 Gen 1 cable is backward compatible with previous USB and DisplayPort generations, so you can use it with legacy equipment.

Highlights

- Converts audio/video signals from sources supporting USB DisplayPort Alt Mode
- Delivers Ultra HD picture quality at resolutions up to 3840 x 2160 (4K x 2K) @ 60 Hz
- Reversible USB-C plug connects in either direction for immediate no-fuss use
- Locking DisplayPort connector prevents cable from coming loose accidentally
- Dual male plugs connect directly to devices—no other adapter or cable is needed

Applications

- Watch 4K video content from a Blu-ray player, game console, laptop or tablet on 2 Ultra HD televisions or projectors
- Connect a Chromebook or MacBook to a conference table's A/V box to give a video presentation on large screens
- Attach two 4K monitors to your
 PC to allow easier multi-tasking
- Play online or PC video games that display optimal graphics

System Requirements

- Source device with USB-C or Thunderbolt 3 port that supports USB DisplayPort Alternate
 Mode
- Display device with DisplayPort input (DisplayPort 1.2 required to achieve 4K @ 60 Hz)



Package Includes

 U444-003-DP-BE USB-C to DisplayPort Adapter, M/M, Black, 3 ft.

Specifications

OVERVIEW		
UPC Code	037332236678	
OPC Code	037332230070	
INPUT		
Cable Length (ft.)	3	
Cable Length (m)	0.9	
Bus Powered	Yes	
BATTERY		
Battery Charging (1.2 Port)	No	
PHYSICAL		
Cable Jacket Rating	VW-1	
Cable Outer Diameter (OD)	4.5mm	
Color	Black	
Material of Construction	PVC and ABS	
Unit Weight (kg)	0.07	
Unit Weight (lbs.)	0.16	
Wire Gauge (AWG)	32/24	
ENVIRONMENTAL		
Operating Temperature Range	32 to 113 F (0 to 45 C)	
Storage Temperature Range	14 to 158 F (-10 to 70 C)	
BTUs	2.1 BTU/Hr	
Power Consumption (Watts)	0.6	
Operating Humidity Range	10% to 85% RH, non-condensing	
Storage Humidity Range	5% to 90% RH, non-condensing	
CONNECTIONS		





Side A - Connector 1	USB Type-C (MALE)	
Side B - Connector 1	DISPLAYPORT (MALE)	
Connector Plating	Nickel	
Contact Plating	Gold	
FEATURES & SPECIFICATIONS		
Max Supported Video Resolution	DP: 3840 X 2160 (4K X 2K) @ 60HZ	
Displayport Specification	1.2	
HDCP Specification	2.2	
USB Specification	USB 3.0 (up to 5 Gbps); USB 3.1 Gen 1 (up to 5 Gbps)	
Driver Required	No	
Technology	DisplayPort; USB 3.1 (Gen 1); USB	
CERTIFICATIONS		
Certifications	CE, FCC, ROHS, REACH	
WARRANTY		
Product Warranty Period (Worldwide)	3-year limited warranty	

© 2019 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies