



PRELIMINARY

SOLID STATE DEVICES, INC

14849 Firestone Boulevard · La Mirada, CA 90638
Phone: (714) 670-SSDI (7734) · Fax: (714) 522-7424

SDR8400S4 thru SDR8400S12

Designer's Data Sheet


FEATURES:

- Forward current to 400 Amps
- PIV to 1200 Volts
- Transient Voltage rating of 200 Volts above PIV
- Pressure contact device
- Single Chip construction
- Low forward voltage drop
- Hermetically sealed
- For High Power applications
- For reverse polarity ad suffix "R"
- Fast Recovery version available (0.7 usec typical)
- Higher Voltage versions up to 5000 volts available
- TX, TXV, and Space Level Screening available

**400 AMPS
400-1200 VOLTS
15μsec**

**STANDARD RECOVERY
HIGH CURRENT RECTIFIER**

DO-8



MAXIMUM RATINGS

RATING (Note 1)	SYMBOL	VALUE	UNIT
Peak Repetitive Reverse and DC Blocking Voltage SDR8400S4 SDR8400S6 SDR8400S8 SDR8400S10 SDR8400S12	VRRM VRWM VR	400 600 800 1000 1200	Volts
Average Rectified Forward Current (Resistive Load, 60Hz, Sine Wave, TA=25°C)	IO	400	Amps
Peak Surge Current (8.3 ms Pulse, Half Sine Wave, TA=25°C)	IFSM	2200	Amps
Operating and storage temperature	Top & Tstg	-55 to +175	°C
Maximum Thermal Resistance Junction to Case	RθJC	0.25	°C/W

NOTE: All specifications are subject to change without notification.
SCD's for these devices should be reviewed by SSDI prior to release.

DATA SHEET#: RP0017 A

RMD

SDR8400S4 thru SDR8400S12

PRELIMINARY




SOLID STATE DEVICES, INC

14849 Firestone Boulevard · La Mirada, CA 90638
Phone: (714) 670-SSDI (7734) · Fax: (714) 522-7424

ELECTRICAL CHARACTERISTICS

CHARACTERISTICS	SYMBOL	MAXIMUM	UNIT
Instantaneous Forward Voltage Drop (IF = 400 Adc pulse, TJ=25°C)	VF	1.55	Vdc
Instantaneous Forward Voltage Drop (IF = 400 Adc pulse, TJ= +175°C)	VF	1.50	Vdc
Reverse Leakage Current (Rated VR pulse, TJ=25°C)	IR	1.5	mA
Reverse Leakage Current (Rated VR pulse, TJ=175°C)	IR	40	mA
Reverse Recovery Time (IFM= 400 A, VR=400V, di/dt= -25μs, Rs=10Ω, Cs=0.5μF, TA=25°C)	trr	15	μsec

CASE OUTLINE: DO-8



DIM	MIN	MAX
A	0.60"	0.65"
B	---	1.6"
C	---	1.675"
D	3.8"	6.0"
E	0.8"	2.2"typ
F	1.031"	1.063"
G	0.050"	0.100"
H	.375-24UNF	
J	0.250"	0.310"
K	0.437"	0.650"

TYPICAL OPERATING CURVES

TA=25°C Unless otherwise specified

