Micro Commercial Components

Micro Commercial Components
20736 Marilla Street Chatsworth
CA 91311
Phone: (818) 701-4933
Fax: (818) 701-4939

MC79L06F

Three-Terminal Low Current Negative Voltage Regulator

Features

- Lead Free Finish/RoHS Compliant ("P" Suffix designates RoHS Compliant. See ordering information)
- Maximum Output current I_O:0.1A
- Internal Short Circuit Current Limiting
- Internal Thermal Overload Protection
- No External Components Required
- Epoxy meets UL 94 V-0 flammability rating
- Moisure Sensitivity Level 1

Absolute Maximum Ratings


Parameter	Symbol	Value	Unit
Input Voltage	V_1	-30	V
Operating Junction Temperature	T_{OPR}	-30---+75	°C
Storage Temperature Range	T_{STG}	-40---+125	°C

Electrical Characteristics(V_i=12V, I_o=40mA, 0 °C <Tj<125 °C, C1=0.33uF, C_o=0.1uF, unless otherwise specified)


Parameter	Sym	Min	Typ	Max	Test conditions
Output Voltage	V_0	-5.76V	-6.0V	-6.24V	Vi=-12V, I_O=40mA
Load Regulation	V_o -I_O		7.0mV	60mV	I_o=1mA-100mA, V_i=-12V
Line regulation	V_o - V_i		15mV	150mV	-8.5V≦V_i≦-20V, I_O=40mA
Quiescent Current	I_q		3.5mA	6.0mA	Vi=-12V, I_O=40mA
Output Noise Voltage	V_N		120μV		10Hz≦f≦100KHz Vi=-12V, I_O=40mA
Ripple Rejection	RR	41dB	71dB		-9V≦V_1≦-19V, I_O=40mA f=120Hz, T_j=25°C e_{IN}=1V_{P-P}

*Note: Bypass Capacitors are recommended for optimum stability and transient response and should be located as close as possible to the regulators

Typical Application:



SOT-89



1. GND
2. IN(Case)
3. OUT

DIMENSINS					
DIM	INCHES		MM		NOTES
	MIN	MAX	MIN	MAX	
A	.173	.181	4.39	4.60	
B	.061	-----	1.55	-----	REF.
C	.154	.165	3.91	4.25	
D	.031	.039	0.80	1.00	
E	.092	.100	2.34	2.54	
F	.118	-----	3.00	-----	TYP
G	.013	.019	0.33	0.48	
H	.015	.021	0.38	0.53	
J	.015	.016	0.38	0.41	
K	.055	.063	1.40	1.60	

Micro Commercial Components

Ordering Information :

Device	Packing
Part Number-TP	Tape&Reel;1Kpcs/Reel

*****IMPORTANT NOTICE*****

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications , enhancements , improvements , or other changes . ***Micro Commercial Components Corp .*** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights ,nor the rights of others . The user of products in such applications shall assume all risks of such use and will agree to hold ***Micro Commercial Components Corp .*** and all the companies whose products are represented on our website, harmless against all damages.

*****LIFE SUPPORT*****

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

*****CUSTOMER AWARENESS*****

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.