

## This document was generated on 09/16/2013 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number:	91813-9010		
Status:			
	Active		
Overview:	KK® Interconnect System		
Description:		al HSG, Glow Wire compatible, 10 Circuits, White, Glow	and the second sec
	Wire Compatible		1111
Documents:			
<u>3D Model</u>		Product Specification PS-99020-0087 (PDF)	
Drawing (PDF)		RoHS Certificate of Compliance (PDF)	
			Series
General			image - Reference only
Product Family		Crimp Housings	
Series		<u>91813</u>	EU RoHS China RoHS
Application		Power, Wire-to-Board	ELV and RoHS
Comments		This Molex product is manufactured from material	Compliant
		that has the following ratings, tested by independent	REACH SVHC
		agencies :. a) A Glow Wire Ignition Temperature (GWIT)	Contains SVHC: No
		of at least 775 deg C per IEC 60695-2-13 b) A Glow	Low-Halogen Status
		Wire Flammability Index (GWFI) above 850 deg C	Not Reviewed
		per IEC 60695-2-12.and hence complies with the	Need more information on product
		requirements set out in the International Standard IEC 60335-1 5th edition - household and similar electrical	environmental compliance?
		appliances - safety; section 30 Resistance to heat	Email productcompliance@molex.com
		and fire. <p><p>The customers using this product</p></p>	For a multiple part number RoHS Certificate of
		must determine its suitability for use in their particular	Compliance, <u>click here</u>
		application through testing or other acceptable means	
		as described in end-product glow-wire flammability	Please visit the Contact Us section for any
		test standard IEC 60695-2-11 and any applicable	non-product compliance questions.
		product end-use standard(s). <p>If it is determined</p>	
		during the customer's evaluation of suitability, that	
		higher performance is required, please contact Molex for	
		possible product options.	Search Parts in this Series
Overview		KK® Interconnect System	<u>91813</u> Series
Product Name		KK®	
UPC		800756783901	Mates With
Distant			KK® Header <u>3003</u> , <u>2599</u>
Physical			
Breakaway		No	Use With
Circuits (maximum)			KK® Crimp Terminal <u>2478</u> , <u>2578</u>
Color - Resin		Natural (White)	
Gender		Female	
Glow-Wire Compliant		Yes	
Material - Resin		Nylon	
Net Weight		2.831/g	
Number of Rows		l Pog	
Packaging Type Panel Mount		Bag No	
Pitch - Mating Interfac		5.08mm	
Pitch - Termination In		5.08mm	
Polarized to Mating P		Yes	
Ports	an	1	
Stackable		No	
Temperature Range -	Operating	See Product Specification	
i omporataro i tange -	Croiding		

Material Info

PS-99020-0087 SD-91813-001

## This document was generated on 09/16/2013 PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION