



## ZWS75B-24





Sales Region	Worldwide
Series	ZWS-B
Status	Production
Feature	
Option	
Option Lineup	Please refer to here.
Recommended EMC Filter	Please refer to here.
Accessories	Please refer to the catalog



Electrical Characteristics		
Input Voltage Range[AC]	85 to 265V	
Input Voltage Range[DC]	120 to 370V	
Efficiency	88% Typ.	
Rated Output Voltage[DC]	24V	
Output Voltage Range[DC]	21.6 to 26.4V	
Maximum Output Current	3.2A	
Maximum Output Power	76.8W	

Cases Shape & Size		
Case' shape	PC board	
Width(W)	50mm Nom.	
Height(H)	33mm Nom.	
Depth(D)	150mm Nom.	
Weight	230g Тур.	

Other			
Operating Temp. Range	-10 to 70°C		
Cooling	Convection cooling		
	UL60950-1		
Sefek Chandend (Carliffed)	CSA C22.2 No.60950-1		
Safety Standard(Certified)	EN60950-1		
	EN50178 (OV II)		
Safety Standard(Conformed)	Den-an		
Demonitor	This page only shows representative characteristics. Please refer to the		
Remarks	technical data for detailed specifications and conditions.		

<sup>!</sup> Images are for reference only and show exemplary products. ! This PDF document was created based on the data listed on the TDK Corporation website.

<sup>!</sup> All specifications are subject to change without notice.