



NOTE:

1.ELECTRICAL CHARACTERISTICS

1-1. CURRENT RATE: 1.0A

1-2. CONTACT RESISTANCE: 100 Milliohms MAX

1-3. INSULATION RESISTANCE: 1,000 Megohms MIN.

1-4. DIELECTRIC WITHSTANDING VOLTAGE: 500V AC FOR 1 MINUTE.

2. RoHS 2002/95/EC COMPLIANT.

ITEM	PAPT NAMF	QTY	MATERIAL	FINISHING
②	Terminal	6	COPPER ALLOY	
①	Housing	1	HI-TEMP.PLASIC UL 94V-0	BLACK

广东星坤科技股份有限公司

生效日期

MARK DESCRIPTION

文件工程章

REVISIONS

www.helloxkb.com www.helloxkb.com www.helloxkb.com

DATE REVISED APPROVED

UNSPECIFIED TOLERANCES

ANGLAR ±5°
L ≤ 4 ±0.2
4 < L ≤ 16 ±0.3
16 < L ≤ 63 ±0.4
L > 63 ±0.5

DSND	DATE	SCALE: N/A	MODEL TYPE:
DWN	DATE	VIEW:	SIM CARD CONN
CHKD	DATE	UNIT: mm/in	PART NO.:
APPD	DATE	SIZE: A4	DWG NO.: XKSIM-005
XKB INDUSTRIAL PRECISION CO., LIMITED			WEIGHT SHEET REVISION
			1.0g 1/1 A0