



Solid State Devices, Inc.

14701 Firestone Blvd * La Mirada, Ca 90638
Phone: (562) 404-4474 * Fax: (562) 404-1773
ssdi@ssdi-power.com * www.ssdi-power.com

SPD9441

Designer's Data Sheet

Part Number/Ordering Information ^{1/}

SPD9441

L Screening ^{2/}

— = Not Screened

TX = TX Level

TXV = TXV

S = S Level

Package Type

— = Axial Leaded

SMS = Surface Mount Square Tab

RADIATION DETECTOR PIN DIODE

FEATURES:

- High Photocurrent Sensitivity
- Linear Output > 4 Decades*
- Fast Rise Time: <20 nsec
- High Reliability Construction
- Hardness to Neutron Bombardment
- Tungsten Pins
- Low Operating Voltage
- Wide Dynamic Range
- Effective Detector of Nuclear and Electromagnetic Radiation (i.e. Gamma Radiation, Electrons, and X-rays)
- Not Restricted to Use at Low Temperatures; Temperature range of -65°C to +200°C
- Replacement for UM9441
- TX, TXV, and S-Level Screening Available ^{2/}

MAXIMUM RATINGS ^{3/}

RATING	SYMBOL	VALUE	UNIT
Peak Repetitive Reverse Voltage DC Blocking Voltage	V_R	100	Volts
Photocurrent	I_P	5	Amps
Operating & Storage Temperature	T_{OP} and T_{STG}	-65 to +200	°C


NOTES:

^{1/} For Ordering Information, Price, and Availability- Contact Factory.


^{2/} Screening Based on MIL-PRF-19500.
Screening Flows Available on Request.

^{3/} Unless Otherwise Specified, All Electrical Characteristics @25°C.

Axial Leaded



Surface Mount Square Tab



NOTE: All specifications are subject to change without notification.
SCD's for these devices should be reviewed by SSDI prior to release.

DATA SHEET #: RC0130A

DOC



Solid State Devices, Inc.

14701 Firestone Blvd * La Mirada, Ca 90638
Phone: (562) 404-4474 * Fax: (562) 404-1773
ssdi@ssdi-power.com * www.ssdi-power.com

SPD9441

ELECTRICAL CHARACTERISTICS ^{3/}

CHARACTERISTICS	SYMBOL	MIN	TYP	MAX	UNIT
Photocurrent, Bias = 50V min 10 ⁶ (RAD(Si)/Sec) Gamma Radiation *Calc.	I_p*	4 4	6 6	-- --	nQ/(RAD(Si) mAdc
Capacitance (VR = 50V, f = 1MHz)	C_J	--	--	11	pF
Reverse Leakage Current (VR = 50Vdc)	I_R	--	--	200	nAdc
Breakdown Voltage (I _r = 100 μA)	BV_R	100	--	--	Vdc


AXIAL

DIMENSIONS

DIM	MIN	MAX
A	---	.200"
B*	---	.300"
C**	.037"	.041"
D	.75"	---


* .175" max special order available.

** .028/.032 special order available.




SMS


DIM	MIN	MAX
A	.195"	.200"
B	---	.350"
C	.019"	.027"
D	.002"	---



TYPICAL PHOTOCURRENT SENSITIVITY



TYPICAL VOLTAGE SENSITIVITY



NOTE: All specifications are subject to change without notification.
SCD's for these devices should be reviewed by SSDI prior to release.

DATA SHEET #: RC0130A

DOC