

Terminal, Compression

by ANDERSON
Catalog ID: VACL2012BN

VERSAtile Aluminum Compression Terminal, 2/0 str AL/CU, 2 H, 1/2"

- Rated at 34.5 KV. UL listed for aluminum or copper conductors. CSA certified.

Product Details

General

Crimp Method	VERSAtile™ (Accomodates Conventional And Anderson Tools)
Die Size	*See Resources / Downloads for die selection and installation instructions
Material	Aluminum Alloy - Tin Plated
Material - Body	Aluminum
Number of Pad Holes	2
Style	Pressed Tubing
UPC	096359334057

Dimensions

Diameter - Pad Bolt	0.5 in
Weight	0.098 lb

Conductor Related

Conductor Compatibility	ACSR-Swan-4-6/1;ACSR-Swanate-4-7/1;ACSR-Sparrow-2-6/1;ACSR-Sparate-2-7/1;ACSR-Robin-1-6/1;ACSR-Raven-1/0-6/1;AAC-Rose-4-7;AAC-Iris-2-7;AAC-Pansy-1-7;AAC-Poppy-1/0-7;AAC-Aster-2/0-7;AAAC 6201 Alloy-Alton-48.69-6/18;AAAC 6201 Alloy-Ames-77.47-6/18;AAAC 6201 Alloy-Azusa-123.3-6/18
Conductor Diameter (VersaCrimp) - Maximum	0.419 in
Conductor Diameter (VersaCrimp) - Minimum	0.232 in

Certifications and Compliance

UL Listed	Yes

Logistics

Carton Quantity	108 EA

For further technical assistance, please contact us

Domestic Customer Service
Hubbell Power Systems
210 N. Allen Centralia, MO 65240 USA
Phone: (573) 682-5521
Fax: (573) 682-8475
Email: hpscs@hubbell.com

International Customer Service
Phone: +1-573-682-5521
Fax: +1-573-682-8516
Email: hpsintlcs@hubbell.com