

PAF500F48-3.3



| | |
|-------------------------------|---|
| Sales Region | Worldwide |
| Series | PAF |
| Status | Production |
| Option | |
| Option Lineup | |
| Recommended EMC Filter | Please refer to here. |
| Accessories | Please refer to the catalog |



Electrical Characteristics

| | |
|--------------------------|------------------------------------|
| Rated Input Voltage[DC] | 48V |
| Input Voltage Range[DC] | 36 to 76V |
| Efficiency | 78% Typ. |
| Rated Output Voltage[DC] | 3.3V |
| Output Voltage Range[DC] | 1.98 to 3.96V |
| Maximum Output Current | |
| Maximum Ripple Noise | 100mV |
| Maximum Output Power | 264W |
| Withstanding Voltage1 | Input - Base plate: 1500VDC: 1min. |
| Withstanding Voltage2 | Input - Output: 1500VDC: 1min. |
| Withstanding Voltage3 | Output - Base plate: 500VDC: 1min. |

Cases Shape & Size

| | |
|------------------------|-----------------------|
| Case'□ shape | On board/Power module |
| Width(W) | 61mm Nom. |
| Height(H) | 12.7mm Nom. |
| Depth(D) | 116.8mm Nom. |
| Weight | 250g Typ. |
| Industry Standard Size | Full brick size |
| Terminal Style | DIP |

Other

| | |
|----------------------------|--|
| Operating Temp. Range | -40 to 100°C |
| Isolated / Non-isolated | Isolated |
| Feature | With baseplate |
| Safety Standard(Certified) | UL60950-1 CSA C22.2 No.60950-1 EN60950-1 |
| Safety Standard(Conformed) | |

